

TERN Ontology Specification

Table of Contents

1. Metadata	10
2. Preamble	10
2.1. Abstract	10
2.2. Normative Status	11
2.3. Normative references	11
2.4. Terms and definitions	11
2.5. Conventions	11
2.5.1. Symbols and abbreviated terms	11
2.5.2. Namespaces	11
2.5.3. Placeholder IRIs	11
2.5.4. RDF serializations	11
3. TERN Ontology Specification	11
3.1. Scope	11
3.2. Standard Parts	12
3.3. Conformance	13
4. Core	14
4.1. Classes	14
4.1.1. Class: tern:Attribute	14
4.1.1.1. Property: dcterms:type	14
4.1.1.2. Property: tern:attribute	15
4.1.1.3. Property: tern:hasSimpleValue	15
4.1.1.4. Property: tern:hasValue	15
4.1.1.5. Property: tern:isAttributeOf	16
4.1.1.6. Property: void:inDataset	16
4.1.1.7. tern:Attribute example	17
4.1.2. Class: tern:Boolean	17
4.1.2.1. Property: rdf:value	18
4.1.3. Class: tern:Date	18
4.1.3.1. Property: rdf:value	18
4.1.4. Class: tern:DateTime	19
4.1.4.1. Property: rdf:value	19
4.1.5. Class: tern:Deployment	19
4.1.5.1. Property: geo:hasGeometry	20
4.1.5.2. Property: sdo:spatial	20
4.1.5.3. Property: ssn:deployedOnPlatform	20
4.1.5.4. Property: ssn:deployedSystem	21

4.1.6. Class: tern:FeatureOfInterest	21
4.1.6.1. Property: tern:featureType	22
4.1.6.2. Property: dcterms:identifier	22
4.1.6.3. Property: dcterms:type	22
4.1.6.4. Property: geo:hasGeometry	23
4.1.6.5. Property: prov:qualifiedAttribution	23
4.1.6.6. Property: prov:wasAttributedTo	24
4.1.6.7. Property: rdfs:comment	24
4.1.6.8. Property: sdo:spatial	25
4.1.6.9. Property: sosa:hasSample	25
4.1.6.10. Property: sosa:isFeatureOfInterestOf	26
4.1.6.11. Property: tern:hasAttribute	26
4.1.6.12. Property: tern:hasSite	26
4.1.6.13. Property: void:inDataset	27
4.1.7. Class: tern:Float	27
4.1.7.1. Property: tern:uncertainty	28
4.1.7.2. Property: rdf:value	28
4.1.7.3. Property: tern:unit	29
4.1.8. Class: tern:IRI	29
4.1.8.1. Property: rdf:value	29
4.1.9. Class: tern:Integer	30
4.1.9.1. Property: tern:uncertainty	30
4.1.9.2. Property: rdf:value	30
4.1.9.3. Property: tern:unit	31
4.1.10. Class: tern:Intervention	31
4.1.10.1. Property: dcterms:identifier	32
4.1.10.2. Property: dcterms:type	32
4.1.10.3. Property: geo:hasGeometry	32
4.1.10.4. Property: prov:endedAtTime	33
4.1.10.5. Property: prov:qualifiedAssociation	33
4.1.10.6. Property: prov:startedAtTime	34
4.1.10.7. Property: prov:wasAssociatedWith	34
4.1.10.8. Property: sdo:spatial	35
4.1.10.9. Property: sosa:hasFeatureOfInterest	35
4.1.10.10. Property: sosa:usedProcedure	36
4.1.10.11. Property: tern:hasAttribute	36
4.1.10.12. Property: tern:interventionType	37
4.1.10.13. Property: void:inDataset	37
4.1.10.14. tern:Intervention example	38
4.1.11. Class: tern:MaterialSample	39
4.1.11.1. Property: dwc:materialSampleID	39

4.1.11.2. Property: tern:hasAttribute	40
4.1.11.3. Property: tern:hasIGSN	40
4.1.12. Class: tern:Observation	40
4.1.12.1. Property: sosa:hasResult	41
4.1.12.2. Property: dcterms:identifier	41
4.1.12.3. Property: dcterms:type	42
4.1.12.4. Property: geo:hasGeometry	42
4.1.12.5. Property: prov:qualifiedAssociation	43
4.1.12.6. Property: prov:wasAssociatedWith	43
4.1.12.7. Property: rdfs:comment	44
4.1.12.8. Property: sdo:spatial	44
4.1.12.9. Property: sosa:hasFeatureOfInterest	44
4.1.12.10. Property: sosa:hasSimpleResult	45
4.1.12.11. Property: sosa:madeBySensor	45
4.1.12.12. Property: sosa:observedProperty	46
4.1.12.13. Property: sosa:phenomenonTime	46
4.1.12.14. Property: tern:resultDateTime	47
4.1.12.15. Property: sosa:usedProcedure	47
4.1.12.16. Property: tern:hasAttribute	48
4.1.12.17. Property: tern:hasSiteVisit	48
4.1.12.18. Property: tern:observationType	49
4.1.12.19. Property: void:inDataset	49
4.1.13. Class: tern:ObservationCollection	50
4.1.13.1. Property: sosa:hasFeatureOfInterest	50
4.1.13.2. Property: sosa:hasMember	50
4.1.13.3. Property: sosa:hasUltimateFeatureOfInterest	51
4.1.13.4. Property: sosa:madeBySensor	52
4.1.13.5. Property: sosa:observedProperty	52
4.1.13.6. Property: sosa:phenomenonTime	52
4.1.13.7. Property: tern:resultDateTime	53
4.1.13.8. Property: sosa:usedProcedure	53
4.1.13.9. Property: tern:hasAttribute	54
4.1.13.10. Property: void:inDataset	54
4.1.14. Class: tern:RDFDataset	55
4.1.14.1. Property: dcterms:contributor	55
4.1.14.2. Property: dcterms:created	56
4.1.14.3. Property: dcterms:creator	56
4.1.14.4. Property: dcterms:date	56
4.1.14.5. Property: dcterms:issued	57
4.1.14.6. Property: dcterms:license	57
4.1.14.7. Property: dcterms:modified	58

4.1.14.8. Property: dcterms:publisher	58
4.1.14.9. Property: dcterms:rightsHolder	59
4.1.14.10. Property: dcterms:source	59
4.1.14.11. Property: dcterms:subject	60
4.1.14.12. Property: void:subset	60
4.1.14.13. Property: dcterms:title	61
4.1.14.14. Property: void:vocabulary	61
4.1.14.15. Property: dcterms:description	62
4.1.14.16. Property: tern:hasAttribute	62
4.1.15. Class: tern:Result	63
4.1.15.1. Property: sosa:isResultOf	63
4.1.15.2. Property: void:inDataset	63
4.1.16. Class: tern:Sample	64
4.1.16.1. Property: sosa:isResultOf	64
Property: Sample's sosa:isSampleOf or tern:hasSite	64
4.1.16.2. Property: tern:hasAttribute	65
4.1.16.3. Property: tern:hasIGSN	65
4.1.17. Class: tern:Sampler	66
4.1.17.1. Property: ssn:implements	66
4.1.17.2. Property: sosa:madeSampling	67
4.1.18. Class: tern:Sampling	67
4.1.18.1. Property: sosa:hasResult	67
4.1.18.2. Property: sosa:madeBySampler	68
4.1.18.3. Property: dcterms:identifier	68
4.1.18.4. Property: dcterms:type	69
4.1.18.5. Property: geo:hasGeometry	69
4.1.18.6. Property: prov:qualifiedAssociation	70
4.1.18.7. Property: prov:wasAssociatedWith	70
4.1.18.8. Property: rdfs:comment	71
4.1.18.9. Property: sdo:spatial	71
4.1.18.10. Property: sosa:hasFeatureOfInterest	72
4.1.18.11. Property: tern:resultDateTime	72
4.1.18.12. Property: sosa:usedProcedure	73
4.1.18.13. Property: tern:hasAttribute	73
4.1.18.14. Property: tern:hasSiteVisit	74
4.1.18.15. Property: tern:samplingType	74
4.1.18.16. Property: void:inDataset	75
4.1.19. Class: tern:Sensor	75
4.1.19.1. Property: ssn:implements	75
4.1.19.2. Property: sosa:madeObservation	76
4.1.19.3. Property: sosa:observes	76

4.1.20. Class: tern:Site	77
4.1.20.1. Property: tern:dimension	77
4.1.20.2. Property: tern:featureType	77
4.1.20.3. Property: tern:hasSiteVisit	78
4.1.20.4. Property: tern:locationProcedure	78
4.1.20.5. Property: geo:sfWithin	79
4.1.20.6. Property: sosa:hasSample	79
4.1.20.7. Property: tern:hasAttribute	80
4.1.20.8. Property: tern:locationDescription	80
4.1.20.9. Property: tern:siteDescription	81
4.1.21. Class: tern:SiteVisit	81
4.1.21.1. Property: dcterms:identifier	81
4.1.21.2. Property: dcterms:type	82
4.1.21.3. Property: tern:hasAttribute	82
4.1.21.4. Property: tern:hasSite	83
4.1.21.5. Property: tern:locationDescription	83
4.1.21.6. Property: tern:siteDescription	84
4.1.22. Class: tern:System	84
4.1.22.1. Property: ssn:hasDeployment	84
4.1.22.2. Property: sosa:isHostedBy	85
4.1.22.3. Property: tern:systemType	85
4.1.22.4. Property: dcat:contactPoint	86
4.1.22.5. Property: dcterms:source	86
4.1.22.6. Property: dcterms:type	87
4.1.22.7. Property: sdo:serialNumber	87
4.1.22.8. Property: skos:altLabel	88
4.1.22.9. Property: skos:exactMatch	88
4.1.22.10. Property: skos:prefLabel	88
4.1.22.11. Property: skos:scopeNote	89
4.1.22.12. Property: ssn:implements	89
4.1.22.13. Property: ssn-system:hasOperatingProperty	90
4.1.22.14. Property: ssn-system:hasSystemCapability	90
4.1.22.15. Property: ssn-system:hasSystemProperty	91
4.1.22.16. Property: tern:hasCalibration	91
4.1.23. Class: tern:Taxon	92
4.1.23.1. Property: dwc:acceptedNameUsage	92
4.1.23.2. Property: dwc:acceptedNameUsageID	92
4.1.23.3. Property: dwc:class	93
4.1.23.4. Property: dwc:cultivarEpithet	93
4.1.23.5. Property: dwc:family	94
4.1.23.6. Property: dwc:genericName	94

4.1.23.7. Property: dwc:genus	95
4.1.23.8. Property: dwc:higherClassification	95
4.1.23.9. Property: dwc:infragenericEpithet	96
4.1.23.10. Property: dwc:infraspecificEpithet	96
4.1.23.11. Property: dwc:kingdom	96
4.1.23.12. Property: dwc:nameAccordingTo	97
4.1.23.13. Property: dwc:nameAccordingToID	97
4.1.23.14. Property: dwc:namePublishedIn	98
4.1.23.15. Property: dwc:namePublishedInID	98
4.1.23.16. Property: dwc:namePublishedInYear	99
4.1.23.17. Property: dwc:nomenclaturalCode	99
4.1.23.18. Property: dwc:nomenclaturalStatus	100
4.1.23.19. Property: dwc:order	100
4.1.23.20. Property: dwc:originalNameUsage	101
4.1.23.21. Property: dwc:originalNameUsageID	101
4.1.23.22. Property: dwc:parentNameUsage	102
4.1.23.23. Property: dwc:parentNameUsageID	102
4.1.23.24. Property: dwc:phylum	102
4.1.23.25. Property: dwc:scientificName	103
4.1.23.26. Property: dwc:scientificNameAuthorship	103
4.1.23.27. Property: dwc:scientificNameID	104
4.1.23.28. Property: dwc:specificEpithet	104
4.1.23.29. Property: dwc:subfamily	105
4.1.23.30. Property: dwc:subgenus	105
4.1.23.31. Property: dwc:taxonConceptID	106
4.1.23.32. Property: dwc:taxonID	106
4.1.23.33. Property: dwc:taxonRank	107
4.1.23.34. Property: dwc:taxonRemarks	107
4.1.23.35. Property: dwc:taxonomicStatus	108
4.1.23.36. Property: dwc:verbatimTaxonRank	108
4.1.23.37. Property: dwc:vernacularName	109
4.1.24. Class: tern:Text	109
4.1.24.1. Property: rdf:value	109
4.1.25. Class: tern:Transect	110
4.1.25.1. Property: tern:hasSiteVisit	110
4.1.25.2. Property: tern:featureType	110
4.1.25.3. Property: geo:hasGeometry	111
4.1.25.4. Property: sdo:spatial	111
4.1.25.5. Property: tern:transectDirection	112
4.1.25.6. Property: tern:transectEndPoint	112
4.1.25.7. Property: tern:transectStartPoint	113

4.1.25.8. Property: <code>sosa:hasSample</code>	113
4.1.26. Class: <code>tern:Value</code>	114
4.1.26.1. Property: <code>tern:unit</code>	114
4.1.26.2. Property: <code>rdf:value</code>	114
4.1.26.3. Property: <code>void:inDataset</code>	115
4.1.27. Class: <code>tern:Calibration</code>	115
4.1.27.1. Property: <code>dcterms:description</code>	115
4.1.27.2. Property: <code>prov:endedAtTime</code>	116
4.1.27.3. Property: <code>prov:startedAtTime</code>	116
4.1.27.4. Property: <code>sosa:usedProcedure</code>	117
4.1.27.5. Property: <code>tern:calibratedBy</code>	117
4.1.27.6. Property: <code>tern:calibratesProperty</code>	118
4.1.27.7. Property: <code>tern:calibrationActualResult</code>	118
4.1.27.8. Property: <code>tern:calibrationOffset</code>	119
4.1.27.9. Property: <code>tern:calibrationReferenceResult</code>	119
4.1.27.10. Property: <code>tern:verifiesCapability</code>	120
4.1.28. Class: <code>tern:IGSN</code>	120
4.1.28.1. Property: <code>geo:hasGeometry</code>	120
4.1.28.2. Property: <code>dcterms:hasPart</code>	121
4.1.28.3. Property: <code>dcterms:isPartOf</code>	121
4.1.28.4. Property: <code>dcterms:publisher</code>	122
4.1.28.5. Property: <code>dcterms:relation</code>	122
4.1.28.6. Property: <code>tern:sampleSubType</code>	123
4.1.28.7. Property: <code>tern:sampleType</code>	123
4.1.29. Class: <code>tern:Input</code>	124
4.1.29.1. Property: <code>dcterms:description</code>	124
4.1.29.2. Property: <code>rdf:value</code>	124
4.1.29.3. Property: <code>rdfs:label</code>	125
4.1.29.4. Property: <code>tern:hasAttribute</code>	125
4.1.29.5. Property: <code>void:inDataset</code>	126
4.1.30. Class: <code>tern:MeasurementRange</code>	126
4.1.30.1. Property: <code>qudt:maxExclusive</code>	126
4.1.30.2. Property: <code>qudt:maxInclusive</code>	127
4.1.30.3. Property: <code>qudt:minExclusive</code>	127
4.1.30.4. Property: <code>qudt:minInclusive</code>	128
4.1.30.5. Property: <code>tern:unit</code>	128
4.1.31. Class: <code>tern:Method</code>	129
4.1.31.1. Property: <code>schema:timeRequired</code>	129
4.1.31.2. Property: <code>skos:note</code>	129
4.1.31.3. Property: <code>tern:hasCategoricalCollection</code>	130
4.1.31.4. Property: <code>tern:hasParameter</code>	130

4.1.31.5. Property: dcterms:source	131
4.1.31.6. Property: tern:instructions	131
4.1.31.7. Property: skos:definition	132
4.1.31.8. Property: tern:equipment	132
4.1.31.9. Property: tern:purpose	133
4.1.31.10. Property: tern:scope	133
4.1.31.11. Property: skos:prefLabel	133
4.1.31.12. Property: tern:undertakenAfter	134
4.1.31.13. Property: tern:undertakenBefore	134
4.1.31.14. Property: tern:undertakenComplementarily	135
4.1.31.15. Property: tern:undertakenConcurrently	135
4.1.32. Class: tern:Platform	136
4.1.32.1. Property: dcterms:description	136
4.1.32.2. Property: geo:hasGeometry	136
4.1.32.3. Property: sdo:spatial	137
4.1.32.4. Property: tern:climateCode	137
4.1.32.5. Property: tern:dateCommissioned	138
4.1.32.6. Property: tern:dateDecommissioned	138
4.1.32.7. Property: tern:platformType	138
4.1.32.8. Property: tern:purpose	139
4.1.33. Class: tern:Procedure	139
4.1.33.1. Property: tern:vocabulary	140
4.1.33.2. Property: ssn:hasInput	140
4.1.33.3. Property: rdf:value	141
4.1.33.4. Property: tern:hasMethod	141
4.1.33.5. Property: void:inDataset	142
4.1.34. Class: tern:RDFDataset	142
4.1.34.1. Property: dcterms:contributor	142
4.1.34.2. Property: dcterms:created	143
4.1.34.3. Property: dcterms:creator	143
4.1.34.4. Property: dcterms:date	144
4.1.34.5. Property: dcterms:issued	144
4.1.34.6. Property: dcterms:license	145
4.1.34.7. Property: dcterms:modified	145
4.1.34.8. Property: dcterms:publisher	145
4.1.34.9. Property: dcterms:rightsHolder	146
4.1.34.10. Property: dcterms:source	146
4.1.34.11. Property: dcterms:subject	147
4.1.34.12. Property: void:subset	147
4.1.34.13. Property: dcterms:title	148
4.1.34.14. Property: void:vocabulary	148

4.1.34.15. Property: dcterms:description	149
4.1.34.16. Property: tern:hasAttribute	149
4.1.35. Class: tern:Survey	150
4.1.35.1. Property: prov:endedAtTime	150
4.1.35.2. Property: prov:qualifiedAssociation	151
4.1.35.3. Property: prov:startedAtTime	151
4.1.35.4. Property: prov:wasAssociatedWith	151
4.1.35.5. Property: void:inDataset	152
4.1.36. Class: tern:VerticalExtent	152
4.1.36.1. Property: tern:maxAltitude	153
4.1.36.2. Property: tern:minAltitude	153
4.1.36.3. Property: tern:unit	154
4.2. External Classes	154
4.2.1. Class: prov:Association	154
4.2.1.1. Property: prov:agent	155
4.2.1.2. Property: prov:hadPlan	155
4.2.1.3. Property: prov:hadRole	156
4.2.1.4. prov:Association example	157
4.2.2. Class: prov:Attribution	158
4.2.2.1. Property: prov:agent	159
4.2.2.2. Property: prov:hadRole	159
4.2.3. Class: time:Duration	160
4.2.3.1. Property: time:numericDuration	160
4.2.3.2. Property: time:unitType	161
4.2.4. Class: time:Instant	161
4.2.4.1. Property: time:inDateTime	162
4.2.4.2. Property: time:inTimePosition	162
4.2.4.3. Property: time:inXSDDate	163
4.2.4.4. Property: time:inXSDDateTimeStamp	163
4.2.4.5. Property: time:inXSDgYear	163
4.2.4.6. Property: time:inXSDgYearMonth	164
4.2.5. Class: time:Interval	164
4.2.5.1. Property: time:hasBeginning	165
4.2.5.2. Property: time:hasDuration	165
4.2.5.3. Property: time:hasEnd	165
5. References	166
Annex A: Specification Parts	166



Status: Draft - while the document is in draft, sections of the document may contain placeholders such as **TBA** and **TBD**.

1. Metadata

IRI	https://w3id.org/tern/profiles/tern/specification
Title	TERN Ontology Specification
Definition	This document lists the normative requirements for data aiming to conform to the TERN Ontology. It is to be used as the authoritative, human-readable list of individual requirements from which profile artefacts such as validators are derived from.
Created	2022-04-06
Modified	2025-06-03
Creator	TERN
Publisher	TERN
License	Creative Commons Attribution 4.0 International (CC BY 4.0)
Alternate document formats	PDF

2. Preamble

2.1. Abstract

The TERN Ontology Specification addresses the data exchange and data representation problems with integrating or exchanging heterogeneous ecological field survey data. The specification combines and profiles multiple internationally-recognised Semantic Web standards and establishes links to informative resources and controlled vocabularies necessary to use the specification.

For many years, the scientific ecological community and industry partners collected rich and insightful data about the land and ecosystems by performing field surveys. Unfortunately, the state of the collected data was often unusable for prompt nationwide reporting and data analysis due to incompatible data storage solutions between non-standardised relational databases, spreadsheets and PDF documents. Without spending further time and money to extract, transform and integrate the data, much of the data's richness and usefulness is lost.

The solution to this problem of an ever-growing set of heterogeneous data is to use existing standards defined by the W3C and follow the Linked Data set of principles. By building a specification based on existing web standards, the richness of the ecological field survey data can now be integrated and queried as one large graph of data on the World Wide Web.

The TERN Ontology Specification is a profile of W3C's SOSA, SSN, SSN-ext and PROV ontologies. It uses these ontologies to describe observations and samplings as kinds of activities on a field survey trip and provides associations of these activities to persons and organisations. The TERN Ontology Specification also uses community-based standards such as OGC's GeoSPARQL to associate spatial features or geometries to things within a field survey trip and QUDT's Units vocabulary for

associating units of measure to results of observations. The TERN Ontology Specification also provides a vast set of TERN-created ecology-based and ecology-related controlled vocabularies to describe observable properties, feature types, instruments and protocol methods. Lastly, the TERN Ontology introduces Site and Site Visit classes to represent survey trips performed on ad-hoc or permanent plots and uses the Attribute class to represent auxiliary information.

2.2. Normative Status

This specification is normative for the TERN Ontology.

2.3. Normative references

2.4. Terms and definitions

2.5. Conventions

2.5.1. Symbols and abbreviated terms

2.5.2. Namespaces

2.5.3. Placeholder IRIs

2.5.4. RDF serializations

3. TERN Ontology Specification

This specification defines the classes and properties of the TERN Ontology and the set of requirements that data validators will use to ensure conformance. This specification also details how data providers should use related ontologies and controlled vocabularies to represent their ecological field survey data. Annex A lists these parts in more detail.

3.1. Scope

The TERN Ontology Specification provides a standardised way to exchange and represent ecological field survey data by defining classes, properties and controlled vocabularies that characterise terrestrial environmental and ecology data. Although the upper ontologies such as SOSA and SSN can theoretically apply to any domain, the TERN Ontology Specification focuses on representing data collected during opportunistic and plot-based field surveys.

Lastly, the TERN Ontology Specification is not concerned with validating data according to specific field survey collection protocols and instead is concerned with validating the structure and coding of the data. Individual data custodians can create a profile of the TERN Ontology Specification and extend it according to their field survey protocol's data collection methodologies by providing more specialised validation and requirements.

3.2. Standard Parts

This specification is one of many resources that make up the TERN Ontology Profile Standard and expresses its structure using the Profiles Vocabulary [PROF]. Each resource in the profile is assigned a role from the [Resource Roles vocabulary](#).

Other resources in the TERN Ontology profile include:

	TERN Ontology - conceptual information model
Description	An overview of the core concepts of the TERN Ontology.
Artifcat	https://linkeddata.tern.org.au/information-models/tern-ontology/conceptual-information-model
Role	role:guidance

	TERN Ontology - cookbook
Description	A cookbook of patterns on representing ecological things with the TERN Ontology.
Artifcat	https://linkeddata.tern.org.au/information-models/tern-ontology/cookbook
Role	role:guidance

	TERN Ontology - classes, properties and shape constraints
Description	A web-based viewer of the TERN Ontology classes, properties and their shape constraints.
Artifcat	https://linkeddata.tern.org.au/viewers/tern-ontology
Role	role:constraints

	TERN Ontology - specification
Description	TERN Ontology specification (<i>this document</i>)
Artifcat	https://linkeddata.tern.org.au/information-models/tern-ontology/specification
Role	role:specification

	TERN Ontology - validator
Description	SHACL shapes for the TERN Ontology.
Artifcat	https://w3id.org/tern/shapes/tern.ttl
Role	role:validator

	TERN Ontology vocabulary - feature types
Description	Feature types controlled vocabulary to describe SOSA-based features of interest.
Artifcat	http://linked.data.gov.au/def/tern-cv/68af3d25-c801-4089-afff-cf701e2bd61d
Role	role:vocabulary

	TERN Ontology vocabulary - observable properties
Description	Observable properties controlled vocabulary to describe SOSA-based observations.
Artifcat	http://linked.data.gov.au/def/tern-cv/5699eca7-9ef0-47a6-bcfb-9306e0e2b85e
Role	role:vocabulary

	TERN Ontology vocabulary - attributes
Description	Attributes controlled vocabulary to describe facts about any entity.
Artifcat	http://linked.data.gov.au/def/tern-cv/dd085299-ae86-4371-ae15-61dfa432f924
Role	role:vocabulary

	TERN Ontology vocabulary - units of measure
Description	Unit of measure controlled vocabulary by QUDT
Artifcat	http://qudt.org/vocab/unit/
Role	role:vocabulary

	TERN Ontology vocabulary - instrument types
Description	Instrument types controlled vocabulary to describe the types of instruments used in observations and sampling acts.
Artifcat	http://linked.data.gov.au/def/tern-cv/a3088b5c-622d-4e25-8a75-4c4961b0dfe8
Role	role:vocabulary

	TERN Ontology vocabulary - site types
Description	Site types controlled vocabulary to describe the types of ecological survey sites.
Artifcat	http://linked.data.gov.au/def/tern-cv/74aa68d3-28fd-468d-8ff5-7e791d9f7159
Role	role:vocabulary

	TERN Ontology vocabulary - CI Role Code
Description	CI Role Code controlled vocabulary to describe the roles available to the TERN Ontology concepts.
Artifcat	http://def.isotc211.org/iso19115/-1/2018/CitationAndResponsiblePartyInformation/code/CI_RoleCode
Role	role:vocabulary

3.3. Conformance

Requirements define the rules and constraints that validators will use to validate data for conformance.

Each requirement will be assigned a subset of the status types defined by the [Registry ontology](#).

Status type	Icon	Definition
experimental	○	An entry that has been accepted into the register temporarily and may be subject to change or withdrawal.
stable	☑	An entry that is seen as having a reasonable measure of stability, may be used to mark the full adoption of a previously 'experimental' entry.

4. Core

This section establishes the core requirements class and provides definitions and usage examples.

4.1. Classes

4.1.1. Class: tern:Attribute

Property	Value
IRI	tern:Attribute
Status	stable ☑
Label	Attribute
Definition	A property-value pair to capture attributes of an individual where observations are not suitable.
Scope note	Follows a similar modelling pattern to schema:PropertyValue.

4.1.1.1. Property: dcterms:type

Property	Value
IRI	dcterms:type
Shape IRI	https://w3id.org/tern/shapes/tern/dcterms-type
Status	stable ☑
Label	type
Definition	Recommended practice is to use a controlled vocabulary such as the DCMI Type Vocabulary DCMI-TYPE . To describe the file format, physical medium, or dimensions of the resource, use the property Format.
Scope note	Useful to capture the proximate class type in situations when <code>rdfs:subClassOf</code> entailment is enabled and <code>rdf:type</code> is not suitable.
Implementation	A <code>dcterms:type</code> predicate <i>MUST</i> have an IRI value.
Cardinality	
Node kind	sh:IRI
Class type	
Expected values	

4.1.1.2. Property: tern:attribute

Property	Value
IRI	<code>tern:attribute</code>
Shape IRI	https://w3id.org/tern/shapes/tern/tern-attribute
Status	stable ☑
Label	attribute
Definition	The identifier of the attribute concept. Attribute concepts are usually described with SKOS controlled vocabularies. TERN manages a list of attributes .
Scope note	
Implementation	A <code>tern:Attribute</code> <i>MUST</i> have exactly 1 <code>tern:attribute</code> predicate where the value node is an IRI.
Cardinality	Exactly 1
Node kind	<code>sh:IRI</code>
Class type	
Expected values	

4.1.1.3. Property: tern:hasSimpleValue

Property	Value
IRI	<code>tern:hasSimpleValue</code>
Shape IRI	https://w3id.org/tern/shapes/tern/tern-hasSimpleValue
Status	stable ☑
Label	has simple value
Definition	The direct link to the IRI or RDF literal value. The simple value <i>MUST</i> be the same value captured in <code>rdf:value</code> of the <code>tern:Value</code> instance.
Scope note	
Implementation	A <code>tern:Attribute</code> <i>MUST</i> have exactly 1 <code>tern:hasSimpleValue</code> predicate where the value node is an IRI or literal.
Cardinality	Exactly 1
Node kind	<code>sh:IRIOrLiteral</code>
Class type	
Expected values	

4.1.1.4. Property: tern:hasValue

Property	Value
IRI	<code>tern:hasValue</code>

Property	Value
Shape IRI	https://w3id.org/tern/shapes/tern/tern-hasValue
Status	stable ☑
Label	has value
Definition	A link to a tern:Value instance which encapsulates the value of this Attribute.
Scope note	
Implementation	A tern:Attribute <i>MUST</i> have exactly 1 tern:hasValue predicate where the value node is an IRI.
Cardinality	Exactly 1
Node kind	sh:BlankNodeOrIRI
Class type	tern:Value
Expected values	

4.1.1.5. Property: tern:isAttributeOf

Property	Value
IRI	tern:isAttributeOf
Shape IRI	https://w3id.org/tern/shapes/tern/tern-isAttributeOf
Status	stable ☑
Label	is attribute of
Definition	A link to the individual which this attribute and its value is applied to. Inverse property of tern:hasAttribute .
Scope note	
Implementation	A tern:isAttributeOf <i>MUST</i> have an IRI value.
Cardinality	
Node kind	sh:IRI
Class type	
Expected values	

4.1.1.6. Property: void:inDataset

Property	Value
IRI	void:inDataset
Shape IRI	https://w3id.org/tern/shapes/tern/void-inDataset
Status	stable ☑
Label	in dataset
Definition	A link to the RDF payload's metadata which this resource was a part of.

Property	Value
Scope note	
Implementation	There <i>MUST</i> exist exactly 1 <code>void:inDataset</code> property with an IRI value to a <code>tern:RDFDataset</code> .
Cardinality	Exactly 1
Node kind	<code>sh:IRI</code>
Class type	<code>tern:RDFDataset</code>
Expected values	

4.1.1.7. `tern:Attribute` example

Annotate the volume of the soil ring using `tern:Attribute`.

```
<urn:example:soil-ring> a tern:Sampler ;
    rdfs:label "soil ring" ;
    ssn:implements <urn:example:method:soil-ring> ;
    tern:systemType <http://linked.data.gov.au/def/tern-cv/24c81cc3-4d68-45a0-91a2-051af25dfb94> ;
    tern:hasAttribute <urn:example:Attribute:1>
.

<urn:example:Attribute:1> a tern:Attribute ;
    rdfs:label "volume of soil ring" ;
    tern:attribute <http://linked.data.gov.au/def/tern-cv/039f87e5-ffd9-4676-b126-c74844d2e095> ;
    tern:hasSimpleValue 209.35 ;
    tern:hasValue [
        a tern:Float ;
        rdf:value 209.35 ;
        tern:unit <http://qudt.org/vocab/unit/CentiM3> ;
    ] ;
.
```

4.1.2. Class: `tern:Boolean`

Property	Value
IRI	<code>tern:Boolean</code>
Status	<code>stable</code> 
Label	Boolean
Definition	Class to encapsulate a true-or-false value.
Scope note	

4.1.2.1. Property: `rdf:value`

Property	Value
IRI	<code>rdf:value</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Boolean-value
Status	stable 
Label	value
Definition	The boolean value.
Scope note	
Implementation	<code>tern:Boolean</code> <i>MUST</i> have exactly 1 <code>rdf:value</code> predicate where the value node is a literal with a datatype of <code>xsd:boolean</code> .
Cardinality	Exactly 1
Node kind	
Class type	<code>xmlschema:boolean</code>
Expected values	- <code>"true"</code> http://www.w3.org/2001/XMLSchema#boolean - <code>"false"</code> http://www.w3.org/2001/XMLSchema#boolean

4.1.3. Class: `tern>Date`

Property	Value
IRI	<code>tern>Date</code>
Status	stable 
Label	Date
Definition	A class to encapsulate an <code>xsd:date</code> value.
Scope note	

4.1.3.1. Property: `rdf:value`

Property	Value
IRI	<code>rdf:value</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Date-value
Status	stable 
Label	value
Definition	The value of the date object.
Scope note	
Implementation	A <code>tern>Date</code> <i>MUST</i> have exactly 1 <code>rdf:value</code> predicate where the value node is a literal with a datatype of <code>xsd:date</code> .
Cardinality	Exactly 1

Property	Value
Node kind	
Class type	<code>xmlschema#date</code>
Expected values	

4.1.4. Class: tern:DateTime

Property	Value
IRI	<code>tern:DateTime</code>
Status	<code>stable</code> 
Label	Date time
Definition	A class to encapsulate an <code>xsd:dateTime</code> value.
Scope note	

4.1.4.1. Property: rdf:value

Property	Value
IRI	<code>rdf:value</code>
Shape IRI	https://w3id.org/tern/shapes/tern/DateTime-value
Status	<code>stable</code> 
Label	value
Definition	The value of the datetime object.
Scope note	
Implementation	A <code>tern:DateTime</code> <i>MUST</i> have exactly 1 <code>rdf:value</code> predicate where the value node is a literal with a datatype of <code>xsd:dateTime</code> .
Cardinality	Exactly 1
Node kind	
Class type	<code>xmlschema#dateTime</code>
Expected values	

4.1.5. Class: tern:Deployment

Property	Value
IRI	<code>tern:Deployment</code>
Status	<code>experimental</code> 
Label	Deployment
Definition	Describes the Deployment of one or more Systems for a particular purpose. Deployment may be done on a Platform.

Property	Value
Scope note	

4.1.5.1. Property: geo:hasGeometry

Property	Value
IRI	geo:hasGeometry
Shape IRI	https://w3id.org/tern/shapes/tern/geo-hasGeometry
Status	stable ☑
Label	has geometry
Definition	A spatial representation for a given feature.
Scope note	
Implementation	A geo:hasGeometry predicate <i>MUST</i> have a blank node or IRI value.
Cardinality	
Node kind	sh:BlankNodeOrIRI
Class type	geosparql#:Geometry
Expected values	

4.1.5.2. Property: sdo:spatial

Property	Value
IRI	sdo:spatial
Shape IRI	https://w3id.org/tern/shapes/tern/sdo-spatial
Status	experimental ○
Label	spatial
Definition	A spatial representation for a given feature.
Scope note	
Implementation	A sdo:spatial predicate <i>MUST</i> have a blank node or IRI value.
Cardinality	
Node kind	sh:BlankNodeOrIRI
Class type	geosparql#:Geometry
Expected values	

4.1.5.3. Property: ssn:deployedOnPlatform

Property	Value
IRI	ssn:deployedOnPlatform
Shape IRI	https://w3id.org/tern/shapes/tern/ssn-deployedOnPlatform

Property	Value
Status	stable ☑
Label	deployed on platform
Definition	Relation between a Deployment and the Platform on which the Systems are deployed.
Scope note	
Implementation	A <code>tern:Deployment</code> MAY have 1 <code>ssh:deployedOnPlatform</code> predicate where the value node is an IRI of type <code>tern:Platform</code> .
Cardinality	Maximum 1
Node kind	<code>sh:IRI</code>
Class type	<code>tern:Platform</code>
Expected values	

4.1.5.4. Property: `ssn:deployedSystem`

Property	Value
IRI	<code>ssn:deployedSystem</code>
Shape IRI	https://w3id.org/tern/shapes/tern/ssn-deployedSystem
Status	stable ☑
Label	deployed system
Definition	Relation between a Deployment and a deployed System.
Scope note	
Implementation	A <code>tern:Deployment</code> MAY have one or many <code>ssn:deployedSystem</code> predicate where the value node is an IRI of type <code>tern:System</code> .
Cardinality	
Node kind	<code>sh:IRI</code>
Class type	<code>tern:System</code>
Expected values	

4.1.6. Class: `tern:FeatureOfInterest`

Property	Value
IRI	<code>tern:FeatureOfInterest</code>
Status	stable ☑
Label	Feature of Interest
Definition	The thing whose property is being estimated or calculated in the course of an Observation to arrive at a Result or whose property is being manipulated by an Actuator, or which is being sampled or transformed in an act of Sampling.

Property	Value
Scope note	

4.1.6.1. Property: tern:featureType

Property	Value
IRI	tern:featureType
Shape IRI	https://w3id.org/tern/shapes/tern/FeatureOfInterest-featureType
Status	stable 
Label	feature type
Definition	The feature type of a tern:FeatureOfInterest from a controlled vocabulary.
Scope note	
Implementation	A tern:FeatureOfInterest <i>MUST</i> have exactly 1 tern:featureType predicate where the value node is an IRI.
Cardinality	Exactly 1
Node kind	sh:IRI
Class type	
Expected values	

4.1.6.2. Property: dcterms:identifier

Property	Value
IRI	dcterms:identifier
Shape IRI	https://w3id.org/tern/shapes/tern/dcterms-identifier
Status	stable 
Label	identifier
Definition	An unambiguous reference to the resource within a given context.
Scope note	
Implementation	N/A
Cardinality	
Node kind	
Class type	
Expected values	

4.1.6.3. Property: dcterms:type

Property	Value
IRI	dcterms:type

Property	Value
Shape IRI	https://w3id.org/tern/shapes/tern/dcterms-type
Status	stable ☑
Label	type
Definition	Recommended practice is to use a controlled vocabulary such as the DCMI Type Vocabulary DCMI-TYPE . To describe the file format, physical medium, or dimensions of the resource, use the property Format.
Scope note	Useful to capture the proximate class type in situations when <code>rdfs:subClassOf</code> entailment is enabled and <code>rdf:type</code> is not suitable.
Implementation	A <code>dcterms:type</code> predicate <i>MUST</i> have an IRI value.
Cardinality	
Node kind	<code>sh:IRI</code>
Class type	
Expected values	

4.1.6.4. Property: `geo:hasGeometry`

Property	Value
IRI	<code>geo:hasGeometry</code>
Shape IRI	https://w3id.org/tern/shapes/tern/geo-hasGeometry
Status	stable ☑
Label	has geometry
Definition	A spatial representation for a given feature.
Scope note	
Implementation	A <code>geo:hasGeometry</code> predicate <i>MUST</i> have a blank node or IRI value.
Cardinality	
Node kind	<code>sh:BlankNodeOrIRI</code>
Class type	<code>geosparql#:Geometry</code>
Expected values	

4.1.6.5. Property: `prov:qualifiedAttribution`

Property	Value
IRI	<code>prov:qualifiedAttribution</code>
Shape IRI	https://w3id.org/tern/shapes/tern/prov-qualifiedAttribution
Status	stable ☑
Label	qualified attribution

Property	Value
Definition	Attribution is the ascribing of an entity to an agent. When an entity <i>e</i> is attributed to agent <i>ag</i> , entity <i>e</i> was generated by some unspecified activity that in turn was associated to agent <i>ag</i> . Thus, this relation is useful when the activity is not known, or irrelevant.
Scope note	
Implementation	A <code>prov:qualifiedAttribution</code> <i>MUST</i> have a blank node or IRI value where the type is <code>prov:Attribution</code> .
Cardinality	
Node kind	<code>sh:BlankNodeOrIRI</code>
Class type	<code>prov#:Attribution</code>
Expected values	

4.1.6.6. Property: `prov:wasAttributedTo`

Property	Value
IRI	<code>prov:wasAttributedTo</code>
Shape IRI	https://w3id.org/tern/shapes/tern/prov-wasAttributedTo
Status	<code>stable</code> ✓
Label	was attributed to
Definition	Attribution is the ascribing of an entity to an agent.
Scope note	
Implementation	A <code>prov:wasAttributedTo</code> predicate <i>MUST</i> have an IRI value of type <code>prov:Agent</code> .
Cardinality	
Node kind	<code>sh:IRI</code>
Class type	<code>prov#:Agent</code>
Expected values	

4.1.6.7. Property: `rdfs:comment`

Property	Value
IRI	<code>rdfs:comment</code>
Shape IRI	https://w3id.org/tern/shapes/tern/rdfs-comment
Status	<code>stable</code> ✓
Label	comment
Definition	A description of the subject resource.
Scope note	
Implementation	An <code>rdfs:comment</code> <i>MUST</i> have a literal value.

Property	Value
Cardinality	
Node kind	sh:Literal
Class type	
Expected values	

4.1.6.8. Property: sdo:spatial

Property	Value
IRI	sdo:spatial
Shape IRI	https://w3id.org/tern/shapes/tern/sdo-spatial
Status	experimental ○
Label	spatial
Definition	A spatial representation for a given feature.
Scope note	
Implementation	A sdo:spatial predicate <i>MUST</i> have a blank node or IRI value.
Cardinality	
Node kind	sh:BlankNodeOrIRI
Class type	geosparql#:Geometry
Expected values	

4.1.6.9. Property: sosa:hasSample

Property	Value
IRI	sosa:hasSample
Shape IRI	https://w3id.org/tern/shapes/tern/sosa-hasSample
Status	stable ☑
Label	has sample
Definition	Relation between a FeatureOfInterest and the Sample used to represent it.
Scope note	
Implementation	A tern:FeatureOfInterest <i>MAY</i> have a sosa:hasSample predicate where the value node is an IRI of type tern:Sample.
Cardinality	
Node kind	
Class type	tern:Sample tern:MaterialSample
Expected values	

4.1.6.10. Property: `sosa:isFeatureOfInterestOf`

Property	Value
IRI	<code>sosa:isFeatureOfInterestOf</code>
Shape IRI	https://w3id.org/tern/shapes/tern/sosa-isFeatureOfInterestOf
Status	stable 
Label	is feature of interest of
Definition	A relation between a <code>FeatureOfInterest</code> and an <code>Observation</code> about it, an <code>Actuation</code> acting on it, or an act of <code>Sampling</code> that sampled it.
Scope note	
Implementation	A <code>tern:FeatureOfInterest</code> <i>MAY</i> have a <code>sosa:isFeatureOfInterestOf</code> predicate where the value node is an IRI of type <code>tern:Observation</code> or <code>tern:Sampling</code> .
Cardinality	
Node kind	
Class type	<code>tern:Observation</code> <code>tern:Sampling</code>
Expected values	

4.1.6.11. Property: `tern:hasAttribute`

Property	Value
IRI	<code>tern:hasAttribute</code>
Shape IRI	https://w3id.org/tern/shapes/tern/tern-hasAttribute
Status	stable 
Label	has attribute
Definition	Link to an <code>Attribute</code> .
Scope note	
Implementation	A <code>tern:hasAttribute</code> predicate <i>MUST</i> have a blank node or an IRI value of type <code>tern:Attribute</code> .
Cardinality	
Node kind	<code>sh:BlankNodeOrIRI</code>
Class type	<code>tern:Attribute</code>
Expected values	

4.1.6.12. Property: `tern:hasSite`

Property	Value
IRI	<code>tern:hasSite</code>

Property	Value
Shape IRI	https://w3id.org/tern/shapes/tern/tern-hasSite
Status	stable ☑
Label	has site
Definition	A property that links, e.g., a FeatureOfInterest to a Site or Transect.
Scope note	
Implementation	A <code>tern:FeatureOfInterest</code> <i>MAY</i> have a <code>tern:hasSite</code> predicate where the value node is an IRI of type <code>tern:Site</code> or <code>tern:Transect</code> .
Cardinality	
Node kind	
Class type	<code>tern:Site</code> <code>tern:Transect</code>
Expected values	

4.1.6.13. Property: void:inDataset

Property	Value
IRI	<code>void:inDataset</code>
Shape IRI	https://w3id.org/tern/shapes/tern/void-inDataset
Status	stable ☑
Label	in dataset
Definition	A link to the RDF payload's metadata which this resource was a part of.
Scope note	
Implementation	There <i>MUST</i> exist exactly 1 <code>void:inDataset</code> property with an IRI value to a <code>tern:RDFDataset</code> .
Cardinality	Exactly 1
Node kind	<code>sh:IRI</code>
Class type	<code>tern:RDFDataset</code>
Expected values	

4.1.7. Class: tern:Float

Property	Value
IRI	<code>tern:Float</code>
Status	stable ☑
Label	Float
Definition	A class to encapsulate a float.

Property	Value
Scope note	

4.1.7.1. Property: tern:uncertainty

Property	Value
IRI	<code>tern:uncertainty</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Float-uncertainty
Status	stable 
Label	uncertainty
Definition	Measurement error ($\pm$).
Scope note	
Implementation	A <code>tern:Float</code> <i>MAY</i> have 1 <code>tern:uncertainty</code> predicate where the value node is a literal with a datatype of <code>xsd:double</code> or <code>xsd:float</code> .
Cardinality	Maximum 1
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#:double</code> <code>xmlschema#:float</code>
Expected values	

4.1.7.2. Property: rdf:value

Property	Value
IRI	<code>rdf:value</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Float-value
Status	stable 
Label	value
Definition	Float value.
Scope note	
Implementation	A <code>tern:Float</code> <i>MUST</i> have exactly 1 <code>rdf:value</code> where the value node is a literal with a datatype of <code>xsd:double</code> or <code>xsd:float</code> .
Cardinality	Exactly 1
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#:double</code> <code>xmlschema#:float</code>
Expected values	

4.1.7.3. Property: tern:unit

Property	Value
IRI	tern:unit
Shape IRI	https://w3id.org/tern/shapes/tern/tern-unit
Status	stable ☑
Label	unit of measure
Definition	The unit of measure of the value. Recommended best practice is to use the QUDT units of measure vocabulary .
Scope note	
Implementation	A tern:unit predicate <i>MUST</i> have an IRI value.
Cardinality	Maximum 1
Node kind	sh:IRI
Class type	
Expected values	

4.1.8. Class: tern:IRI

Property	Value
IRI	tern:IRI
Status	stable ☑
Label	IRI
Definition	A class to encapsulate an IRI value.
Scope note	

4.1.8.1. Property: rdf:value

Property	Value
IRI	rdf:value
Shape IRI	https://w3id.org/tern/shapes/tern/IRI-value
Status	stable ☑
Label	value
Definition	An IRI value.
Scope note	
Implementation	A tern:IRI <i>MUST</i> have exactly 1 rdf:value predicate where the value node is an IRI.
Cardinality	Exactly 1
Node kind	sh:IRI

Property	Value
Class type	
Expected values	

4.1.9. Class: tern:Integer

Property	Value
IRI	tern:Integer
Status	stable 
Label	Integer
Definition	A class to encapsulate an integer value.
Scope note	

4.1.9.1. Property: tern:uncertainty

Property	Value
IRI	tern:uncertainty
Shape IRI	https://w3id.org/tern/shapes/tern/Integer-uncertainty
Status	stable 
Label	uncertainty
Definition	Measurement error ($\pm$).
Scope note	
Implementation	A tern:Integer <i>MAY</i> have 1 tern:uncertainty predicate where the value node is a literal with a datatype of xsd:integer , xsd:double , or xsd:float .
Cardinality	Maximum 1
Node kind	sh:Literal
Class type	xmlschema#:integer xmlschema#:double xmlschema#:float
Expected values	

4.1.9.2. Property: rdf:value

Property	Value
IRI	rdf:value
Shape IRI	https://w3id.org/tern/shapes/tern/Integer-value
Status	stable 
Label	value

Property	Value
Definition	Integer value.
Scope note	
Implementation	A tern:Integer <i>MUST</i> have exactly 1 rdf:value predicate where the value node is a literal with a datatype of xsd:integer
Cardinality	Exactly 1
Node kind	sh:Literal
Class type	xmlschema#:integer
Expected values	

4.1.9.3. Property: tern:unit

Property	Value
IRI	tern:unit
Shape IRI	https://w3id.org/tern/shapes/tern/tern-unit
Status	stable ☑
Label	unit of measure
Definition	The unit of measure of the value. Recommended best practice is to use the QUDT units of measure vocabulary .
Scope note	
Implementation	A tern:unit predicate <i>MUST</i> have an IRI value.
Cardinality	Maximum 1
Node kind	sh:IRI
Class type	
Expected values	

4.1.10. Class: tern:Intervention

Property	Value
IRI	tern:Intervention
Status	experimental ○
Label	Intervention
Definition	An Intervention is a human-induced activity that carries out a Procedure to observe or change the properties of a Feature Of Interest .
Scope note	An intervention is a management process to maintain, restore or improve an ecosystem within a spatial area.

4.1.10.1. Property: `dcterms:identifier`

Property	Value
IRI	<code>dcterms:identifier</code>
Shape IRI	https://w3id.org/tern/shapes/tern/dcterms-identifier
Status	stable 
Label	identifier
Definition	An unambiguous reference to the resource within a given context.
Scope note	
Implementation	N/A
Cardinality	
Node kind	
Class type	
Expected values	

4.1.10.2. Property: `dcterms:type`

Property	Value
IRI	<code>dcterms:type</code>
Shape IRI	https://w3id.org/tern/shapes/tern/dcterms-type
Status	stable 
Label	type
Definition	Recommended practice is to use a controlled vocabulary such as the DCMI Type Vocabulary DCMI-TYPE . To describe the file format, physical medium, or dimensions of the resource, use the property <code>Format</code> .
Scope note	Useful to capture the proximate class type in situations when <code>rdfs:subClassOf</code> entailment is enabled and <code>rdf:type</code> is not suitable.
Implementation	A <code>dcterms:type</code> predicate <i>MUST</i> have an IRI value.
Cardinality	
Node kind	<code>sh:IRI</code>
Class type	
Expected values	

4.1.10.3. Property: `geo:hasGeometry`

Property	Value
IRI	<code>geo:hasGeometry</code>
Shape IRI	https://w3id.org/tern/shapes/tern/geo-hasGeometry

Property	Value
Status	stable ☑
Label	has geometry
Definition	A spatial representation for a given feature.
Scope note	
Implementation	A <code>geo:hasGeometry</code> predicate <i>MUST</i> have a blank node or IRI value.
Cardinality	
Node kind	<code>sh:BlankNodeOrIRI</code>
Class type	<code>geosparql#:Geometry</code>
Expected values	

4.1.10.4. Property: `prov:endedAtTime`

Property	Value
IRI	<code>prov:endedAtTime</code>
Shape IRI	https://w3id.org/tern/shapes/tern/prov-endedAtTime
Status	stable ☑
Label	ended at time
Definition	The time at which an activity ended.
Scope note	
Implementation	A <code>tern:Survey</code> , <code>tern:SiteVisit</code> or a <code>tern:Intervention</code> <i>MAY</i> have a maximum of 1 <code>prov:endedAtTime</code> predicate where the value node is a literal with the datatype <code>xsd:dateTime</code> .
Cardinality	Maximum 1
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#:dateTime</code>
Expected values	

4.1.10.5. Property: `prov:qualifiedAssociation`

Property	Value
IRI	<code>prov:qualifiedAssociation</code>
Shape IRI	https://w3id.org/tern/shapes/tern/prov-qualifiedAssociation
Status	stable ☑
Label	qualified association

Property	Value
Definition	An activity association is an assignment of responsibility to an agent for an activity, indicating that the agent had a role in the activity. It further allows for a plan to be specified, which is the plan intended by the agent to achieve some goals in the context of this activity.
Scope note	
Implementation	A <code>prov:qualifiedAssociation</code> <i>MUST</i> have a blank node or IRI value of type <code>prov:Association</code> .
Cardinality	
Node kind	<code>sh:BlankNodeOrIRI</code>
Class type	<code>prov#:Association</code>
Expected values	

4.1.10.6. Property: `prov:startedAtTime`

Property	Value
IRI	<code>prov:startedAtTime</code>
Shape IRI	https://w3id.org/tern/shapes/tern/prov-startedAtTime
Status	stable ☑
Label	started at time
Definition	The time at which an activity started.
Scope note	
Implementation	A <code>tern:Survey</code> , <code>tern:SiteVisit</code> or a <code>tern:Intervention</code> <i>MUST</i> have exactly 1 <code>prov:startedAtTime</code> predicate where the value node is a literal with the datatype <code>xsd:dateTime</code> .
Cardinality	Exactly 1
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#:dateTime</code>
Expected values	

4.1.10.7. Property: `prov:wasAssociatedWith`

Property	Value
IRI	<code>prov:wasAssociatedWith</code>
Shape IRI	https://w3id.org/tern/shapes/tern/prov-wasAssociatedWith
Status	stable ☑
Label	was associated with

Property	Value
Definition	An activity association is an assignment of responsibility to an agent for an activity, indicating that the agent had a role in the activity. It further allows for a plan to be specified, which is the plan intended by the agent to achieve some goals in the context of this activity.
Scope note	
Implementation	A <code>prov:wasAssociatedWith</code> predicate <i>MUST</i> an IRI value of type <code>prov:Agent</code> or <code>sdo:Person</code> .
Cardinality	
Node kind	
Class type	<code>prov#:Agent</code> <code>schema.org:Person</code>
Expected values	

4.1.10.8. Property: sdo:spatial

Property	Value
IRI	<code>sdo:spatial</code>
Shape IRI	https://w3id.org/tern/shapes/tern/sdo-spatial
Status	<code>experimental</code> ○
Label	spatial
Definition	A spatial representation for a given feature.
Scope note	
Implementation	A <code>sdo:spatial</code> predicate <i>MUST</i> have a blank node or IRI value.
Cardinality	
Node kind	<code>sh:BlankNodeOrIRI</code>
Class type	<code>geosparql#:Geometry</code>
Expected values	

4.1.10.9. Property: sosa:hasFeatureOfInterest

Property	Value
IRI	<code>sosa:hasFeatureOfInterest</code>
Shape IRI	https://w3id.org/tern/shapes/tern/sosa-hasFeatureOfInterest
Status	<code>stable</code> ☑
Label	has feature of interest

Property	Value
Definition	A relation between an Observation and the entity whose quality was observed, or between an Actuation and the entity whose property was modified, or between an act of Sampling and the entity that was sampled.
Scope note	
Implementation	Exactly 1 <code>sosa:hasFeatureOfInterest</code> predicate <i>MUST</i> exist_ with an IRI value.
Cardinality	Exactly 1
Node kind	
Class type	<code>tern:FeatureOfInterest</code> <code>tern:Sample</code> <code>tern:MaterialSample</code> <code>tern:Site</code> <code>tern:Transect</code>
Expected values	

4.1.10.10. Property: `sosa:usedProcedure`

Property	Value
IRI	<code>sosa:usedProcedure</code>
Shape IRI	https://w3id.org/tern/shapes/tern/sosa-usedProcedure
Status	stable 
Label	used procedure
Definition	A relation to link to a re-usable Procedure used in making an Observation, an Actuation, or a Sample, typically through a Sensor, Actuator or Sampler.
Scope note	
Implementation	Exactly 1 <code>sosa:usedProcedure</code> <i>MUST</i> exist where the value node is a <code>tern:Method</code> or <code>tern:Procedure</code> .
Cardinality	Exactly 1
Node kind	
Class type	<code>tern:Procedure</code> <code>tern:Method</code>
Expected values	

4.1.10.11. Property: `tern:hasAttribute`

Property	Value
IRI	<code>tern:hasAttribute</code>
Shape IRI	https://w3id.org/tern/shapes/tern/tern-hasAttribute
Status	stable 

Property	Value
Label	has attribute
Definition	Link to an Attribute.
Scope note	
Implementation	A tern:hasAttribute predicate <i>MUST</i> have a blank node or an IRI value of type tern:Attribute .
Cardinality	
Node kind	sh:BlankNodeOrIRI
Class type	tern:Attribute
Expected values	

4.1.10.12. Property: **tern:interventionType**

Property	Value
IRI	tern:interventionType
Shape IRI	https://w3id.org/tern/shapes/tern/tern-interventionType
Status	experimental ○
Label	intervention type
Definition	The type of intervention.
Scope note	
Implementation	A tern:Intervention <i>MAY</i> have a maximum of 1 tern:interventionType predicate where the value node is an IRI.
Cardinality	Maximum 1
Node kind	sh:IRI
Class type	
Expected values	

4.1.10.13. Property: **void:inDataset**

Property	Value
IRI	void:inDataset
Shape IRI	https://w3id.org/tern/shapes/tern/void-inDataset
Status	stable ☑
Label	in dataset
Definition	A link to the RDF payload's metadata which this resource was a part of.
Scope note	

Property	Value
Implementation	There <i>MUST</i> exist exactly 1 <code>void:inDataset</code> property with an IRI value to a <code>tern:RDFDataset</code> .
Cardinality	Exactly 1
Node kind	<code>sh:IRI</code>
Class type	<code>tern:RDFDataset</code>
Expected values	

4.1.10.14. tern:Intervention example

The following example is based on the [DCCEEW's RLP protocols](#) for intervention.

Definition of intervention within the field survey protocol context:

An intervention is a management process to maintain, restore or improve an ecosystem within a spatial area. Interventions can take a range of forms, including fencing to protect remnant vegetation (Spooner et al. 2002), weed and pest animal control (Martin and van Klinken 2006; Reddiex et al. 2006), restoration and revegetation, re-introductions or translocations (Silcock et al. 2019), removal of watering points, controlled burns, nest box installation and community or landholder workshops (Capon et al. 2020).

— Interventions Module, McCallum K, Laws M, Bignall J, O'Neill S, Sparrow B. (unpublished draft)
 'Interventions module' in (eds) Ecological Field Monitoring Protocols Manual: Standardising environmental monitoring and data systems for improved decision making. Draft v 0.1 Report to DAWE. TERN, Adelaide.

4.1.10.14.1. Debris removal

The RLP field survey protocols define a number of interventions in a table. Below shows one example taken from the field survey protocols for *debris removal*.

All RLP field survey interventions have *inputs* and *outputs*. Inputs are modelled as `tern:Attribute` class instances and outputs are modelled as `tern:Observation` class instances. The `tern:interventionType` property links to a *global* concept within TERN's controlled vocabularies for *debris removal* and the `sosa:usedProcedure` links to the *local* protocol-specific version of *debris removal*. The spatial extent is recorded digitally as a polygon feature in the data input app and is captured here with the `geo:hasGeometry` property pointing to a description of the polygon as an instance of `geo:Geometry`. The actual coordinates of the polygon are recorded on the geometry object with the property `geo:asWKT`. Each one of the input fields are recorded as a `tern:Attribute` linked to the intervention activity via the property `tern:hasAttribute`. Each individual outcome is also recorded as a `tern:Attribute`. Observations that are made after the intervention can be linked using the `prov:wasInformedBy` property to express that the observational result was affected by a past intervention activity.

RLP interventions table headers

Project Service	Field Collection	App Group	Output Measure	Mapping Requirements	Mapping Area (ha)	Reporting Fields	Data Field Class	Schema	Comment RLP	Comment TERN
-----------------	------------------	-----------	----------------	----------------------	-------------------	------------------	------------------	--------	-------------	--------------

Debris removal table

[debris removal table]

Diagram modelling debris removal with the Intervention class

[intervention example debris removal]

Other interventions are described in the original document at [MERIT Ready Reckoner V3 Regional Land Partnerships – Project Services](#).

4.1.11. Class: tern:MaterialSample

Property	Value
IRI	<code>tern:MaterialSample</code>
Status	<code>stable</code> ☑
Label	Material sample
Definition	A physical result of a sampling (or subsampling) event. In biological collections, the material sample is typically collected, and either preserved or destructively processed.
Scope note	

4.1.11.1. Property: dwc:materialSampleID

Property	Value
IRI	<code>dwc:materialSampleID</code>
Shape IRI	https://w3id.org/tern/shapes/tern/dwc-materialSampleID
Status	<code>stable</code> ☑
Label	material sample ID
Definition	An identifier for the MaterialSample (as opposed to a particular digital record of the material sample). In the absence of a persistent global unique identifier, construct one from a combination of identifiers in the record that will most closely make the materialSampleID globally unique.
Scope note	
Implementation	A <code>dwc:materialSampleID</code> predicate <i>MUST</i> have a literal value or IRI value.
Cardinality	
Node kind	<code>sh:IRIOrLiteral</code>
Class type	

Property	Value
Expected values	

4.1.11.2. Property: tern:hasAttribute

Property	Value
IRI	tern:hasAttribute
Shape IRI	https://w3id.org/tern/shapes/tern/tern-hasAttribute
Status	stable 
Label	has attribute
Definition	Link to an Attribute.
Scope note	
Implementation	A tern:hasAttribute predicate <i>MUST</i> have a blank node or an IRI value of type tern:Attribute .
Cardinality	
Node kind	sh:BlankNodeOrIRI
Class type	tern:Attribute
Expected values	

4.1.11.3. Property: tern:hasIGSN

Property	Value
IRI	tern:hasIGSN
Shape IRI	https://w3id.org/tern/shapes/tern/tern-hasIGSN
Status	experimental 
Label	has IGSN
Definition	Relation between a Sample and an IGSN.
Scope note	
Implementation	A tern:Sample or tern:MaterialSample <i>MUST</i> have exactly 1 tern:hasIGSN predicate where the value node is an IRI of type tern:IGSN .
Cardinality	Exactly 1
Node kind	
Class type	tern:IGSN
Expected values	

4.1.12. Class: tern:Observation

Property	Value
IRI	tern:Observation
Status	stable 
Label	Observation
Definition	Act of carrying out an (Observation) Procedure to estimate or calculate a value of a property of a FeatureOfInterest . Links to a Sensor to describe what made the Observation and how; links to an ObservableProperty to describe what the result is an estimate of, and to a FeatureOfInterest to detail what that property was associated with.
Scope note	

4.1.12.1. Property: [sosa:hasResult](#)

Property	Value
IRI	sosa:hasResult
Shape IRI	https://w3id.org/tern/shapes/tern/Observation-hasResult
Status	stable 
Label	has result
Definition	Relation linking an Observation or Actuation or act of Sampling and a Result or Sample.
Scope note	
Implementation	A tern:Observation <i>MUST</i> have exactly 1 sosa:hasResult where the value node is a blank node or IRI of type tern:Value .
Cardinality	Exactly 1
Node kind	sh:BlankNodeOrIRI
Class type	tern:Value
Expected values	

4.1.12.2. Property: [dcterms:identifier](#)

Property	Value
IRI	dcterms:identifier
Shape IRI	https://w3id.org/tern/shapes/tern/dcterms-identifier
Status	stable 
Label	identifier
Definition	An unambiguous reference to the resource within a given context.
Scope note	
Implementation	N/A

Property	Value
Cardinality	
Node kind	
Class type	
Expected values	

4.1.12.3. Property: `dcterms:type`

Property	Value
IRI	<code>dcterms:type</code>
Shape IRI	https://w3id.org/tern/shapes/tern/dcterms-type
Status	stable 
Label	type
Definition	Recommended practice is to use a controlled vocabulary such as the DCMI Type Vocabulary DCMI-TYPE . To describe the file format, physical medium, or dimensions of the resource, use the property Format.
Scope note	Useful to capture the proximate class type in situations when <code>rdfs:subClassOf</code> entailment is enabled and <code>rdf:type</code> is not suitable.
Implementation	A <code>dcterms:type</code> predicate <i>MUST</i> have an IRI value.
Cardinality	
Node kind	<code>sh:IRI</code>
Class type	
Expected values	

4.1.12.4. Property: `geo:hasGeometry`

Property	Value
IRI	<code>geo:hasGeometry</code>
Shape IRI	https://w3id.org/tern/shapes/tern/geo-hasGeometry
Status	stable 
Label	has geometry
Definition	A spatial representation for a given feature.
Scope note	
Implementation	A <code>geo:hasGeometry</code> predicate <i>MUST</i> have a blank node or IRI value.
Cardinality	
Node kind	<code>sh:BlankNodeOrIRI</code>
Class type	<code>geosparql#:Geometry</code>

Property	Value
Expected values	

4.1.12.5. Property: prov:qualifiedAssociation

Property	Value
IRI	<code>prov:qualifiedAssociation</code>
Shape IRI	https://w3id.org/tern/shapes/tern/prov-qualifiedAssociation
Status	stable 
Label	qualified association
Definition	An activity association is an assignment of responsibility to an agent for an activity, indicating that the agent had a role in the activity. It further allows for a plan to be specified, which is the plan intended by the agent to achieve some goals in the context of this activity.
Scope note	
Implementation	A <code>prov:qualifiedAssociation</code> <i>MUST</i> have a blank node or IRI value of type <code>prov:Association</code> .
Cardinality	
Node kind	<code>sh:BlankNodeOrIRI</code>
Class type	<code>prov#:Association</code>
Expected values	

4.1.12.6. Property: prov:wasAssociatedWith

Property	Value
IRI	<code>prov:wasAssociatedWith</code>
Shape IRI	https://w3id.org/tern/shapes/tern/prov-wasAssociatedWith
Status	stable 
Label	was associated with
Definition	An activity association is an assignment of responsibility to an agent for an activity, indicating that the agent had a role in the activity. It further allows for a plan to be specified, which is the plan intended by the agent to achieve some goals in the context of this activity.
Scope note	
Implementation	A <code>prov:wasAssociatedWith</code> predicate <i>MUST</i> an IRI value of type <code>prov:Agent</code> or <code>sdo:Person</code> .
Cardinality	
Node kind	

Property	Value
Class type	<code>prov#:Agent</code> <code>schema.org:Person</code>
Expected values	

4.1.12.7. Property: `rdfs:comment`

Property	Value
IRI	<code>rdfs:comment</code>
Shape IRI	https://w3id.org/tern/shapes/tern/rdfs-comment
Status	<code>stable</code> ☑
Label	comment
Definition	A description of the subject resource.
Scope note	
Implementation	An <code>rdfs:comment</code> <i>MUST</i> have a literal value.
Cardinality	
Node kind	<code>sh:Literal</code>
Class type	
Expected values	

4.1.12.8. Property: `sdo:spatial`

Property	Value
IRI	<code>sdo:spatial</code>
Shape IRI	https://w3id.org/tern/shapes/tern/sdo-spatial
Status	<code>experimental</code> ○
Label	spatial
Definition	A spatial representation for a given feature.
Scope note	
Implementation	A <code>sdo:spatial</code> predicate <i>MUST</i> have a blank node or IRI value.
Cardinality	
Node kind	<code>sh:BlankNodeOrIRI</code>
Class type	<code>geosparql#:Geometry</code>
Expected values	

4.1.12.9. Property: `sosa:hasFeatureOfInterest`

Property	Value
IRI	sosa:hasFeatureOfInterest
Shape IRI	https://w3id.org/tern/shapes/tern/sosa-hasFeatureOfInterest
Status	stable 
Label	has feature of interest
Definition	A relation between an Observation and the entity whose quality was observed, or between an Actuation and the entity whose property was modified, or between an act of Sampling and the entity that was sampled.
Scope note	
Implementation	Exactly 1 sosa:hasFeatureOfInterest predicate <i>MUST</i> exist_ with an IRI value.
Cardinality	Exactly 1
Node kind	
Class type	tern:FeatureOfInterest tern:Sample tern:MaterialSample tern:Site tern:Transect
Expected values	

4.1.12.10. Property: [sosa:hasSimpleResult](#)

Property	Value
IRI	sosa:hasSimpleResult
Shape IRI	https://w3id.org/tern/shapes/tern/sosa-hasSimpleResult
Status	stable 
Label	has simple result
Definition	The simple value of an Observation or Actuation or act of Sampling.
Scope note	
Implementation	Exactly 1 sosa:hasSimpleResult predicate <i>MUST</i> exist where the value node is an IRI or literal.
Cardinality	Exactly 1
Node kind	
Class type	
Expected values	

4.1.12.11. Property: [sosa:madeBySensor](#)

Property	Value
IRI	sosa:madeBySensor
Shape IRI	https://w3id.org/tern/shapes/tern/sosa-madeBySensor
Status	stable 
Label	made by sensor
Definition	Relation between an Observation and the Sensor which made the Observations.
Scope note	
Implementation	A sosa:madeBySensor predicate <i>MAY</i> exist where the value node is an IRI.
Cardinality	Maximum 1
Node kind	sh:IRI
Class type	tern:Sensor
Expected values	

4.1.12.12. Property: [sosa:observedProperty](#)

Property	Value
IRI	sosa:observedProperty
Shape IRI	https://w3id.org/tern/shapes/tern/sosa-observedProperty
Status	stable 
Label	observed property
Definition	Relation linking an Observation to the property that was observed. The ObservableProperty should be a property of the FeatureOfInterest (linked by hasFeatureOfInterest) of this Observation.
Scope note	
Implementation	A tern:Observation <i>MUST</i> have exactly 1 sosa:observedProperty where the value node is an IRI.
Cardinality	Exactly 1
Node kind	sh:IRI
Class type	
Expected values	

4.1.12.13. Property: [sosa:phenomenonTime](#)

Property	Value
IRI	sosa:phenomenonTime
Shape IRI	https://w3id.org/tern/shapes/tern/sosa-phenomenonTime
Status	stable 

Property	Value
Label	phenomenon time
Definition	The time that the Result of an Observation, Actuation or Sampling applies to the FeatureOfInterest. Not necessarily the same as the resultTime. May be an Interval or an Instant, or some other compound TemporalEntity.
Scope note	
Implementation	Exactly 1 <code>sosa:phenomenonTime</code> predicate <i>MUST</i> exist where the value node is a blank node or IRI of type <code>time:Instant</code> .
Cardinality	Exactly 1
Node kind	<code>sh:BlankNodeOrIRI</code>
Class type	<code>time#:Instant</code>
Expected values	

4.1.12.14. Property: `tern:resultDateTime`

Property	Value
IRI	<code>tern:resultDateTime</code>
Shape IRI	https://w3id.org/tern/shapes/tern/sosa-resultTime
Status	<code>stable</code> 
Label	result date time
Definition	The result time is the instant of time when the Observation, Actuation or Sampling activity was completed.
Scope note	
Implementation	A <code>tern:resultDateTime</code> predicate <i>MUST</i> have a literal value where the datatype is an <code>xsd:date</code> , <code>xsd:dateTime</code> or <code>xsd:dateTimeStamp</code> .
Cardinality	Exactly 1
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#:dateTime</code> <code>xmlschema#:date</code> <code>xmlschema#:dateTimeStamp</code>
Expected values	

4.1.12.15. Property: `sosa:usedProcedure`

Property	Value
IRI	<code>sosa:usedProcedure</code>
Shape IRI	https://w3id.org/tern/shapes/tern/sosa-usedProcedure
Status	<code>stable</code> 

Property	Value
Label	used procedure
Definition	A relation to link to a re-usable Procedure used in making an Observation, an Actuation, or a Sample, typically through a Sensor, Actuator or Sampler.
Scope note	
Implementation	Exactly 1 <code>sosa:usedProcedure</code> <i>MUST</i> exist where the value node is a <code>tern:Method</code> or <code>tern:Procedure</code> .
Cardinality	Exactly 1
Node kind	
Class type	<code>tern:Procedure</code> <code>tern:Method</code>
Expected values	

4.1.12.16. Property: `tern:hasAttribute`

Property	Value
IRI	<code>tern:hasAttribute</code>
Shape IRI	https://w3id.org/tern/shapes/tern/tern-hasAttribute
Status	stable ☑
Label	has attribute
Definition	Link to an Attribute.
Scope note	
Implementation	A <code>tern:hasAttribute</code> predicate <i>MUST</i> have a blank node or an IRI value of type <code>tern:Attribute</code> .
Cardinality	
Node kind	<code>sh:BlankNodeOrIRI</code>
Class type	<code>tern:Attribute</code>
Expected values	

4.1.12.17. Property: `tern:hasSiteVisit`

Property	Value
IRI	<code>tern:hasSiteVisit</code>
Shape IRI	https://w3id.org/tern/shapes/tern/tern-hasSiteVisit
Status	stable ☑
Label	has site visit
Definition	A property that links, e.g., a Site to a Site Visit.
Scope note	

Property	Value
Implementation	A maximum of 1 tern:hasSiteVisit <i>MAY</i> exist where the value node is an IRI of type tern:SiteVisit .
Cardinality	Maximum 1
Node kind	sh:IRI
Class type	tern:SiteVisit
Expected values	

4.1.12.18. Property: **tern:observationType**

Property	Value
IRI	tern:observationType
Shape IRI	https://w3id.org/tern/shapes/tern/tern-observationType
Status	stable ☑
Label	observation type
Definition	The type of observation.
Scope note	
Implementation	A maximum of 1 tern:observationType <i>MAY</i> exist with an IRI value.
Cardinality	Maximum 1
Node kind	sh:IRI
Class type	
Expected values	

4.1.12.19. Property: **void:inDataset**

Property	Value
IRI	void:inDataset
Shape IRI	https://w3id.org/tern/shapes/tern/void-inDataset
Status	stable ☑
Label	in dataset
Definition	A link to the RDF payload's metadata which this resource was a part of.
Scope note	
Implementation	There <i>MUST</i> exist exactly 1 void:inDataset property with an IRI value to a tern:RDFDataset .
Cardinality	Exactly 1
Node kind	sh:IRI
Class type	tern:RDFDataset

Property	Value
Expected values	

4.1.13. Class: tern:ObservationCollection

Property	Value
IRI	tern:ObservationCollection
Status	experimental ○
Label	Observation collection
Definition	Collection of one or more observations, whose members share a common value for one or more property
Scope note	

4.1.13.1. Property: sosa:hasFeatureOfInterest

Property	Value
IRI	sosa:hasFeatureOfInterest
Shape IRI	https://w3id.org/tern/shapes/tern/ObservationCollection-hasFeatureOfInterest
Status	stable ☑
Label	has feature of interest
Definition	A relation between an Observation and the entity whose quality was observed, or between an Actuation and the entity whose property was modified, or between an act of Sampling and the entity that was sampled.
Scope note	
Implementation	A tern:ObservationCollection MAY have a maximum of 1 sosa:hasFeatureOfInterest predicate where the value node is an IRI of type tern:FeatureOfInterest .
Cardinality	Maximum 1
Node kind	
Class type	tern:FeatureOfInterest tern:Sample tern:MaterialSample tern:Site tern:Transect
Expected values	

4.1.13.2. Property: sosa:hasMember

Property	Value
IRI	sosa:hasMember

Property	Value
Shape IRI	https://w3id.org/tern/shapes/tern/ObservationCollection-hasMember
Status	stable 
Label	has member
Definition	Link to a member of a collection of observations that share the same value for one or more of the characteristic properties.
Scope note	
Implementation	A <code>tern:ObservationCollection</code> <i>MUST</i> have at least 1 <code>sosa:hasMember</code> predicate where the value node is an IRI of type <code>tern:Observation</code> or <code>tern:ObservationCollection</code> .
Cardinality	Minimum 1
Node kind	
Class type	<code>tern:Observation</code> <code>tern:ObservationCollection</code>
Expected values	

4.1.13.3. Property: `sosa:hasUltimateFeatureOfInterest`

Property	Value
IRI	<code>sosa:hasUltimateFeatureOfInterest</code>
Shape IRI	https://w3id.org/tern/shapes/tern/ObservationCollection-hasUltimateFeatureOfInterest
Status	experimental 
Label	has ultimate feature of interest
Definition	Link to the ultimate feature of interest of an observation or act of sampling. This is useful when the proximate feature of interest is a sample of the ultimate feature of interest, directly or transitively.
Scope note	
Implementation	A <code>tern:ObservationCollection</code> <i>MAY</i> have a maximum of 1 <code>sosa:hasUltimateFeatureOfInterest</code> where the value node is an IRI of type <code>tern:FeatureOfInterest</code> .
Cardinality	Maximum 1
Node kind	
Class type	<code>tern:FeatureOfInterest</code> <code>tern:Sample</code> <code>tern:MaterialSample</code> <code>tern:Site</code> <code>tern:Transect</code>
Expected values	

4.1.13.4. Property: `sosa:madeBySensor`

Property	Value
IRI	<code>sosa:madeBySensor</code>
Shape IRI	https://w3id.org/tern/shapes/tern/ObservationCollection-madeBySensor
Status	stable 
Label	made by sensor
Definition	Relation between an Observation and the Sensor which made the Observations.
Scope note	
Implementation	A <code>tern:ObservationCollection</code> MAY have a maximum of 1 <code>sosa:madeBySensor</code> predicate where the value node is an IRI of type <code>tern:Sensor</code> .
Cardinality	Maximum 1
Node kind	<code>sh:IRI</code>
Class type	<code>tern:Sensor</code>
Expected values	

4.1.13.5. Property: `sosa:observedProperty`

Property	Value
IRI	<code>sosa:observedProperty</code>
Shape IRI	https://w3id.org/tern/shapes/tern/ObservationCollection-observedProperty
Status	stable 
Label	observed property
Definition	Relation linking an Observation to the property that was observed. The ObservableProperty should be a property of the FeatureOfInterest (linked by <code>hasFeatureOfInterest</code>) of this Observation.
Scope note	
Implementation	A <code>tern:ObservationCollection</code> MAY have a maximum of 1 <code>sosa:observedProperty</code> predicate where the value node is an IRI.
Cardinality	Maximum 1
Node kind	<code>sh:IRI</code>
Class type	
Expected values	

4.1.13.6. Property: `sosa:phenomenonTime`

Property	Value
IRI	<code>sosa:phenomenonTime</code>

Property	Value
Shape IRI	https://w3id.org/tern/shapes/tern/ObservationCollection-phenomenonTime
Status	stable 
Label	phenomenon time
Definition	The time that the Result of an Observation, Actuation, or Sampling applies to the FeatureOfInterest. Not necessarily the same as the resultTime. May be an interval or an instant, or some other compound temporal entity.
Scope note	
Implementation	A <code>tern:ObservationCollection</code> MAY have a maximum of 1 <code>sosa:phenomenonTime</code> predicate where the value node is an IRI of type <code>time:Instant</code> .
Cardinality	Maximum 1
Node kind	
Class type	<code>time#:Instant</code>
Expected values	

4.1.13.7. Property: `tern:resultDateTime`

Property	Value
IRI	<code>tern:resultDateTime</code>
Shape IRI	https://w3id.org/tern/shapes/tern/ObservationCollection-resultTime
Status	stable 
Label	result time
Definition	The result time is the instant of time when the Observation, Actuation or Sampling activity was completed.
Scope note	
Implementation	A <code>tern:ObservationCollection</code> MAY have a maximum of 1 <code>tern:resultDateTime</code> predicate where the value node is a literal with the datatype <code>xsd:date</code> , <code>xsd:dateTime</code> or <code>xsd:dateTimeStamp</code> .
Cardinality	Maximum 1
Node kind	
Class type	<code>xmlschema#:dateTime</code> <code>xmlschema#:date</code> <code>xmlschema#:dateTimeStamp</code>
Expected values	

4.1.13.8. Property: `sosa:usedProcedure`

Property	Value
IRI	<code>sosa:usedProcedure</code>

Property	Value
Shape IRI	https://w3id.org/tern/shapes/tern/ObservationCollection-usedProcedure
Status	stable 
Label	used procedure
Definition	A relation to link to a re-usable Procedure used in making an Observation, an Actuation, or a Sample, typically through a Sensor, Actuator or Sampler.
Scope note	
Implementation	A tern:ObservationCollection <i>MAY</i> have a maximum of 1 sosa:usedProcedure predicate where the value node is an IRI.
Cardinality	Maximum 1
Node kind	sh:IRI
Class type	
Expected values	

4.1.13.9. Property: tern:hasAttribute

Property	Value
IRI	tern:hasAttribute
Shape IRI	https://w3id.org/tern/shapes/tern/tern-hasAttribute
Status	stable 
Label	has attribute
Definition	Link to an Attribute.
Scope note	
Implementation	A tern:hasAttribute predicate <i>MUST</i> have a blank node or an IRI value of type tern:Attribute .
Cardinality	
Node kind	sh:BlankNodeOrIRI
Class type	tern:Attribute
Expected values	

4.1.13.10. Property: void:inDataset

Property	Value
IRI	void:inDataset
Shape IRI	https://w3id.org/tern/shapes/tern/void-inDataset
Status	stable 
Label	in dataset

Property	Value
Definition	A link to the RDF payload's metadata which this resource was a part of.
Scope note	
Implementation	There <i>MUST</i> exist exactly 1 <code>void:inDataset</code> property with an IRI value to a <code>tern:RDFDataset</code> .
Cardinality	Exactly 1
Node kind	<code>sh:IRI</code>
Class type	<code>tern:RDFDataset</code>
Expected values	

4.1.14. Class: `tern:RDFDataset`

Property	Value
IRI	<code>tern:RDFDataset</code>
Status	<code>stable</code> ☑
Label	RDFDataset
Definition	A set of RDF triples that are published, maintained or aggregated by a single provider.
Scope note	This is a specialised version of the <code>void:Dataset</code> class where it may be constrained by additional property shapes in the future.

4.1.14.1. Property: `dcterms:contributor`

Property	Value
IRI	<code>dcterms:contributor</code>
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-contributor
Status	<code>stable</code> ☑
Label	contributor
Definition	An entity, such as a person, organisation, or service, that is responsible for making contributions to the dataset. The contributor should be described as an RDF resource, rather than just providing the name as a literal.
Scope note	
Implementation	A <code>tern:RDFDataset</code> <i>MAY</i> have a <code>dcterms:contributor</code> predicate where the value node is an IRI.
Cardinality	
Node kind	<code>sh:IRI</code>
Class type	
Expected values	

4.1.14.2. Property: `dcterms:created`

Property	Value
IRI	<code>dcterms:created</code>
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-created
Status	stable 
Label	created
Definition	Date of creation of the dataset. The value should be formatted and data-typed as an <code>xsd:date</code> .
Scope note	
Implementation	A <code>tern:RDFDataset</code> MAY have a <code>dcterms:created</code> predicate where the value node is a literal with the datatype <code>xsd:date</code> .
Cardinality	
Node kind	
Class type	<code>xmlschema#:date</code>
Expected values	

4.1.14.3. Property: `dcterms:creator`

Property	Value
IRI	<code>dcterms:creator</code>
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-creator
Status	stable 
Label	creator
Definition	An entity, such as a person, organisation, or service, that is primarily responsible for creating the dataset. The creator should be described as an RDF resource, rather than just providing the name as a literal.
Scope note	
Implementation	A <code>tern:RDFDataset</code> MAY have a <code>dcterms:creator</code> predicate where the value node is an IRI.
Cardinality	
Node kind	<code>sh:IRI</code>
Class type	
Expected values	

4.1.14.4. Property: `dcterms:date`

Property	Value
IRI	<code>dcterms:date</code>

Property	Value
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-date
Status	stable 
Label	date
Definition	A point or period of time associated with an event in the life-cycle of the resource. The value should be formatted and data-typed as an <code>xsd:date</code> .
Scope note	
Implementation	A <code>tern:RDFDataset</code> MAY have a <code>dcterms:date</code> predicate where the value node is a literal with the datatype <code>xsd:date</code> .
Cardinality	
Node kind	
Class type	<code>xmlschema#:date</code>
Expected values	

4.1.14.5. Property: `dcterms:issued`

Property	Value
IRI	<code>dcterms:issued</code>
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-issued
Status	stable 
Label	issued
Definition	Date of formal issuance (e.g., publication) of the dataset. The value should be formatted and datatyped as an <code>xsd:date</code> .
Scope note	
Implementation	A <code>tern:RDFDataset</code> MAY have a <code>dcterms:issued</code> predicate where the value node is a literal with the datatype <code>xsd:date</code> .
Cardinality	
Node kind	
Class type	<code>xmlschema#:date</code>
Expected values	

4.1.14.6. Property: `dcterms:license`

Property	Value
IRI	<code>dcterms:license</code>
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-license
Status	stable 
Label	license

Property	Value
Definition	A legal document giving official permission to do something with the resource.
Scope note	
Implementation	A <code>tern:RDFDataset</code> MAY have a <code>dcterms:license</code> predicate where the value node is an IRI.
Cardinality	
Node kind	<code>sh:IRI</code>
Class type	
Expected values	

4.1.14.7. Property: `dcterms:modified`

Property	Value
IRI	<code>dcterms:modified</code>
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-modified
Status	<code>stable</code> ☑
Label	modified
Definition	Date on which the dataset was changed. The value should be formatted and datatyped as an <code>xsd:date</code> .
Scope note	
Implementation	A <code>tern:RDFDataset</code> MAY have a <code>dcterms:modified</code> predicate where the value node is a literal with the datatype <code>xsd:date</code> .
Cardinality	
Node kind	
Class type	<code>xmlschema#:date</code>
Expected values	

4.1.14.8. Property: `dcterms:publisher`

Property	Value
IRI	<code>dcterms:publisher</code>
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-publisher
Status	<code>stable</code> ☑
Label	publisher
Definition	An entity, such as a person, organisation, or service, that is responsible for making the dataset available. The publisher should be described as an RDF resource, rather than just providing the name as a literal.
Scope note	

Property	Value
Implementation	A tern:RDFDataset MAY have a dcterms:publisher predicate where the value node is an IRI.
Cardinality	
Node kind	sh:IRI
Class type	
Expected values	

4.1.14.9. Property: **dcterms:rightsHolder**

Property	Value
IRI	dcterms:rightsHolder
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-rightsHolder
Status	stable 
Label	rights holder
Definition	A person or organization owning or managing rights over the resource.
Scope note	
Implementation	A tern:RDFDataset MAY have a dcterms:rightsHolder predicate where the value node is an IRI or literal.
Cardinality	
Node kind	sh:IRIOrLiteral
Class type	
Expected values	

4.1.14.10. Property: **dcterms:source**

Property	Value
IRI	dcterms:source
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-source
Status	stable 
Label	source
Definition	A related resource from which the dataset is derived. The source should be described as an RDF resource, rather than as a literal.
Scope note	
Implementation	A tern:RDFDataset MAY have a dcterms:source predicate where the value node is an IRI.
Cardinality	
Node kind	sh:IRI

Property	Value
Class type	
Expected values	

4.1.14.11. Property: `dcterms:subject`

Property	Value
IRI	<code>dcterms:subject</code>
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-subject
Status	stable 
Label	subject
Definition	A topic of the resource. Recommended practice is to refer to the subject with a URI. If this is not possible or feasible, a literal value that identifies the subject may be provided. Both should preferably refer to a subject in a controlled vocabulary.
Scope note	
Implementation	A <code>tern:RDFDataset</code> <i>MAY</i> have a <code>dcterms:subject</code> predicate where the value node is an IRI or literal.
Cardinality	
Node kind	<code>sh:IRIOrLiteral</code>
Class type	
Expected values	

4.1.14.12. Property: `void:subset`

Property	Value
IRI	<code>void:subset</code>
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-subset
Status	stable 
Label	subset
Definition	The <code>void:subset</code> property can be used to provide descriptions of parts of a dataset. A part of a dataset is itself a <code>void:Dataset</code>, and any of the annotations for datasets listed in this guide can be applied to the subset. Reasons for subdividing a dataset might include: - Parts have different provenance (different <code>dcterms:source</code>) - Parts have different publication dates (different <code>dcterms:date</code>) - Parts are accesible through different SPARQL endpoints (different <code>void:sparqlEndpoint</code>) - Parts are about different topics (different <code>dcterms:subject</code>) - Parts can be downloaded separately in different RDF dumps (different <code>void:dataDump</code>)

Property	Value
Scope note	
Implementation	A tern:RDFDataset <i>MAY</i> have a void:subset predicate where the value node is an IRI of type void:Dataset .
Cardinality	
Node kind	sh:IRI
Class type	void#:Dataset
Expected values	

4.1.14.13. Property: **dcterms:title**

Property	Value
IRI	dcterms:title
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-title
Status	stable ☑
Label	title
Definition	The name of the dataset.
Scope note	
Implementation	A tern:RDFDataset <i>MAY</i> have a dcterms:title predicate where the value node is a literal with a datatype xsd:string .
Cardinality	
Node kind	
Class type	xmlschema#:string
Expected values	

4.1.14.14. Property: **void:vocabulary**

Property	Value
IRI	void:vocabulary
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-vocabulary
Status	stable ☑
Label	vocabulary
Definition	A vocabulary or owl:Ontology whose classes or properties are used in a void:Dataset .
Scope note	
Implementation	A tern:RDFDataset <i>MAY</i> have a void:vocabulary predicate where the value node is an IRI.
Cardinality	

Property	Value
Node kind	sh:IRI
Class type	
Expected values	

4.1.14.15. Property: dcterms:description

Property	Value
IRI	dcterms:description
Shape IRI	https://w3id.org/tern/shapes/tern/dcterms-description
Status	stable ☑
Label	description
Definition	A textual description.
Scope note	
Implementation	A dcterms:description predicate has a literal value with the datatype xsd:string .
Cardinality	
Node kind	
Class type	xmlschema#:string
Expected values	

4.1.14.16. Property: tern:hasAttribute

Property	Value
IRI	tern:hasAttribute
Shape IRI	https://w3id.org/tern/shapes/tern/tern-hasAttribute
Status	stable ☑
Label	has attribute
Definition	Link to an Attribute.
Scope note	
Implementation	A tern:hasAttribute predicate <i>MUST</i> have a blank node or an IRI value of type tern:Attribute .
Cardinality	
Node kind	sh:BlankNodeOrIRI
Class type	tern:Attribute
Expected values	

4.1.15. Class: tern:Result

Property	Value
IRI	<code>tern:Result</code>
Status	stable 
Label	Result
Definition	The result of an <code>Observation</code> , <code>Actuation</code> , or act of <code>Sampling</code> . To store an observation's simple result value one can use the <code>hasSimpleResult</code> property.
Scope note	

4.1.15.1. Property: `sosa:isResultOf`

Property	Value
IRI	<code>sosa:isResultOf</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Result-isResultOf
Status	stable 
Label	is result of
Definition	Relation linking a Result to the Observation or Actuation or act of Sampling that created or caused it.
Scope note	
Implementation	A <code>tern:Result</code> MAY have at most 1 <code>sosa:isResultOf</code> predicate where the value node is an IRI of type <code>tern:Observation</code> or <code>tern:Sampling</code> .
Cardinality	Maximum 1
Node kind	
Class type	<code>tern:Observation</code> <code>tern:Sampling</code>
Expected values	

4.1.15.2. Property: `void:inDataset`

Property	Value
IRI	<code>void:inDataset</code>
Shape IRI	https://w3id.org/tern/shapes/tern/void-inDataset
Status	stable 
Label	in dataset
Definition	A link to the RDF payload's metadata which this resource was a part of.
Scope note	
Implementation	There <i>MUST</i> exist exactly 1 <code>void:inDataset</code> property with an IRI value to a <code>tern:RDFDataset</code> .

Property	Value
Cardinality	Exactly 1
Node kind	sh:IRI
Class type	tern:RDFDataset
Expected values	

4.1.16. Class: tern:Sample

Property	Value
IRI	tern:Sample
Status	stable 
Label	Sample
Definition	A feature which is intended to be representative of a FeatureOfInterest on which Observations may be made.
Scope note	A sample may be a physical sample or a sub-divided section of some larger feature of interest. For example, land surface, plant population, ground cover are all common sub-samples of a site (feature of interest) in ecological surveys.

4.1.16.1. Property: sosa:isResultOf

Property	Value
IRI	sosa:isResultOf
Shape IRI	https://w3id.org/tern/shapes/tern/Sample-isResultOf
Status	stable 
Label	is result of
Definition	Relation linking a Result to the Sampling that created or caused it.
Scope note	
Implementation	A tern:Sample <i>MAY</i> have a sosa:isResultOf predicate where the value node is an IRI of type tern:Sampling .
Cardinality	
Node kind	sh:IRI
Class type	tern:Sampling
Expected values	

Property: Sample's sosa:isSampleOf or tern:hasSite

Property	Value
IRI	nb8df7c5c86414387be6e85d1441e1036b193[Sample's sosa:isSampleOf or tern:hasSite]

Property	Value
Shape IRI	https://w3id.org/tern/shapes/tern/Sample-isSampleOf
Status	experimental ○
Label	is sample of or has site
Definition	At least one sdo:spatial, geo:hasGeometry, tern:transectStartPoint, or tern:transectEndPoint exists along the chain of sosa:isSampleOf or tern:hasSite paths.
Scope note	
Implementation	At least one sdo:spatial, geo:hasGeometry, tern:transectStartPoint, or tern:transectEndPoint exists along the chain of sosa:isSampleOf or tern:hasSite paths.
Cardinality	
Node kind	
Class type	
Expected values	

4.1.16.2. Property: tern:hasAttribute

Property	Value
IRI	tern:hasAttribute
Shape IRI	https://w3id.org/tern/shapes/tern/tern-hasAttribute
Status	stable ☑
Label	has attribute
Definition	Link to an Attribute.
Scope note	
Implementation	A tern:hasAttribute predicate <i>MUST</i> have a blank node or an IRI value of type tern:Attribute .
Cardinality	
Node kind	sh:BlankNodeOrIRI
Class type	tern:Attribute
Expected values	

4.1.16.3. Property: tern:hasIGSN

Property	Value
IRI	tern:hasIGSN
Shape IRI	https://w3id.org/tern/shapes/tern/tern-hasIGSN
Status	experimental ○

Property	Value
Label	has IGSN
Definition	Relation between a Sample and an IGSN.
Scope note	
Implementation	A tern:Sample or tern:MaterialSample <i>MUST</i> have exactly 1 tern:hasIGSN predicate where the value node is an IRI of type tern:IGSN .
Cardinality	Exactly 1
Node kind	
Class type	tern:IGSN
Expected values	

4.1.17. Class: **tern:Sampler**

Property	Value
IRI	tern:Sampler
Status	stable ☑
Label	Sampler
Definition	A device that is used by, or implements, a (Sampling) Procedure to create or transform one or more samples.
Scope note	A ball mill, diamond drill, hammer, hypodermic syringe and needle, image Sensor or a soil auger can all act as sampling devices (i.e., be Samplers). However, sometimes the distinction between the Sampler and the Sensor is not evident, as they are packaged as a unit. A Sampler need not be a physical device.

4.1.17.1. Property: **ssn:implements**

Property	Value
IRI	ssn:implements
Shape IRI	https://w3id.org/tern/shapes/tern/Sampler-implements
Status	stable ☑
Label	implements
Definition	Relation between an entity that implements a Procedure in some executable way and the Procedure (an algorithm, procedure or method).
Scope note	
Implementation	A tern:Sampler <i>MUST</i> have at least 1 ssn:implements predicate where the value node is an IRI.
Cardinality	Minimum 1

Property	Value
Node kind	sh:IRI
Class type	
Expected values	

4.1.17.2. Property: **sosa:madeSampling**

Property	Value
IRI	sosa:madeSampling
Shape IRI	https://w3id.org/tern/shapes/tern/sosa-madeSampling
Status	stable ☑
Label	made sampling
Definition	Relation between a Sampler (sampling device or entity) and the Sampling act it performed.
Scope note	
Implementation	A sosa:madeSampling predicate MAY exist where the value node is an IRI.
Cardinality	
Node kind	sh:IRI
Class type	tern:Sampling
Expected values	

4.1.18. Class: **tern:Sampling**

Property	Value
IRI	tern:Sampling
Status	stable ☑
Label	Sampling
Definition	An activity of Sampling carries out a (Sampling) Procedure to create or transform one or more Samples.
Scope note	Crushing a rock sample in a ball mill to create sub-samples of the rock. Digging a pit through a soil sequence. Dividing a field site into quadrants. Drawing blood from a patient. Drilling an observation well. Establishing a station for environmental monitoring. Registering an image of the landscape. Sieving a powder to separate the subset finer than 100-mesh. Selecting a subset of a population. Splitting a piece of drill-core to create two new samples. Taking a diamond-drill core from a rock outcrop.

4.1.18.1. Property: **sosa:hasResult**

Property	Value
IRI	<code>sosa:hasResult</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Sampling-hasResult
Status	stable 
Label	has result
Definition	Relation linking an Observation or Actuation or act of Sampling and a Result or Sample.
Scope note	
Implementation	A <code>tern:Sampling</code> <i>MUST</i> have at least 1 <code>sosa:hasResult</code> predicate where the value node is an IRI of type <code>tern:Sample</code> .
Cardinality	Minimum 1
Node kind	
Class type	<code>tern:Sample</code> <code>tern:MaterialSample</code> <code>tern:Site</code>
Expected values	

4.1.18.2. Property: `sosa:madeBySampler`

Property	Value
IRI	<code>sosa:madeBySampler</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Sampling-madeBySampler
Status	stable 
Label	made by sampler
Definition	Relation linking an act of Sampling to the Sampler (sampling device or entity) that made it.
Scope note	
Implementation	A <code>tern:Sampling</code> <i>MAY</i> have a <code>sosa:madeBySampler</code> predicate where the value node is an IRI of type <code>tern:Sampler</code> .
Cardinality	
Node kind	<code>sh:IRI</code>
Class type	<code>tern:Sampler</code>
Expected values	

4.1.18.3. Property: `dcterms:identifier`

Property	Value
IRI	<code>dcterms:identifier</code>

Property	Value
Shape IRI	https://w3id.org/tern/shapes/tern/dcterms-identifier
Status	stable ☑
Label	identifier
Definition	An unambiguous reference to the resource within a given context.
Scope note	
Implementation	N/A
Cardinality	
Node kind	
Class type	
Expected values	

4.1.18.4. Property: dcterms:type

Property	Value
IRI	<code>dcterms:type</code>
Shape IRI	https://w3id.org/tern/shapes/tern/dcterms-type
Status	stable ☑
Label	type
Definition	Recommended practice is to use a controlled vocabulary such as the DCMI Type Vocabulary DCMI-TYPE . To describe the file format, physical medium, or dimensions of the resource, use the property Format.
Scope note	Useful to capture the proximate class type in situations when <code>rdfs:subClassOf</code> entailment is enabled and <code>rdf:type</code> is not suitable.
Implementation	A <code>dcterms:type</code> predicate <i>MUST</i> have an IRI value.
Cardinality	
Node kind	<code>sh:IRI</code>
Class type	
Expected values	

4.1.18.5. Property: geo:hasGeometry

Property	Value
IRI	<code>geo:hasGeometry</code>
Shape IRI	https://w3id.org/tern/shapes/tern/geo-hasGeometry
Status	stable ☑
Label	has geometry

Property	Value
Definition	A spatial representation for a given feature.
Scope note	
Implementation	A <code>geo:hasGeometry</code> predicate <i>MUST</i> have a blank node or IRI value.
Cardinality	
Node kind	<code>sh:BlankNodeOrIRI</code>
Class type	<code>geosparql#:Geometry</code>
Expected values	

4.1.18.6. Property: `prov:qualifiedAssociation`

Property	Value
IRI	<code>prov:qualifiedAssociation</code>
Shape IRI	https://w3id.org/tern/shapes/tern/prov-qualifiedAssociation
Status	<code>stable</code> ✓
Label	qualified association
Definition	An activity association is an assignment of responsibility to an agent for an activity, indicating that the agent had a role in the activity. It further allows for a plan to be specified, which is the plan intended by the agent to achieve some goals in the context of this activity.
Scope note	
Implementation	A <code>prov:qualifiedAssociation</code> <i>MUST</i> have a blank node or IRI value of type <code>prov:Association</code> .
Cardinality	
Node kind	<code>sh:BlankNodeOrIRI</code>
Class type	<code>prov#:Association</code>
Expected values	

4.1.18.7. Property: `prov:wasAssociatedWith`

Property	Value
IRI	<code>prov:wasAssociatedWith</code>
Shape IRI	https://w3id.org/tern/shapes/tern/prov-wasAssociatedWith
Status	<code>stable</code> ✓
Label	was associated with

Property	Value
Definition	An activity association is an assignment of responsibility to an agent for an activity, indicating that the agent had a role in the activity. It further allows for a plan to be specified, which is the plan intended by the agent to achieve some goals in the context of this activity.
Scope note	
Implementation	A <code>prov:wasAssociatedWith</code> predicate <i>MUST</i> an IRI value of type <code>prov:Agent</code> or <code>sdo:Person</code> .
Cardinality	
Node kind	
Class type	<code>prov#:Agent</code> <code>schema.org:Person</code>
Expected values	

4.1.18.8. Property: `rdfs:comment`

Property	Value
IRI	<code>rdfs:comment</code>
Shape IRI	https://w3id.org/tern/shapes/tern/rdfs-comment
Status	<code>stable</code> ☑
Label	comment
Definition	A description of the subject resource.
Scope note	
Implementation	An <code>rdfs:comment</code> <i>MUST</i> have a literal value.
Cardinality	
Node kind	<code>sh:Literal</code>
Class type	
Expected values	

4.1.18.9. Property: `sdo:spatial`

Property	Value
IRI	<code>sdo:spatial</code>
Shape IRI	https://w3id.org/tern/shapes/tern/sdo-spatial
Status	<code>experimental</code> ○
Label	spatial
Definition	A spatial representation for a given feature.
Scope note	

Property	Value
Implementation	A <code>sdo:spatial</code> predicate <i>MUST</i> have a blank node or IRI value.
Cardinality	
Node kind	<code>sh:BlankNodeOrIRI</code>
Class type	<code>geosparql#:Geometry</code>
Expected values	

4.1.18.10. Property: `sosa:hasFeatureOfInterest`

Property	Value
IRI	<code>sosa:hasFeatureOfInterest</code>
Shape IRI	https://w3id.org/tern/shapes/tern/sosa-hasFeatureOfInterest
Status	stable 
Label	has feature of interest
Definition	A relation between an Observation and the entity whose quality was observed, or between an Actuation and the entity whose property was modified, or between an act of Sampling and the entity that was sampled.
Scope note	
Implementation	Exactly 1 <code>sosa:hasFeatureOfInterest</code> predicate <i>MUST</i> exist_ with an IRI value.
Cardinality	Exactly 1
Node kind	
Class type	<code>tern:FeatureOfInterest</code> <code>tern:Sample</code> <code>tern:MaterialSample</code> <code>tern:Site</code> <code>tern:Transect</code>
Expected values	

4.1.18.11. Property: `tern:resultDateTime`

Property	Value
IRI	<code>tern:resultDateTime</code>
Shape IRI	https://w3id.org/tern/shapes/tern/sosa-resultTime
Status	stable 
Label	result date time
Definition	The result time is the instant of time when the Observation, Actuation or Sampling activity was completed.
Scope note	

Property	Value
Implementation	A tern:resultDateTime predicate <i>MUST</i> have a literal value where the datatype is an xsd:date , xsd:dateTime or xsd:dateTimeStamp .
Cardinality	Exactly 1
Node kind	sh:Literal
Class type	xmlschema#dateTime xmlschema#date xmlschema#dateTimeStamp
Expected values	

4.1.18.12. Property: **sosa:usedProcedure**

Property	Value
IRI	sosa:usedProcedure
Shape IRI	https://w3id.org/tern/shapes/tern/sosa-usedProcedure
Status	stable ☑
Label	used procedure
Definition	A relation to link to a re-usable Procedure used in making an Observation, an Actuation, or a Sample, typically through a Sensor, Actuator or Sampler.
Scope note	
Implementation	Exactly 1 sosa:usedProcedure <i>MUST</i> exist where the value node is a tern:Method or tern:Procedure .
Cardinality	Exactly 1
Node kind	
Class type	tern:Procedure tern:Method
Expected values	

4.1.18.13. Property: **tern:hasAttribute**

Property	Value
IRI	tern:hasAttribute
Shape IRI	https://w3id.org/tern/shapes/tern/tern-hasAttribute
Status	stable ☑
Label	has attribute
Definition	Link to an Attribute.
Scope note	

Property	Value
Implementation	A tern:hasAttribute predicate <i>MUST</i> have a blank node or an IRI value of type tern:Attribute .
Cardinality	
Node kind	sh:BlankNodeOrIRI
Class type	tern:Attribute
Expected values	

4.1.18.14. Property: **tern:hasSiteVisit**

Property	Value
IRI	tern:hasSiteVisit
Shape IRI	https://w3id.org/tern/shapes/tern/tern-hasSiteVisit
Status	stable ☑
Label	has site visit
Definition	A property that links, e.g., a Site to a Site Visit.
Scope note	
Implementation	A maximum of 1 tern:hasSiteVisit <i>MAY</i> exist where the value node is an IRI of type tern:SiteVisit .
Cardinality	Maximum 1
Node kind	sh:IRI
Class type	tern:SiteVisit
Expected values	

4.1.18.15. Property: **tern:samplingType**

Property	Value
IRI	tern:samplingType
Shape IRI	https://w3id.org/tern/shapes/tern/tern-samplingType
Status	stable ☑
Label	sampling type
Definition	The type of sampling act.
Scope note	
Implementation	A tern:Sampling <i>MAY</i> have a maximum of 1 tern:samplingType predicate where the value node is an IRI.
Cardinality	Maximum 1
Node kind	sh:IRI

Property	Value
Class type	
Expected values	

4.1.18.16. Property: void:inDataset

Property	Value
IRI	<code>void:inDataset</code>
Shape IRI	https://w3id.org/tern/shapes/tern/void-inDataset
Status	stable 
Label	in dataset
Definition	A link to the RDF payload's metadata which this resource was a part of.
Scope note	
Implementation	There <i>MUST</i> exist exactly 1 <code>void:inDataset</code> property with an IRI value to a <code>tern:RDFDataset</code> .
Cardinality	Exactly 1
Node kind	<code>sh:IRI</code>
Class type	<code>tern:RDFDataset</code>
Expected values	

4.1.19. Class: tern:Sensor

Property	Value
IRI	<code>tern:Sensor</code>
Status	stable 
Label	Sensor
Definition	Device, agent (including humans), or software (simulation) involved in, or implementing, a Procedure. Sensors respond to a stimulus, e.g., a change in the environment, or input data composed from the results of prior Observations, and generate a Result. Sensors can be hosted by Platforms.
Scope note	

4.1.19.1. Property: ssn:implements

Property	Value
IRI	<code>ssn:implements</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Sensor-implements
Status	stable 

Property	Value
Label	implements
Definition	Relation between an entity that implements a Procedure in some executable way and the Procedure (an algorithm, procedure or method).
Scope note	
Implementation	A tern:Sensor <i>MUST</i> have at least 1 ssn:implements predicate where the value node is an IRI.
Cardinality	Minimum 1
Node kind	sh:IRI
Class type	
Expected values	

4.1.19.2. Property: **sosa:madeObservation**

Property	Value
IRI	sosa:madeObservation
Shape IRI	https://w3id.org/tern/shapes/tern/Sensor-madeObservation
Status	stable ☑
Label	made observation
Definition	Relation between a Sensor and an Observation made by the Sensor .
Scope note	
Implementation	A tern:Sensor <i>MAY</i> have an sosa:madeObservation predicate where the value node is an IRI of type tern:Observation .
Cardinality	
Node kind	sh:IRI
Class type	tern:Observation
Expected values	

4.1.19.3. Property: **sosa:observes**

Property	Value
IRI	sosa:observes
Shape IRI	https://w3id.org/tern/shapes/tern/Sensor-observes
Status	stable ☑
Label	observes
Definition	Relation between a Sensor and an ObservableProperty that it is capable of sensing.
Scope note	

Property	Value
Implementation	A tern:Sensor <i>MAY</i> have an sosa:observes predicate where the value node is an IRI.
Cardinality	
Node kind	sh:IRI
Class type	
Expected values	

4.1.20. Class: tern:Site

Property	Value
IRI	tern:Site
Status	stable ☑
Label	Site
Definition	An ecological monitoring site where observations and samplings occur. This Site class is a subclass of Sample since ecological sites are designed to be representative of an environmental system (which may be an ecosystem or bioregion) or zone (which may be a zone such as a parcel or tract).
Scope note	Ausplots Rangelands Site 59858 (Site Name: WAACOO0011)

4.1.20.1. Property: tern:dimension

Property	Value
IRI	tern:dimension
Shape IRI	https://w3id.org/tern/shapes/tern/Site-dimension
Status	experimental ○
Label	dimension
Definition	Dimenion in metres.
Scope note	
Implementation	A tern:Site <i>MAY</i> have a maximum of 1 tern:dimension predicate where the value node is a literal with the datatype `xsd:string`.
Cardinality	Maximum 1
Node kind	sh:Literal
Class type	xmlschema#string
Expected values	

4.1.20.2. Property: tern:featureType

Property	Value
IRI	<code>tern:featureType</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Site-featureType
Status	stable 
Label	site feature type
Definition	The feature type of a [Feature of Interest](#FeatureofInterest).
Scope note	
Implementation	A <code>tern:Site</code> <i>MUST</i> have exactly 1 <code>tern:featureType</code> predicate where the value node is an IRI.
Cardinality	Exactly 1
Node kind	<code>sh:IRI</code>
Class type	
Expected values	

4.1.20.3. Property: `tern:hasSiteVisit`

Property	Value
IRI	<code>tern:hasSiteVisit</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Site-hasSiteVisit
Status	stable 
Label	has site visit
Definition	A property that links, e.g., a Site to a Site Visit.
Scope note	
Implementation	A <code>tern:Site</code> <i>MAY</i> have a <code>tern:hasSiteVisit</code> predicate where the value node is an IRI of type <code>tern:SiteVisit</code> .
Cardinality	
Node kind	<code>sh:IRI</code>
Class type	<code>tern:SiteVisit</code>
Expected values	

4.1.20.4. Property: `tern:locationProcedure`

Property	Value
IRI	<code>tern:locationProcedure</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Site-locationProcedure
Status	experimental 
Label	location procedure

Property	Value
Definition	Link to a procedure used to obtain the location.
Scope note	
Implementation	A tern:Site <i>MAY</i> have a maximum of 1 tern:locationProcedure predicate where the value node is an IRI.
Cardinality	Maximum 1
Node kind	sh:IRI
Class type	
Expected values	

4.1.20.5. Property: **geo:sfWithin**

Property	Value
IRI	geo:sfWithin
Shape IRI	https://w3id.org/tern/shapes/tern/geo-sfWithin
Status	experimental ○
Label	SF within
Definition	Exists if the subject SpatialObject is spatially within the object SpatialObject. DE-9IM: T*FF*
Scope note	
Implementation	A geo:sfWithin <i>MUST</i> have an IRI value.
Cardinality	
Node kind	sh:IRI
Class type	
Expected values	

4.1.20.6. Property: **sosa:hasSample**

Property	Value
IRI	sosa:hasSample
Shape IRI	https://w3id.org/tern/shapes/tern/sosa-hasSample
Status	stable ☑
Label	has sample
Definition	Relation between a FeatureOfInterest and the Sample used to represent it.
Scope note	
Implementation	A tern:FeatureOfInterest <i>MAY</i> have a sosa:hasSample predicate where the value node is an IRI of type tern:Sample .

Property	Value
Cardinality	
Node kind	
Class type	<code>tern:Sample</code> <code>tern:MaterialSample</code>
Expected values	

4.1.20.7. Property: `tern:hasAttribute`

Property	Value
IRI	<code>tern:hasAttribute</code>
Shape IRI	https://w3id.org/tern/shapes/tern/tern-hasAttribute
Status	stable 
Label	has attribute
Definition	Link to an Attribute.
Scope note	
Implementation	A <code>tern:hasAttribute</code> predicate <i>MUST</i> have a blank node or an IRI value of type <code>tern:Attribute</code> .
Cardinality	
Node kind	<code>sh:BlankNodeOrIRI</code>
Class type	<code>tern:Attribute</code>
Expected values	

4.1.20.8. Property: `tern:locationDescription`

Property	Value
IRI	<code>tern:locationDescription</code>
Shape IRI	https://w3id.org/tern/shapes/tern/tern-locationDescription
Status	experimental 
Label	location description
Definition	The description of the site's location. Example: 10km west of Fletcherview Tropical Rangeland SuperSite.
Scope note	
Implementation	A <code>tern:locationDescription</code> <i>MUST</i> have a literal value with the datatype <code>xsd:string</code> .
Cardinality	Maximum 1
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#string</code>

Property	Value
Expected values	

4.1.20.9. Property: tern:siteDescription

Property	Value
IRI	tern:siteDescription
Shape IRI	https://w3id.org/tern/shapes/tern/tern-siteDescription
Status	experimental ○
Label	site description
Definition	The description of the site. Example: Outer fringe of larger lake chain, isolated by reddish dunes, yellow sand fan into western edge. Very few, 3, plants regenerating after recent moderate rains. Silt, sand with scattered iron conglomerate stones on surface.
Scope note	
Implementation	A tern:siteDescription <i>MUST</i> have a literal value with the datatype xsd:string .
Cardinality	Maximum 1
Node kind	sh:Literal
Class type	xmlschema#:string
Expected values	

4.1.21. Class: tern:SiteVisit

Property	Value
IRI	tern:SiteVisit
Status	stable ☑
Label	Site Visit
Definition	A Site Visit is a Survey that visits a Site .
Scope note	

4.1.21.1. Property: dcterms:identifier

Property	Value
IRI	dcterms:identifier
Shape IRI	https://w3id.org/tern/shapes/tern/dcterms-identifier
Status	stable ☑
Label	identifier

Property	Value
Definition	An unambiguous reference to the resource within a given context.
Scope note	
Implementation	N/A
Cardinality	
Node kind	
Class type	
Expected values	

4.1.21.2. Property: `dcterms:type`

Property	Value
IRI	<code>dcterms:type</code>
Shape IRI	https://w3id.org/tern/shapes/tern/dcterms-type
Status	stable 
Label	type
Definition	Recommended practice is to use a controlled vocabulary such as the DCMI Type Vocabulary DCMI-TYPE . To describe the file format, physical medium, or dimensions of the resource, use the property <code>Format</code> .
Scope note	Useful to capture the proximate class type in situations when <code>rdfs:subClassOf</code> entailment is enabled and <code>rdf:type</code> is not suitable.
Implementation	A <code>dcterms:type</code> predicate <i>MUST</i> have an IRI value.
Cardinality	
Node kind	<code>sh:IRI</code>
Class type	
Expected values	

4.1.21.3. Property: `tern:hasAttribute`

Property	Value
IRI	<code>tern:hasAttribute</code>
Shape IRI	https://w3id.org/tern/shapes/tern/tern-hasAttribute
Status	stable 
Label	has attribute
Definition	Link to an Attribute.
Scope note	
Implementation	A <code>tern:hasAttribute</code> predicate <i>MUST</i> have a blank node or an IRI value of type <code>tern:Attribute</code> .

Property	Value
Cardinality	
Node kind	sh:BlankNodeOrIRI
Class type	tern:Attribute
Expected values	

4.1.21.4. Property: tern:hasSite

Property	Value
IRI	tern:hasSite
Shape IRI	https://w3id.org/tern/shapes/tern/tern-hasSite
Status	stable ☑
Label	has site
Definition	A property that links, e.g., a FeatureOfInterest to a Site or Transect.
Scope note	
Implementation	A tern:FeatureOfInterest MAY have a tern:hasSite predicate where the value node is an IRI of type tern:Site or tern:Transect.
Cardinality	
Node kind	
Class type	tern:Site tern:Transect
Expected values	

4.1.21.5. Property: tern:locationDescription

Property	Value
IRI	tern:locationDescription
Shape IRI	https://w3id.org/tern/shapes/tern/tern-locationDescription
Status	experimental ○
Label	location description
Definition	The description of the site's location. Example: 10km west of Fletcherview Tropical Rangeland SuperSite.
Scope note	
Implementation	A tern:locationDescription <i>MUST</i> have a literal value with the datatype xsd:string.
Cardinality	Maximum 1
Node kind	sh:Literal
Class type	xmlschema#string

Property	Value
Expected values	

4.1.21.6. Property: tern:siteDescription

Property	Value
IRI	tern:siteDescription
Shape IRI	https://w3id.org/tern/shapes/tern/tern-siteDescription
Status	experimental ○
Label	site description
Definition	The description of the site. Example: Outer fringe of larger lake chain, isolated by reddish dunes, yellow sand fan into western edge. Very few, 3, plants regenerating after recent moderate rains. Silt, sand with scattered iron conglomerate stones on surface.
Scope note	
Implementation	A tern:siteDescription <i>MUST</i> have a literal value with the datatype xsd:string .
Cardinality	Maximum 1
Node kind	sh:Literal
Class type	xmlschema#:string
Expected values	

4.1.22. Class: tern:System

Property	Value
IRI	tern:System
Status	stable ☑
Label	System
Definition	System is a unit of abstraction for pieces of infrastructure that implement Procedures. A System may have components, its subsystems, which are other Systems.
Scope note	

4.1.22.1. Property: ssn:hasDeployment

Property	Value
IRI	ssn:hasDeployment
Shape IRI	https://w3id.org/tern/shapes/tern/System-hasDeployment
Status	experimental ○

Property	Value
Label	has deployment
Definition	Relation between a System and a Deployment, recording that the System is deployed in that Deployment.
Scope note	
Implementation	A tern:System MAY have an ssn:hasDeployment predicate where the value node is an IRI of type tern:Deployment .
Cardinality	
Node kind	
Class type	tern:Deployment
Expected values	

4.1.22.2. Property: **sosa:isHostedBy**

Property	Value
IRI	sosa:isHostedBy
Shape IRI	https://w3id.org/tern/shapes/tern/System-isHostedBy
Status	stable ☑
Label	is hosted by
Definition	Relation between a Sensor, Actuator, Sampler, or Platform, and the Platform that it is mounted on or hosted by.
Scope note	
Implementation	A tern:System MAY have a maximum of 1 sosa:isHostedBy predicate where the value node is an IRI of type tern:Platform .
Cardinality	Maximum 1
Node kind	sh:IRI
Class type	tern:Platform
Expected values	

4.1.22.3. Property: **tern:systemType**

Property	Value
IRI	tern:systemType
Shape IRI	https://w3id.org/tern/shapes/tern/System-systemType
Status	stable ☑
Label	system type
Definition	The type of system. Values are from some controlled vocabulary.
Scope note	

Property	Value
Implementation	A tern:System <i>MAY</i> have a tern:systemType predicate where the value node is an IRI.
Cardinality	
Node kind	sh:IRI
Class type	
Expected values	

4.1.22.4. Property: dcat:contactPoint

Property	Value
IRI	dcat:contactPoint
Shape IRI	https://w3id.org/tern/shapes/tern/dcat-contactPoint
Status	stable ☑
Label	contact point
Definition	Relevant contact information for the resource. Can be used to identify a person or organization that can be contacted for questions about the resource.
Scope note	
Implementation	A resource <i>MAY</i> have a dcat:contactPoint predicate where the value is an IRI or literal.
Cardinality	
Node kind	sh:IRIOrLiteral
Class type	
Expected values	

4.1.22.5. Property: dcterms:source

Property	Value
IRI	dcterms:source
Shape IRI	https://w3id.org/tern/shapes/tern/dcterms-source
Status	stable ☑
Label	source
Definition	A related source from which the described resource is derived. The described resource may be derived from the related source in whole or in part.
Scope note	
Implementation	A resource <i>MAY</i> have a dcterms:source predicate where the value is an IRI or literal.
Cardinality	

Property	Value
Node kind	<code>sh:IRIOrLiteral</code>
Class type	
Expected values	

4.1.22.6. Property: `dcterms:type`

Property	Value
IRI	<code>dcterms:type</code>
Shape IRI	https://w3id.org/tern/shapes/tern/dcterms-type
Status	stable 
Label	type
Definition	Recommended practice is to use a controlled vocabulary such as the DCMI Type Vocabulary DCMI-TYPE . To describe the file format, physical medium, or dimensions of the resource, use the property Format.
Scope note	Useful to capture the proximate class type in situations when <code>rdfs:subClassOf</code> entailment is enabled and <code>rdf:type</code> is not suitable.
Implementation	A <code>dcterms:type</code> predicate <i>MUST</i> have an IRI value.
Cardinality	
Node kind	<code>sh:IRI</code>
Class type	
Expected values	

4.1.22.7. Property: `sdo:serialNumber`

Property	Value
IRI	<code>sdo:serialNumber</code>
Shape IRI	https://w3id.org/tern/shapes/tern/schema-serialNumber
Status	stable 
Label	serial number
Definition	The serial number or any alphanumeric identifier of a device (e.g., sensor, sampler).
Scope note	
Implementation	A <code>sdo:serialNumber</code> predicate <i>MUST</i> have a literal value.
Cardinality	
Node kind	<code>sh:Literal</code>
Class type	
Expected values	

4.1.22.8. Property: skos:altLabel

Property	Value
IRI	<code>skos:altLabel</code>
Shape IRI	https://w3id.org/tern/shapes/tern/skos-altLabel
Status	stable ☑
Label	alternative label
Definition	An alternative label for the resource.
Scope note	
Implementation	A <code>skos:altLabel</code> predicate <i>MUST</i> have a literal value.
Cardinality	
Node kind	<code>sh:Literal</code>
Class type	
Expected values	

4.1.22.9. Property: skos:exactMatch

Property	Value
IRI	<code>skos:exactMatch</code>
Shape IRI	https://w3id.org/tern/shapes/tern/skos-exactMatch
Status	stable ☑
Label	exact match
Definition	Indicates that two concepts, terms, or resources are semantically equivalent and can be used interchangeably. Used to link a resource to its exact corresponding match in another system or vocabulary.
Scope note	
Implementation	A resource <i>MAY</i> have a <code>skos:exactMatch</code> predicate where the value is an IRI.
Cardinality	
Node kind	<code>sh:IRI</code>
Class type	
Expected values	

4.1.22.10. Property: skos:prefLabel

Property	Value
IRI	<code>skos:prefLabel</code>
Shape IRI	https://w3id.org/tern/shapes/tern/skos-prefLabel
Status	stable ☑

Property	Value
Label	preferred label
Definition	The preferred label of the resource.
Scope note	
Implementation	A skos:prefLabel predicate <i>MUST</i> have a literal value.
Cardinality	
Node kind	sh:Literal
Class type	
Expected values	

4.1.22.11. Property: skos:scopeNote

Property	Value
IRI	skos:scopeNote
Shape IRI	https://w3id.org/tern/shapes/tern/skos-scopeNote
Status	stable ☑
Label	scope note
Definition	A note that provides additional information about the resource.
Scope note	
Implementation	A skos:scopeNote predicate <i>MUST</i> have a literal value.
Cardinality	
Node kind	sh:Literal
Class type	
Expected values	

4.1.22.12. Property: ssn:implements

Property	Value
IRI	ssn:implements
Shape IRI	https://w3id.org/tern/shapes/tern/ssn-implements
Status	stable ☑
Label	ssn implements
Definition	Relation between an entity that implements a Procedure in some executable way and the Procedure (an algorithm, procedure or method).
Scope note	
Implementation	Exactly 1 ssn:implements <i>MUST</i> exist where the value node is a tern:Method or tern:Procedure .

Property	Value
Cardinality	Exactly 1
Node kind	
Class type	<code>tern:Procedure</code> <code>tern:Method</code>
Expected values	

4.1.22.13. Property: `ssn-system:hasOperatingProperty`

Property	Value
IRI	<code>ssn-system:hasOperatingProperty</code>
Shape IRI	https://w3id.org/tern/shapes/tern/ssn-system-hasOperatingProperty
Status	<code>experimental</code> ○
Label	has operating property
Definition	Relation from an <code>OperatingRange</code> of a <code>System</code> to an <code>OperatingProperty</code> describing the operating range of the <code>System</code> . This property is used to specify the operating characteristics or properties that define the operating conditions of a system.
Scope note	
Implementation	A <code>ssn-system:hasOperatingProperty</code> predicate <i>MUST</i> have an IRI or blank node value of type <code>ssn-system:OperatingProperty</code> .
Cardinality	
Node kind	<code>n3da140865bca4e10a155115c6af4ae86b240</code>
Class type	<code>systems:OperatingProperty</code>
Expected values	

4.1.22.14. Property: `ssn-system:hasSystemCapability`

Property	Value
IRI	<code>ssn-system:hasSystemCapability</code>
Shape IRI	https://w3id.org/tern/shapes/tern/ssn-system-hasSystemCapability
Status	<code>experimental</code> ○
Label	has system capability
Definition	Relation from a <code>System</code> to a <code>SystemCapability</code> describing the capabilities of the <code>System</code> under certain <code>Conditions</code> . This property is used to specify what a system is capable of doing under specific circumstances.
Scope note	
Implementation	A <code>ssn-system:hasSystemCapability</code> predicate <i>MUST</i> have an IRI or blank node value of type <code>ssn-system:SystemCapability</code> .

Property	Value
Cardinality	
Node kind	n3da140865bca4e10a155115c6af4ae86b243
Class type	systems:SystemCapability
Expected values	

4.1.22.15. Property: `ssn-system:hasSystemProperty`

Property	Value
IRI	<code>ssn-system:hasSystemProperty</code>
Shape IRI	https://w3id.org/tern/shapes/tern/ssn-system-hasSystemProperty
Status	experimental ○
Label	has system property
Definition	Relation from a SystemCapability of a System to a SystemProperty describing the capabilities of the System. This property is used to specify the inherent properties or characteristics that describe the capabilities of a system.
Scope note	
Implementation	A <code>ssn-system:hasSystemProperty</code> predicate <i>MUST</i> have an IRI or blank node value of type <code>ssn-system:SystemProperty</code> .
Cardinality	
Node kind	n3da140865bca4e10a155115c6af4ae86b246
Class type	systems:SystemProperty
Expected values	

4.1.22.16. Property: `tern:hasCalibration`

Property	Value
IRI	<code>tern:hasCalibration</code>
Shape IRI	https://w3id.org/tern/shapes/tern/tern-hasCalibration
Status	experimental ○
Label	has calibration
Definition	Relation between a System and a Calibration, recording that the System is calibrated.
Scope note	
Implementation	A <code>tern:System</code> <i>MAY</i> have an <code>tern:hasCalibration</code> predicate where the value node is an IRI of type <code>tern:Calibration</code> .
Cardinality	
Node kind	

Property	Value
Class type	<code>tern:Calibration</code>
Expected values	

4.1.23. Class: `tern:Taxon`

Property	Value
IRI	<code>tern:Taxon</code>
Status	<code>stable</code> 
Label	Taxon
Definition	A group of organisms (sensu http://purl.obolibrary.org/obo/OBI_0100026) considered by taxonomists to form a homogeneous unit.
Scope note	The genus <i>Truncorotaloides</i> as published by Bronnimann et al. in 1953 in the Journal of Paleontology Vol. 27(6) p. 817-820.

4.1.23.1. Property: `dwc:acceptedNameUsage`

Property	Value
IRI	<code>dwc:acceptedNameUsage</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-acceptedNameUsage
Status	<code>stable</code> 
Label	accepted name usage
Definition	The full name, with authorship and date information if known, of the currently valid (zoological) or accepted (botanical) taxon.
Scope note	
Implementation	A <code>tern:Taxon</code> MAY have a <code>dwc:acceptedNameUsage</code> predicate where the value node is a literal with the datatype <code>xsd:string</code> .
Cardinality	
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#string</code>
Expected values	

4.1.23.2. Property: `dwc:acceptedNameUsageID`

Property	Value
IRI	<code>dwc:acceptedNameUsageID</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-acceptedNameUsageID
Status	<code>stable</code> 

Property	Value
Label	accepted name usage ID
Definition	An identifier for the name usage (documented meaning of the name according to a source) of the currently valid (zoological) or accepted (botanical) taxon.
Scope note	
Implementation	A tern:Taxon MAY have a dwc:acceptedNameUsageID predicate where the value node is a literal with the datatype xsd:string .
Cardinality	
Node kind	sh:Literal
Class type	xmlschema#string
Expected values	

4.1.23.3. Property: dwc:class

Property	Value
IRI	dwc:class
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-class
Status	stable 
Label	class
Definition	The full scientific name of the class in which the taxon is classified.
Scope note	
Implementation	A tern:Taxon MAY have a dwc:class predicate where the value node is a literal with the datatype xsd:string .
Cardinality	
Node kind	sh:Literal
Class type	xmlschema#string
Expected values	

4.1.23.4. Property: dwc:cultivarEpithet

Property	Value
IRI	dwc:cultivarEpithet
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-cultivarEpithet
Status	stable 
Label	cultivarEpithet
Definition	Part of the name of a cultivar, cultivar group or grex that follows the scientific name.
Scope note	

Property	Value
Implementation	A tern:Taxon MAY have a dwc:cultivarEpithet predicate where the value node is a literal with the datatype xsd:string .
Cardinality	
Node kind	sh:Literal
Class type	xmlschema#string
Expected values	

4.1.23.5. Property: dwc:family

Property	Value
IRI	dwc:family
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-family
Status	stable 
Label	family
Definition	The full scientific name of the family in which the taxon is classified.
Scope note	
Implementation	A tern:Taxon MAY have a dwc:family predicate where the value node is a literal with the datatype xsd:string .
Cardinality	
Node kind	sh:Literal
Class type	xmlschema#string
Expected values	

4.1.23.6. Property: dwc:genericName

Property	Value
IRI	dwc:genericName
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-genericName
Status	stable 
Label	generic name
Definition	The genus part of the scientificName without authorship.
Scope note	
Implementation	A tern:Taxon MAY have a dwc:genericName predicate where the value node is a literal with the datatype xsd:string .
Cardinality	
Node kind	sh:Literal

Property	Value
Class type	<code>xmlschema#:string</code>
Expected values	

4.1.23.7. Property: `dwc:genus`

Property	Value
IRI	<code>dwc:genus</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-genus
Status	stable 
Label	genus
Definition	The full scientific name of the genus in which the taxon is classified.
Scope note	
Implementation	A <code>tern:Taxon</code> MAY have a <code>dwc:genus</code> predicate where the value node is a literal with the datatype <code>xsd:string</code> .
Cardinality	
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#:string</code>
Expected values	

4.1.23.8. Property: `dwc:higherClassification`

Property	Value
IRI	<code>dwc:higherClassification</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-higherClassification
Status	stable 
Label	higher classification
Definition	A list (concatenated and separated) of taxa names terminating at the rank immediately superior to the taxon referenced in the taxon record.
Scope note	
Implementation	A <code>tern:Taxon</code> MAY have a <code>dwc:higherClassification</code> predicate where the value node is a literal with the datatype <code>xsd:string</code> .
Cardinality	
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#:string</code>
Expected values	

4.1.23.9. Property: `dwc:infragenericEpithet`

Property	Value
IRI	<code>dwc:infragenericEpithet</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-infragenericEpithet
Status	stable 
Label	infrageneric epithet
Definition	The infrageneric part of a binomial name at ranks above species but below genus.
Scope note	
Implementation	A <code>tern:Taxon</code> MAY have a <code>dwc:infragenericEpithet</code> predicate where the value node is a literal with the datatype <code>xsd:string</code> .
Cardinality	
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#string</code>
Expected values	

4.1.23.10. Property: `dwc:infraspecificEpithet`

Property	Value
IRI	<code>dwc:infraspecificEpithet</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-infraspecificEpithet
Status	stable 
Label	infraspecific epithet
Definition	The name of the lowest or terminal infraspecific epithet of the scientificName, excluding any rank designation.
Scope note	
Implementation	A <code>tern:Taxon</code> MAY have a <code>dwc:infraspecificEpithet</code> predicate where the value node is a literal with the datatype <code>xsd:string</code> .
Cardinality	
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#string</code>
Expected values	

4.1.23.11. Property: `dwc:kingdom`

Property	Value
IRI	<code>dwc:kingdom</code>

Property	Value
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-kingdom
Status	stable 
Label	kingdom
Definition	The full scientific name of the kingdom in which the taxon is classified.
Scope note	
Implementation	A tern:Taxon MAY have a dwc:kingdom predicate where the value node is a literal with the datatype xsd:string .
Cardinality	
Node kind	sh:Literal
Class type	xmlschema#:string
Expected values	

4.1.23.12. Property: **dwc:nameAccordingTo**

Property	Value
IRI	dwc:nameAccordingTo
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-nameAccordingTo
Status	stable 
Label	name according to
Definition	The reference to the source in which the specific taxon concept circumscription is defined or implied. For taxa that result from identifications, a reference to the keys, monographs, experts and other sources should be given.
Scope note	
Implementation	A tern:Taxon MAY have a dwc:nameAccordingTo predicate where the value node is a literal with the datatype xsd:string .
Cardinality	
Node kind	sh:Literal
Class type	xmlschema#:string
Expected values	

4.1.23.13. Property: **dwc:nameAccordingToID**

Property	Value
IRI	dwc:nameAccordingToID
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-nameAccordingToID
Status	stable 

Property	Value
Label	name according to ID
Definition	An identifier for the source in which the specific taxon concept circumscription is defined or implied. See nameAccordingTo.
Scope note	
Implementation	A tern:Taxon MAY have a dwc:nameAccordingToID predicate where the value node is a literal with a datatype of xsd:string .
Cardinality	
Node kind	sh:Literal
Class type	xmlschema#string
Expected values	

4.1.23.14. Property: dwc:namePublishedIn

Property	Value
IRI	dwc:namePublishedIn
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-namePublishedIn
Status	stable 
Label	name published in
Definition	A reference for the publication in which the scientificName was originally established under the rules of the associated nomenclaturalCode.
Scope note	
Implementation	A tern:Taxon MAY have a dwc:namePublishedIn predicate where the value node is a literal with the datatype xsd:string .
Cardinality	
Node kind	sh:Literal
Class type	xmlschema#string
Expected values	

4.1.23.15. Property: dwc:namePublishedInID

Property	Value
IRI	dwc:namePublishedInID
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-namePublishedInID
Status	stable 
Label	name published in ID
Definition	An identifier for the publication in which the scientificName was originally established under the rules of the associated nomenclaturalCode.

Property	Value
Scope note	
Implementation	A tern:Taxon MAY have a dwc:namePublishedInID where the value node is a literal with the datatype xsd:string .
Cardinality	
Node kind	sh:Literal
Class type	xmlschema#:string
Expected values	

4.1.23.16. Property: **dwc:namePublishedInYear**

Property	Value
IRI	dwc:namePublishedInYear
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-namePublishedInYear
Status	stable 
Label	name published in year
Definition	The four-digit year in which the scientificName was published.
Scope note	
Implementation	A tern:Taxon MAY have a dwc:namePublishedInYear predicate where the value node is a literal with the datatype xsd:string .
Cardinality	
Node kind	sh:Literal
Class type	xmlschema#:string
Expected values	

4.1.23.17. Property: **dwc:nomenclaturalCode**

Property	Value
IRI	dwc:nomenclaturalCode
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-nomenclaturalCode
Status	stable 
Label	nomenclatural code
Definition	The nomenclatural code (or codes in the case of an ambiregnal name) under which the scientificName is constructed.
Scope note	
Implementation	A tern:Taxon MAY have a dwc:nomenclaturalCode predicate where the value node is a literal with the datatype xsd:string .
Cardinality	

Property	Value
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#string</code>
Expected values	

4.1.23.18. Property: `dwc:nomenclaturalStatus`

Property	Value
IRI	<code>dwc:nomenclaturalStatus</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-nomenclaturalStatus
Status	<code>stable</code> 
Label	nomenclatural status
Definition	The status related to the original publication of the name and its conformance to the relevant rules of nomenclature. It is based essentially on an algorithm according to the business rules of the code. It requires no taxonomic opinion.
Scope note	
Implementation	A <code>tern:Taxon</code> MAY have a <code>dwc:nomenclaturalStatus</code> predicate where the value node is a literal with the datatype <code>xsd:string</code> .
Cardinality	
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#string</code>
Expected values	

4.1.23.19. Property: `dwc:order`

Property	Value
IRI	<code>dwc:order</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-order
Status	<code>stable</code> 
Label	order
Definition	The full scientific name of the order in which the taxon is classified.
Scope note	
Implementation	A <code>tern:Taxon</code> MAY have a <code>dwc:order</code> predicate where the value node is a literal with the datatype <code>xsd:string</code> .
Cardinality	
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#string</code>
Expected values	

4.1.23.20. Property: **dwc:originalNameUsage**

Property	Value
IRI	dwc:originalNameUsage
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-originalNameUsage
Status	stable ☑
Label	original name usage
Definition	The taxon name, with authorship and date information if known, as it originally appeared when first established under the rules of the associated nomenclaturalCode. The basionym (botany) or basonym (bacteriology) of the scientificName or the senior/earlier homonym for replaced names.
Scope note	
Implementation	A tern:Taxon <i>MAY</i> have a dwc:originalNameUsage predicate where the value node is a literal with the datatype xsd:string .
Cardinality	
Node kind	sh:Literal
Class type	xmlschema#string
Expected values	

4.1.23.21. Property: **dwc:originalNameUsageID**

Property	Value
IRI	dwc:originalNameUsageID
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-originalNameUsageID
Status	stable ☑
Label	original name usage ID
Definition	An identifier for the name usage (documented meaning of the name according to a source) in which the terminal element of the scientificName was originally established under the rules of the associated nomenclaturalCode.
Scope note	
Implementation	A tern:Taxon <i>MAY</i> have a dwc:originalNameUsageID predicate where the value node is a literal with the datatype xsd:string .
Cardinality	
Node kind	sh:Literal
Class type	xmlschema#string
Expected values	

4.1.23.22. Property: **dwc:parentNameUsage**

Property	Value
IRI	dwc:parentNameUsage
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-parentNameUsage
Status	stable ☑
Label	parent name usage
Definition	The full name, with authorship and date information if known, of the direct, most proximate higher-rank parent taxon (in a classification) of the most specific element of the scientificName.
Scope note	
Implementation	A tern:Taxon <i>MAY</i> have a dwc:parentNameUsage predicate where the value node is a literal with the datatype xsd:string .
Cardinality	
Node kind	sh:Literal
Class type	xmlschema#string
Expected values	

4.1.23.23. Property: **dwc:parentNameUsageID**

Property	Value
IRI	dwc:parentNameUsageID
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-parentNameUsageID
Status	stable ☑
Label	parent name usage ID
Definition	An identifier for the name usage (documented meaning of the name according to a source) of the direct, most proximate higher-rank parent taxon (in a classification) of the most specific element of the scientificName.
Scope note	
Implementation	A tern:Taxon <i>MAY</i> have a dwc:parentNameUsageID predicate where the value node is a literal with the datatype xsd:string .
Cardinality	
Node kind	sh:Literal
Class type	xmlschema#string
Expected values	

4.1.23.24. Property: **dwc:phylum**

Property	Value
IRI	<code>dwc:phylum</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-phylum
Status	stable 
Label	phylum
Definition	The full scientific name of the phylum or division in which the taxon is classified.
Scope note	
Implementation	A <code>tern:Taxon</code> MAY have a <code>dwc:phylum</code> predicate where the value node is a literal with the datatype <code>xsd:string</code> .
Cardinality	
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#string</code>
Expected values	

4.1.23.25. Property: `dwc:scientificName`

Property	Value
IRI	<code>dwc:scientificName</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-scientificName
Status	stable 
Label	scientific name
Definition	The full scientific name, with authorship and date information if known. When forming part of an Identification, this should be the name in lowest level taxonomic rank that can be determined. This term should not contain identification qualifications, which should instead be supplied in the IdentificationQualifier term.
Scope note	
Implementation	A <code>tern:Taxon</code> MAY have a <code>dwc:scientificName</code> predicate where the value node is a literal with the datatype <code>xsd:string</code> .
Cardinality	
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#string</code>
Expected values	

4.1.23.26. Property: `dwc:scientificNameAuthorship`

Property	Value
IRI	<code>dwc:scientificNameAuthorship</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-scientificNameAuthorship
Status	stable 
Label	scientific name authorship
Definition	The authorship information for the scientificName formatted according to the conventions of the applicable nomenclaturalCode.
Scope note	
Implementation	A <code>tern:Taxon</code> MAY have a <code>dwc:scientificNameAuthorship</code> predicate where the value node is a literal with the datatype <code>xsd:string</code> .
Cardinality	
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#string</code>
Expected values	

4.1.23.27. Property: `dwc:scientificNameID`

Property	Value
IRI	<code>dwc:scientificNameID</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-scientificNameID
Status	stable 
Label	scientific name ID
Definition	An identifier for the nomenclatural (not taxonomic) details of a scientific name.
Scope note	
Implementation	A <code>tern:Taxon</code> MAY have a <code>'dwc:scientificNameID</code> predicate where the value node is a literal with the datatype <code>xsd:string</code> .
Cardinality	
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#string</code>
Expected values	

4.1.23.28. Property: `dwc:specificEpithet`

Property	Value
IRI	<code>dwc:specificEpithet</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-specificEpithet
Status	stable 

Property	Value
Label	specific epithet
Definition	The name of the first or species epithet of the scientificName.
Scope note	
Implementation	A <code>tern:Taxon</code> MAY have a <code>dwc:specificEpithet</code> predicate where the value node is a literal with the datatype <code>xsd:string</code> .
Cardinality	
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#:string</code>
Expected values	

4.1.23.29. Property: `dwc:subfamily`

Property	Value
IRI	<code>dwc:subfamily</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-subfamily
Status	<code>stable</code> ☑
Label	subfamily
Definition	The full scientific name of the subfamily in which the taxon is classified.
Scope note	
Implementation	A <code>tern:Taxon</code> MAY have a <code>dwc:subfamily</code> predicate where the value node is a literal with the datatype <code>xsd:string</code> .
Cardinality	
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#:string</code>
Expected values	

4.1.23.30. Property: `dwc:subgenus`

Property	Value
IRI	<code>dwc:subgenus</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-subgenus
Status	<code>stable</code> ☑
Label	subgenus
Definition	The full scientific name of the subgenus in which the taxon is classified. Values should include the genus to avoid homonym confusion.
Scope note	

Property	Value
Implementation	A tern:Taxon MAY have a dwc:subgenus predicate where the value node is a literal with the datatype xsd:string .
Cardinality	
Node kind	sh:Literal
Class type	xmlschema#string
Expected values	

4.1.23.31. Property: **dwc:taxonConceptID**

Property	Value
IRI	dwc:taxonConceptID
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-taxonConceptID
Status	stable ☑
Label	taxon concept ID
Definition	An identifier for the taxonomic concept to which the record refers - not for the nomenclatural details of a taxon.
Scope note	
Implementation	A tern:Taxon MAY have a dwc:taxonConceptID predicate where the value node is a literal with the datatype xsd:string .
Cardinality	
Node kind	sh:Literal
Class type	xmlschema#string
Expected values	

4.1.23.32. Property: **dwc:taxonID**

Property	Value
IRI	dwc:taxonID
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-taxonID
Status	stable ☑
Label	taxon ID
Definition	A global unique identifier for the taxon (name in a classification).
Scope note	
Implementation	A ternTaxon MAY have a dwc:taxonID predicate where the value node is a literal with the datatype xsd:string .
Cardinality	
Node kind	sh:Literal

Property	Value
Class type	<code>xmlschema#:string</code>
Expected values	

4.1.23.33. Property: `dwc:taxonRank`

Property	Value
IRI	<code>dwc:taxonRank</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-taxonRank
Status	stable 
Label	taxon rank
Definition	The taxonomic rank of the most specific name in the scientificName.
Scope note	
Implementation	A <code>tern:Taxon</code> MAY have a <code>dwc:taxonRank</code> predicate where the value node is a literal with the datatype <code>xsd:string</code> .
Cardinality	
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#:string</code>
Expected values	

4.1.23.34. Property: `dwc:taxonRemarks`

Property	Value
IRI	<code>dwc:taxonRemarks</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-taxonRemarks
Status	stable 
Label	taxon remarks
Definition	Comments or notes about the taxon or name.
Scope note	
Implementation	A <code>tern:Taxon</code> MAY have a <code>dwc:taxonRemarks</code> predicate where the value node is a literal with the datatype <code>xsd:string</code> .
Cardinality	
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#:string</code>
Expected values	

4.1.23.35. Property: **dwc:taxonomicStatus**

Property	Value
IRI	dwc:taxonomicStatus
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-taxonomicStatus
Status	stable ☑
Label	taxonomic status
Definition	The status of the use of the scientificName as a label for a taxon. Requires taxonomic opinion to define the scope of a taxon. Rules of priority then are used to define the taxonomic status of the nomenclature contained in that scope, combined with the experts opinion. It must be linked to a specific taxonomic reference that defines the concept.
Scope note	
Implementation	A tern:Taxon <i>MAY</i> have a dwc:taxonomicStatus predicate where the value node is a literal with the datatype xsd:string .
Cardinality	
Node kind	sh:Literal
Class type	xmlschema#:string
Expected values	

4.1.23.36. Property: **dwc:verbatimTaxonRank**

Property	Value
IRI	dwc:verbatimTaxonRank
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-verbatimTaxonRank
Status	stable ☑
Label	verbatim taxon rank
Definition	The taxonomic rank of the most specific name in the scientificName as it appears in the original record.
Scope note	
Implementation	A tern:Taxon <i>MAY</i> have a dwc:verbatimTaxonRank predicate where the value node is a literal with the datatype xsd:string .
Cardinality	
Node kind	sh:Literal
Class type	xmlschema#:string
Expected values	

4.1.23.37. Property: dwc:vernacularName

Property	Value
IRI	dwc:vernacularName
Shape IRI	https://w3id.org/tern/shapes/tern/Taxon-vernacularName
Status	stable 
Label	vernacular name
Definition	A common or vernacular name.
Scope note	
Implementation	A tern:Taxon <i>MAY</i> have a dwc:vernacularName predicate where the value node is a literal with the datatype xsd:string .
Cardinality	
Node kind	sh:Literal
Class type	xmlschema#string
Expected values	

4.1.24. Class: tern:Text

Property	Value
IRI	tern:Text
Status	stable 
Label	Text
Definition	Class to encapsulate a textual value.
Scope note	

4.1.24.1. Property: rdf:value

Property	Value
IRI	rdf:value
Shape IRI	https://w3id.org/tern/shapes/tern/Text-value
Status	stable 
Label	value
Definition	The text value.
Scope note	
Implementation	A tern:Text <i>MUST</i> have exactly 1 rdf:value predicate where the value node is a literal with the datatype xsd:string or rdf:langString .
Cardinality	Exactly 1
Node kind	

Property	Value
Class type	<code>xmlschema#:string</code> <code>22-rdf-syntax-ns#langString</code>
Expected values	

4.1.25. Class: `tern:Transect`

Property	Value
IRI	<code>tern:Transect</code>
Status	<code>stable</code> 
Label	Transect
Definition	A transect is a path where observations and samplings may occur.
Scope note	There are several types of transects in ecology such as strip transects, line transects, belt transects, point transects and curved line transects.

4.1.25.1. Property: `tern:hasSiteVisit`

Property	Value
IRI	<code>tern:hasSiteVisit</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Site-hasSiteVisit
Status	<code>stable</code> 
Label	has site visit
Definition	A property that links, e.g., a Site to a Site Visit.
Scope note	
Implementation	A <code>tern:Site</code> MAY have a <code>tern:hasSiteVisit</code> predicate where the value node is an IRI of type <code>tern:SiteVisit</code> .
Cardinality	
Node kind	<code>sh:IRI</code>
Class type	<code>tern:SiteVisit</code>
Expected values	

4.1.25.2. Property: `tern:featureType`

Property	Value
IRI	<code>tern:featureType</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Transect-featureType
Status	<code>stable</code> 
Label	feature type

Property	Value
Definition	The feature type of a [Feature of Interest](#FeatureofInterest).
Scope note	
Implementation	A tern:Transect <i>MUST</i> have exactly 1 tern:featureType predicate where the value node is an IRI with the value http://linked.data.gov.au/def/tern-cv/de46fa49-d1c9-4bef-8462-d7ee5174e1e1 .
Cardinality	Exactly 1
Node kind	sh:IRI
Class type	
Expected values	

4.1.25.3. Property: **geo:hasGeometry**

Property	Value
IRI	geo:hasGeometry
Shape IRI	https://w3id.org/tern/shapes/tern/Transect-hasGeometry
Status	stable ☑
Label	has geometry
Definition	A spatial representation for a given feature.
Scope note	
Implementation	A tern:Transect <i>MAY</i> have a maximum of 1 geo:hasGeometry predicate where the value node is a blank node or IRI of type sf:LineString or geo:Geometry .
Cardinality	Maximum 1
Node kind	sh:BlankNodeOrIRI
Class type	sf#:LineString geosparql#:Geometry
Expected values	

4.1.25.4. Property: **sdo:spatial**

Property	Value
IRI	sdo:spatial
Shape IRI	https://w3id.org/tern/shapes/tern/Transect-spatial
Status	stable ☑
Label	spatial
Definition	A spatial representation for a given feature.
Scope note	

Property	Value
Implementation	A tern:Transect <i>MAY</i> have a maximum of 1 sdo:spatial predicate where the value node is a blank node or IRI of type sf:LineString or geo:Geometry .
Cardinality	Maximum 1
Node kind	sh:BlankNodeOrIRI
Class type	sf#:LineString geosparql#:Geometry
Expected values	

4.1.25.5. Property: **tern:transectDirection**

Property	Value
IRI	tern:transectDirection
Shape IRI	https://w3id.org/tern/shapes/tern/Transect-transectDirection
Status	stable 
Label	transect direction
Definition	Describes the direction of the transect.
Scope note	
Implementation	A tern:Transect <i>MAY</i> have a maximum of 1 tern:transectDirection where the value node is an IRI or literal.
Cardinality	Maximum 1
Node kind	sh:IRIOrLiteral
Class type	
Expected values	

4.1.25.6. Property: **tern:transectEndPoint**

Property	Value
IRI	tern:transectEndPoint
Shape IRI	https://w3id.org/tern/shapes/tern/Transect-transectEndPoint
Status	stable 
Label	transect end point
Definition	Relationship to the sf:Point or geo:Geometry representing the end of a transect.
Scope note	
Implementation	A tern:Transect <i>MAY</i> have a maximum of 1 tern:transectEndPoint predicate where the value node is an IRI of type sf:Point or geo:Geometry .
Cardinality	Maximum 1

Property	Value
Node kind	
Class type	<code>sf#:Point</code> <code>geosparql#:Geometry</code>
Expected values	

4.1.25.7. Property: `tern:transectStartPoint`

Property	Value
IRI	<code>tern:transectStartPoint</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Transect-transectStartPoint
Status	stable 
Label	transect start point
Definition	Relationship to the <code>sf:Point</code> or <code>geo:Geometry</code> representing the start of a transect.
Scope note	
Implementation	A <code>tern:Transect</code> <i>MAY</i> have a maximum of 1 <code>tern:transectStartPoint</code> predicate where the value node is an IRI of type <code>sf:Point</code> or <code>geo:Geometry</code> .
Cardinality	Maximum 1
Node kind	
Class type	<code>sf#:Point</code> <code>geosparql#:Geometry</code>
Expected values	

4.1.25.8. Property: `sosa:hasSample`

Property	Value
IRI	<code>sosa:hasSample</code>
Shape IRI	https://w3id.org/tern/shapes/tern/sosa-hasSample
Status	stable 
Label	has sample
Definition	Relation between a <code>FeatureOfInterest</code> and the <code>Sample</code> used to represent it.
Scope note	
Implementation	A <code>tern:FeatureOfInterest</code> <i>MAY</i> have a <code>sosa:hasSample</code> predicate where the value node is an IRI of type <code>tern:Sample</code> .
Cardinality	
Node kind	

Property	Value
Class type	<code>tern:Sample</code> <code>tern:MaterialSample</code>
Expected values	

4.1.26. Class: `tern:Value`

Property	Value
IRI	<code>tern:Value</code>
Status	<code>stable</code> ✓
Label	Value
Definition	A value of an <code>Attribute</code> or an <code>Observation</code> .
Scope note	This is an 'abstract' class and is not intended to be used directly to create individuals.

4.1.26.1. Property: `tern:unit`

Property	Value
IRI	<code>tern:unit</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Value-unit
Status	<code>stable</code> ✓
Label	unit
Definition	The unit of the <code>tern:Value</code> .
Scope note	
Implementation	A <code>tern:Value</code> <i>MAY</i> have maximum one <code>tern:unit</code> predicate where the value is an IRI.
Cardinality	Maximum 1
Node kind	<code>sh:IRI</code>
Class type	
Expected values	

4.1.26.2. Property: `rdf:value`

Property	Value
IRI	<code>rdf:value</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Value-value
Status	<code>stable</code> ✓
Label	value

Property	Value
Definition	The value of the tern:Value .
Scope note	
Implementation	A tern:Value <i>MUST</i> have exactly one rdf:value predicate.
Cardinality	Exactly 1
Node kind	sh:Literal
Class type	
Expected values	

4.1.26.3. Property: void:inDataset

Property	Value
IRI	void:inDataset
Shape IRI	https://w3id.org/tern/shapes/tern/void-inDataset
Status	stable 
Label	in dataset
Definition	A link to the RDF payload's metadata which this resource was a part of.
Scope note	
Implementation	There <i>MUST</i> exist exactly 1 void:inDataset property with an IRI value to a tern:RDFDataset .
Cardinality	Exactly 1
Node kind	sh:IRI
Class type	tern:RDFDataset
Expected values	

4.1.27. Class: tern:Calibration

Property	Value
IRI	tern:Calibration
Status	experimental 
Label	Calibration
Definition	An activity to calibrate properties of a System (such as a Sensor or Sampler) to ensure accurate measurements and proper functioning of the device.
Scope note	

4.1.27.1. Property: dcterms:description

Property	Value
IRI	<code>dcterms:description</code>
Shape IRI	https://w3id.org/tern/shapes/tern/dcterms-description
Status	stable 
Label	description
Definition	A textual description.
Scope note	
Implementation	A <code>dcterms:description</code> predicate has a literal value with the datatype <code>xsd:string</code> .
Cardinality	
Node kind	
Class type	<code>xmlschema#string</code>
Expected values	

4.1.27.2. Property: `prov:endedAtTime`

Property	Value
IRI	<code>prov:endedAtTime</code>
Shape IRI	https://w3id.org/tern/shapes/tern/prov-endedAtTime
Status	stable 
Label	ended at time
Definition	The time at which an activity ended.
Scope note	
Implementation	A <code>tern:Survey</code> , <code>tern:SiteVisit</code> or a <code>tern:Intervention</code> <i>MAY</i> have a maximum of 1 <code>prov:endedAtTime</code> predicate where the value node is a literal with the datatype <code>xsd:dateTime</code> .
Cardinality	Maximum 1
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#dateTime</code>
Expected values	

4.1.27.3. Property: `prov:startedAtTime`

Property	Value
IRI	<code>prov:startedAtTime</code>
Shape IRI	https://w3id.org/tern/shapes/tern/prov-startedAtTime
Status	stable 

Property	Value
Label	started at time
Definition	The time at which an activity started.
Scope note	
Implementation	A <code>tern:Survey</code> , <code>tern:SiteVisit</code> or a <code>tern:Intervention</code> <i>MUST</i> have exactly 1 <code>prov:startedAtTime</code> predicate where the value node is a literal with the datatype <code>xsd:dateTime</code> .
Cardinality	Exactly 1
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#dateTime</code>
Expected values	

4.1.27.4. Property: `sosa:usedProcedure`

Property	Value
IRI	<code>sosa:usedProcedure</code>
Shape IRI	https://w3id.org/tern/shapes/tern/sosa-usedProcedure
Status	<code>stable</code> 
Label	used procedure
Definition	A relation to link to a re-usable Procedure used in making an Observation, an Actuation, or a Sample, typically through a Sensor, Actuator or Sampler.
Scope note	
Implementation	Exactly 1 <code>sosa:usedProcedure</code> <i>MUST</i> exist where the value node is a <code>tern:Method</code> or <code>tern:Procedure</code> .
Cardinality	Exactly 1
Node kind	
Class type	<code>tern:Procedure</code> <code>tern:Method</code>
Expected values	

4.1.27.5. Property: `tern:calibratedBy`

Property	Value
IRI	<code>tern:calibratedBy</code>
Shape IRI	https://w3id.org/tern/shapes/tern/tern-calibratedBy
Status	<code>experimental</code> 
Label	calibrated by

Property	Value
Definition	Indicates the agent (person, organization, or service) that performed the calibration activity. This property links a Calibration to the responsible agent.
Scope note	
Implementation	A <code>tern:calibratedBy</code> predicate <i>MUST</i> have an IRI value of type <code>prov:Agent</code> .
Cardinality	
Node kind	<code>sh:IRI</code>
Class type	<code>prov#:Agent</code>
Expected values	

4.1.27.6. Property: `tern:calibratesProperty`

Property	Value
IRI	<code>tern:calibratesProperty</code>
Shape IRI	https://w3id.org/tern/shapes/tern/tern-calibratesProperty
Status	<code>experimental</code> ○
Label	calibrates property
Definition	Relation from a calibration activity to a system property that is being calibrated. This property is used to specify which system property is the target of the calibration.
Scope note	
Implementation	A <code>tern:calibratesProperty</code> predicate <i>MUST</i> have an IRI or blank node value of type <code>ssn-system:SystemProperty</code> .
Cardinality	
Node kind	<code>n823711835ce84c68b7240bbe1a8755afb249</code>
Class type	<code>systems:SystemProperty</code>
Expected values	

4.1.27.7. Property: `tern:calibrationActualResult`

Property	Value
IRI	<code>tern:calibrationActualResult</code>
Shape IRI	https://w3id.org/tern/shapes/tern/tern-calibrationActualResult
Status	<code>experimental</code> ○
Label	calibration actual result
Definition	Links to the actual measured value obtained during calibration. This represents the value returned by the system or device being calibrated.
Scope note	

Property	Value
Implementation	A tern:Calibration <i>MAY</i> have maximum one tern:calibrationActualResult predicate where the value is a blank node or IRI of type tern:Value .
Cardinality	Maximum 1
Node kind	sh:BlankNodeOrIRI
Class type	tern:Value
Expected values	

4.1.27.8. Property: **tern:calibrationOffset**

Property	Value
IRI	tern:calibrationOffset
Shape IRI	https://w3id.org/tern/shapes/tern/tern-calibrationOffset
Status	experimental ○
Label	calibration offset
Definition	Links to a value representing the difference between the reference and actual results during calibration. This offset can be used for measurement corrections.
Scope note	
Implementation	A tern:Calibration <i>MAY</i> have maximum one tern:calibrationOffset predicate where the value is a blank node or IRI of type tern:Value .
Cardinality	Maximum 1
Node kind	sh:BlankNodeOrIRI
Class type	tern:Value
Expected values	

4.1.27.9. Property: **tern:calibrationReferenceResult**

Property	Value
IRI	tern:calibrationReferenceResult
Shape IRI	https://w3id.org/tern/shapes/tern/tern-calibrationReferenceResult
Status	experimental ○
Label	calibration reference result
Definition	Links to a reference value used during calibration. This represents the known, standard, or expected value against which the actual measurement is compared.
Scope note	

Property	Value
Implementation	A tern:Calibration <i>MAY</i> have maximum one tern:calibrationReferenceResult predicate where the value is a blank node or IRI of type tern:Value .
Cardinality	Maximum 1
Node kind	sh:BlankNodeOrIRI
Class type	tern:Value
Expected values	

4.1.27.10. Property: **tern:verifiesCapability**

Property	Value
IRI	tern:verifiesCapability
Shape IRI	https://w3id.org/tern/shapes/tern/tern-verifiesCapability
Status	experimental ○
Label	verifies capability
Definition	Relation from a calibration activity to a system capability that is being verified. This property is used to specify which system capability is being confirmed or validated.
Scope note	
Implementation	A tern:verifiesCapability predicate <i>MUST</i> have an IRI or blank node value of type ssn-system:SystemCapability .
Cardinality	
Node kind	n823711835ce84c68b7240bbe1a8755afb268
Class type	systems:SystemCapability
Expected values	

4.1.28. Class: **tern:IGSN**

Property	Value
IRI	tern:IGSN
Status	experimental ○
Label	IGSN
Definition	A globally unique identifier assigned to physical samples to enable traceability, citation, and reuse in scientific research, adhering to FAIR data principles.
Scope note	

4.1.28.1. Property: **geo:hasGeometry**

Property	Value
IRI	geo:hasGeometry
Shape IRI	https://w3id.org/tern/shapes/tern/IGSN-hasGeometry
Status	experimental ○
Label	IGSN hasGeometry
Definition	This SHACL shape defines constraints for the geo:hasGeometry property. It specifies that values of the geo:hasGeometry property of tern:IGSN must be IRIs of type geo:Geometry . The status of this shape is experimental, indicating that it might be subject to change in the future.
Scope note	
Implementation	A tern:IGSN <i>MUST</i> have at least 1 geo:hasGeometry of type geo:Geometry .
Cardinality	Minimum 1
Node kind	sh:IRI
Class type	geosparql#:Geometry
Expected values	

4.1.28.2. Property: [dcterms:hasPart](#)

Property	Value
IRI	dcterms:hasPart
Shape IRI	https://w3id.org/tern/shapes/tern/IGSN-hasPart
Status	experimental ○
Label	IGSN hasPart
Definition	This SHACL shape defines constraints for the dcterms:hasPart property. It specifies that values of the dcterms:hasPart property of tern:IGSN must be IRIs of type tern:IGSN . The status of this shape is experimental, indicating that it might be subject to change in the future.
Scope note	
Implementation	A dcterms:hasPart predicate <i>MUST</i> have an IRI value of type tern:IGSN .
Cardinality	
Node kind	
Class type	tern:IGSN
Expected values	

4.1.28.3. Property: [dcterms:isPartOf](#)

Property	Value
IRI	dcterms:isPartOf

Property	Value
Shape IRI	https://w3id.org/tern/shapes/tern/IGSN-isPartOf
Status	experimental ○
Label	IGSN isPartOf
Definition	This SHACL shape defines constraints for the <code>dcterms:isPartOf</code> property. It specifies that values of the <code>dcterms:isPartOf</code> property of <code>tern:IGSN</code> must be IRIs of type <code>tern:IGSN</code> . The status of this shape is experimental, indicating that it might be subject to change in the future.
Scope note	
Implementation	A <code>dcterms:isPartOf</code> predicate <i>MUST</i> have an IRI value of type <code>tern:IGSN</code> .
Cardinality	
Node kind	
Class type	<code>tern:IGSN</code>
Expected values	

4.1.28.4. Property: `dcterms:publisher`

Property	Value
IRI	<code>dcterms:publisher</code>
Shape IRI	https://w3id.org/tern/shapes/tern/IGSN-publisher
Status	experimental ○
Label	IGSN publisher
Definition	This SHACL shape defines constraints for the <code>dcterms:publisher</code> property. It specifies that values of the <code>dcterms:publisher</code> property of <code>tern:IGSN</code> must be IRIs of specified types. The status of this shape is experimental, indicating that it might be subject to change in the future.
Scope note	
Implementation	A <code>dcterms:publisher</code> predicate <i>MUST</i> have an IRI value of type <code>tern:IGSN</code> .
Cardinality	Minimum 1
Node kind	<code>sh:IRI</code>
Class type	<code>schema.org:Organization</code> <code>schema.org:Project</code> <code>prov#:Agent</code>
Expected values	

4.1.28.5. Property: `dcterms:relation`

Property	Value
IRI	<code>dcterms:relation</code>

Property	Value
Shape IRI	https://w3id.org/tern/shapes/tern/IGSN-relation
Status	experimental ○
Label	IGSN relation
Definition	This SHACL shape defines constraints for the <code>dcterms:relation</code> property. It specifies that values of the <code>dcterms:relation</code> property of <code>tern:IGSN</code> must be IRIs of type <code>tern:IGSN</code> . The status of this shape is experimental, indicating that it might be subject to change in the future.
Scope note	
Implementation	A <code>dcterms:relation</code> predicate <i>MUST</i> have an IRI value of type <code>tern:IGSN</code> .
Cardinality	
Node kind	
Class type	<code>tern:IGSN</code>
Expected values	

4.1.28.6. Property: `tern:sampleSubType`

Property	Value
IRI	<code>tern:sampleSubType</code>
Shape IRI	https://w3id.org/tern/shapes/tern/tern-sampleSubType
Status	experimental ○
Label	sample sub type
Definition	The sample sub type of a <code>tern:IGSN</code> from a controlled vocabulary.
Scope note	
Implementation	A <code>tern:IGSN</code> <i>MUST</i> have exactly 1 <code>tern:sampleSubType</code> predicate where the value node is an IRI.
Cardinality	Exactly 1
Node kind	<code>sh:IRI</code>
Class type	
Expected values	

4.1.28.7. Property: `tern:sampleType`

Property	Value
IRI	<code>tern:sampleType</code>
Shape IRI	https://w3id.org/tern/shapes/tern/tern-sampleType
Status	experimental ○
Label	sample type

Property	Value
Definition	The sample type of a tern:IGSN from a controlled vocabulary.
Scope note	
Implementation	A tern:IGSN <i>MUST</i> have exactly 1 tern:sampleType predicate where the value node is an IRI.
Cardinality	Exactly 1
Node kind	sh:IRI
Class type	
Expected values	

4.1.29. Class: **tern:Input**

Property	Value
IRI	tern:Input
Status	experimental ○
Label	Input
Definition	Input - Any information that is provided to a Procedure for its use.
Scope note	

4.1.29.1. Property: **dcterms:description**

Property	Value
IRI	dcterms:description
Shape IRI	nb24bd8a488304acfa438a053cbc2bc64b30
Status	experimental ○
Label	input description
Definition	The description of the input.
Scope note	
Implementation	If present, dcterms:description predicates on a tern:Input <i>MUST</i> have string values.
Cardinality	
Node kind	
Class type	
Expected values	

4.1.29.2. Property: **rdf:value**

Property	Value
IRI	rdf:value
Shape IRI	nb24bd8a488304acfa438a053cbc2bc64b31
Status	experimental ○
Label	input value
Definition	The value of the input.
Scope note	
Implementation	A tern:Input <i>MAY</i> have at most 1 rdf:value predicate.
Cardinality	Maximum 1
Node kind	
Class type	
Expected values	

4.1.29.3. Property: [rdfs:label](#)

Property	Value
IRI	rdfs:label
Shape IRI	nb24bd8a488304acfa438a053cbc2bc64b32
Status	experimental ○
Label	input label
Definition	The label of the input.
Scope note	
Implementation	A tern:Input <i>MUST</i> have exactly 1 rdfs:label predicate with a string value.
Cardinality	Exactly 1
Node kind	
Class type	
Expected values	

4.1.29.4. Property: [tern:hasAttribute](#)

Property	Value
IRI	tern:hasAttribute
Shape IRI	https://w3id.org/tern/shapes/tern/tern-hasAttribute
Status	stable ✓
Label	has attribute
Definition	Link to an Attribute.

Property	Value
Scope note	
Implementation	A <code>tern:hasAttribute</code> predicate <i>MUST</i> have a blank node or an IRI value of type <code>tern:Attribute</code> .
Cardinality	
Node kind	<code>sh:BlankNodeOrIRI</code>
Class type	<code>tern:Attribute</code>
Expected values	

4.1.29.5. Property: `void:inDataset`

Property	Value
IRI	<code>void:inDataset</code>
Shape IRI	https://w3id.org/tern/shapes/tern/void-inDataset
Status	<code>stable</code> ✓
Label	in dataset
Definition	A link to the RDF payload's metadata which this resource was a part of.
Scope note	
Implementation	There <i>MUST</i> exist exactly 1 <code>void:inDataset</code> property with an IRI value to a <code>tern:RDFDataset</code> .
Cardinality	Exactly 1
Node kind	<code>sh:IRI</code>
Class type	<code>tern:RDFDataset</code>
Expected values	

4.1.30. Class: `tern:MeasurementRange`

Property	Value
IRI	<code>tern:MeasurementRange</code>
Status	<code>experimental</code> ○
Label	Measurement Range
Definition	The set of values that the Sensor can return as the Result of an Observation under the defined Conditions with the defined system properties.
Scope note	

4.1.30.1. Property: `qudt:maxExclusive`

Property	Value
IRI	<code>qudt:maxExclusive</code>
Shape IRI	https://w3id.org/tern/shapes/tern/qudt-maxExclusive
Status	experimental ○
Label	maximum exclusive value
Definition	The exclusive upper bound of the measurement range. This value represents the value just above the maximum that can be measured by the sensor.
Scope note	
Implementation	A <code>qudt:maxExclusive</code> predicate <i>MAY</i> have maximum one literal value representing the exclusive upper bound of the measurement range.
Cardinality	Maximum 1
Node kind	<code>sh:Literal</code>
Class type	
Expected values	

4.1.30.2. Property: `qudt:maxInclusive`

Property	Value
IRI	<code>qudt:maxInclusive</code>
Shape IRI	https://w3id.org/tern/shapes/tern/qudt-maxInclusive
Status	experimental ○
Label	maximum inclusive value
Definition	The inclusive upper bound of the measurement range. This value represents the maximum value that can be measured by the sensor.
Scope note	
Implementation	A <code>qudt:maxInclusive</code> predicate <i>MAY</i> have maximum one literal value representing the upper bound of the measurement range.
Cardinality	Maximum 1
Node kind	<code>sh:Literal</code>
Class type	
Expected values	

4.1.30.3. Property: `qudt:minExclusive`

Property	Value
IRI	<code>qudt:minExclusive</code>
Shape IRI	https://w3id.org/tern/shapes/tern/qudt-minExclusive
Status	experimental ○

Property	Value
Label	minimum exclusive value
Definition	The exclusive lower bound of the measurement range. This value represents the value just below the minimum that can be measured by the sensor.
Scope note	
Implementation	A <code>qudt:minExclusive</code> predicate <i>MAY</i> have maximum one literal value representing the exclusive lower bound of the measurement range.
Cardinality	Maximum 1
Node kind	<code>sh:Literal</code>
Class type	
Expected values	

4.1.30.4. Property: `qudt:minInclusive`

Property	Value
IRI	<code>qudt:minInclusive</code>
Shape IRI	https://w3id.org/tern/shapes/tern/qudt-minInclusive
Status	<code>experimental</code> ○
Label	minimum inclusive value
Definition	The inclusive lower bound of the measurement range. This value represents the minimum value that can be measured by the sensor.
Scope note	
Implementation	A <code>qudt:minInclusive</code> predicate <i>MAY</i> have maximum one literal value representing the lower bound of the measurement range.
Cardinality	Maximum 1
Node kind	<code>sh:Literal</code>
Class type	
Expected values	

4.1.30.5. Property: `tern:unit`

Property	Value
IRI	<code>tern:unit</code>
Shape IRI	https://w3id.org/tern/shapes/tern/tern-unit
Status	<code>stable</code> ☑
Label	unit of measure
Definition	The unit of measure of the value. Recommended best practice is to use the QUDT units of measure vocabulary .

Property	Value
Scope note	
Implementation	A tern:unit predicate <i>MUST</i> have an IRI value.
Cardinality	Maximum 1
Node kind	sh:IRI
Class type	
Expected values	

4.1.31. Class: tern:Method

Property	Value
IRI	tern:Method
Status	stable ☑
Label	Method
Definition	A Method describes in detailed steps how a workflow, protocol, plan or algorithm is carried out to make an Observation or a Sample. It explains the steps to be carried out to arrive at reproducible Result.
Scope note	

4.1.31.1. Property: schema:timeRequired

Property	Value
IRI	schema:timeRequired
Shape IRI	n11c9b6dbf289454786d8c185e1488e3eb51
Status	experimental ○
Label	method required duration
Definition	The time required for the method.
Scope note	
Implementation	A tern:Method <i>MAY</i> have at most 1 schema:timeRequired predicate with a string value.
Cardinality	Maximum 1
Node kind	
Class type	
Expected values	

4.1.31.2. Property: skos:note

Property	Value
IRI	skos:note
Shape IRI	n11c9b6dbf289454786d8c185e1488e3eb52
Status	stable 
Label	note of method
Definition	Notes about the method.
Scope note	
Implementation	If present, skos:note predicates on a tern:Method <i>MUST</i> have string values.
Cardinality	
Node kind	
Class type	
Expected values	

4.1.31.3. Property: [tern:hasCategoricalCollection](#)

Property	Value
IRI	tern:hasCategoricalCollection
Shape IRI	n11c9b6dbf289454786d8c185e1488e3eb53
Status	experimental 
Label	categorical collection of method
Definition	The categorical collection of the method.
Scope note	
Implementation	If present, tern:hasCategoricalCollection predicates on a tern:Method <i>MUST</i> have values of type skos:Collection .
Cardinality	
Node kind	
Class type	
Expected values	

4.1.31.4. Property: [tern:hasParameter](#)

Property	Value
IRI	tern:hasParameter
Shape IRI	n11c9b6dbf289454786d8c185e1488e3eb54
Status	experimental 
Label	parameter of method
Definition	The parameters of the method.

Property	Value
Scope note	
Implementation	If present, <code>tern:hasParameter</code> predicates on a <code>tern:Method</code> <i>MUST</i> have values of type <code>skos:Concept</code> .
Cardinality	
Node kind	
Class type	
Expected values	

4.1.31.5. Property: `dcterms:source`

Property	Value
IRI	<code>dcterms:source</code>
Shape IRI	<code>n11c9b6dbf289454786d8c185e1488e3eb55</code>
Status	<code>stable</code> ☑
Label	digital camera preferred label
Definition	The source of the method.
Scope note	
Implementation	If present, <code>dcterms:source</code> predicates on a <code>tern:Method</code> <i>MUST</i> have string or URI values.
Cardinality	
Node kind	
Class type	
Expected values	

4.1.31.6. Property: `tern:instructions`

Property	Value
IRI	<code>tern:instructions</code>
Shape IRI	<code>n11c9b6dbf289454786d8c185e1488e3eb60</code>
Status	<code>stable</code> ☑
Label	method instructions
Definition	The instructions for the method.
Scope note	
Implementation	A <code>tern:Method</code> <i>MAY</i> have at most 1 <code>tern:instructions</code> predicate with a value of type <code>rdf:Seq</code> .
Cardinality	Maximum 1

Property	Value
Node kind	
Class type	
Expected values	

4.1.31.7. Property: skos:definition

Property	Value
IRI	skos:definition
Shape IRI	n11c9b6dbf289454786d8c185e1488e3eb61
Status	stable ☑
Label	method definition
Definition	The definition of the method.
Scope note	
Implementation	A tern:Method <i>MAY</i> have at most 1 skos:definition predicate with a string value.
Cardinality	Maximum 1
Node kind	
Class type	
Expected values	

4.1.31.8. Property: tern:equipment

Property	Value
IRI	tern:equipment
Shape IRI	n11c9b6dbf289454786d8c185e1488e3eb62
Status	stable ☑
Label	method equipment
Definition	The equipment used for the method.
Scope note	
Implementation	A tern:Method <i>MAY</i> have at most 1 tern:equipment predicate with a value of type skos:Concept .
Cardinality	Maximum 1
Node kind	
Class type	
Expected values	

4.1.31.9. Property: tern:purpose

Property	Value
IRI	tern:purpose
Shape IRI	n11c9b6dbf289454786d8c185e1488e3eb63
Status	stable 
Label	method purpose
Definition	The purpose of the method.
Scope note	
Implementation	A tern:Method MAY have at most 1 tern:purpose predicate with a string value.
Cardinality	Maximum 1
Node kind	
Class type	
Expected values	

4.1.31.10. Property: tern:scope

Property	Value
IRI	tern:scope
Shape IRI	n11c9b6dbf289454786d8c185e1488e3eb64
Status	stable 
Label	method scope
Definition	The scope of the method.
Scope note	
Implementation	A tern:Method MAY have at most 1 tern:scope predicate with a string value.
Cardinality	Maximum 1
Node kind	
Class type	
Expected values	

4.1.31.11. Property: skos:prefLabel

Property	Value
IRI	skos:prefLabel
Shape IRI	n11c9b6dbf289454786d8c185e1488e3eb65
Status	stable 
Label	method preferred label

Property	Value
Definition	The preferred label of the method.
Scope note	
Implementation	A tern:Method <i>MUST</i> have exactly 1 skos:prefLabel predicate with a string value.
Cardinality	Exactly 1
Node kind	
Class type	
Expected values	

4.1.31.12. Property: **tern:undertakenAfter**

Property	Value
IRI	tern:undertakenAfter
Shape IRI	https://w3id.org/tern/shapes/tern/tern-undertakenAfter
Status	experimental ○
Label	undertaken after
Definition	Link to a Method.
Scope note	
Implementation	A tern:undertakenAfter predicate <i>MUST</i> have an IRI value of type tern:Method .
Cardinality	
Node kind	
Class type	tern:Method
Expected values	

4.1.31.13. Property: **tern:undertakenBefore**

Property	Value
IRI	tern:undertakenBefore
Shape IRI	https://w3id.org/tern/shapes/tern/tern-undertakenBefore
Status	experimental ○
Label	undertaken before
Definition	Link to a Method.
Scope note	
Implementation	A tern:undertakenBefore predicate <i>MUST</i> have an IRI value of type tern:Method .
Cardinality	
Node kind	

Property	Value
Class type	<code>tern:Method</code>
Expected values	

4.1.31.14. Property: `tern:undertakenComplementarily`

Property	Value
IRI	<code>tern:undertakenComplementarily</code>
Shape IRI	https://w3id.org/tern/shapes/tern/tern-undertakenComplementarily
Status	experimental ○
Label	undertaken complementarily
Definition	Link to a Method.
Scope note	
Implementation	A <code>tern:undertakenComplementarily</code> predicate <i>MUST</i> have an IRI value of type <code>tern:Method</code> .
Cardinality	
Node kind	
Class type	<code>tern:Method</code>
Expected values	

4.1.31.15. Property: `tern:undertakenConcurrently`

Property	Value
IRI	<code>tern:undertakenConcurrently</code>
Shape IRI	https://w3id.org/tern/shapes/tern/tern-undertakenConcurrently
Status	experimental ○
Label	undertaken concurrently
Definition	Link to a Method.
Scope note	
Implementation	A <code>tern:undertakenConcurrently</code> predicate <i>MUST</i> have an IRI value of type <code>tern:Method</code> .
Cardinality	
Node kind	
Class type	<code>tern:Method</code>
Expected values	

4.1.32. Class: tern:Platform

Property	Value
IRI	<code>tern:Platform</code>
Status	stable 
Label	Platform
Definition	An entity that hosts other entities, particularly Sensors, Samplers, and other Platforms.
Scope note	

4.1.32.1. Property: dcterms:description

Property	Value
IRI	<code>dcterms:description</code>
Shape IRI	https://w3id.org/tern/shapes/tern/dcterms-description
Status	stable 
Label	description
Definition	A textual description.
Scope note	
Implementation	A <code>dcterms:description</code> predicate has a literal value with the datatype <code>xsd:string</code> .
Cardinality	
Node kind	
Class type	<code>xmlschema#:string</code>
Expected values	

4.1.32.2. Property: geo:hasGeometry

Property	Value
IRI	<code>geo:hasGeometry</code>
Shape IRI	https://w3id.org/tern/shapes/tern/geo-hasGeometry
Status	stable 
Label	has geometry
Definition	A spatial representation for a given feature.
Scope note	
Implementation	A <code>geo:hasGeometry</code> predicate <i>MUST</i> have a blank node or IRI value.
Cardinality	
Node kind	<code>sh:BlankNodeOrIRI</code>

Property	Value
Class type	<code>geosparql#:Geometry</code>
Expected values	

4.1.32.3. Property: `sdo:spatial`

Property	Value
IRI	<code>sdo:spatial</code>
Shape IRI	https://w3id.org/tern/shapes/tern/sdo-spatial
Status	<code>experimental</code> ○
Label	spatial
Definition	A spatial representation for a given feature.
Scope note	
Implementation	A <code>sdo:spatial</code> predicate <i>MUST</i> have a blank node or IRI value.
Cardinality	
Node kind	<code>sh:BlankNodeOrIRI</code>
Class type	<code>geosparql#:Geometry</code>
Expected values	

4.1.32.4. Property: `tern:climateCode`

Property	Value
IRI	<code>tern:climateCode</code>
Shape IRI	https://w3id.org/tern/shapes/tern/tern-climateCode
Status	<code>stable</code> ☑
Label	climate code
Definition	The Köppen Climate Classification code that categorizes climates based on temperature, precipitation, and seasonal patterns. It was developed by Wladimir Köppen in 1884 and has been refined over time.
Scope note	
Implementation	A <code>tern:climateCode</code> predicate <i>MAY</i> have an IRI value or a literal value.
Cardinality	
Node kind	
Class type	
Expected values	

4.1.32.5. Property: tern:dateCommissioned

Property	Value
IRI	<code>tern:dateCommissioned</code>
Shape IRI	https://w3id.org/tern/shapes/tern/tern-dateCommissioned
Status	stable 
Label	date commissioned
Definition	The date when, e.g., a Site is ready to commence its operations, after it is successfully installed and tested.
Scope note	
Implementation	A managed feature <i>MUST</i> have exactly 1 <code>tern:dateCommissioned</code> predicate where the value node is a literal with the datatype <code>xsd:date</code> .
Cardinality	Exactly 1
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#:date</code>
Expected values	

4.1.32.6. Property: tern:dateDecommissioned

Property	Value
IRI	<code>tern:dateDecommissioned</code>
Shape IRI	https://w3id.org/tern/shapes/tern/tern-dateDecommissioned
Status	stable 
Label	date decommissioned
Definition	The date when, e.g., a Site is decommissioned or stopped operating.
Scope note	
Implementation	A managed feature <i>MAY</i> have a maximum of 1 <code>tern:dateDecommissioned</code> predicate where the value node is a literal with the datatype <code>xsd:date</code> .
Cardinality	Maximum 1
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#:date</code>
Expected values	

4.1.32.7. Property: tern:platformType

Property	Value
IRI	<code>tern:platformType</code>
Shape IRI	https://w3id.org/tern/shapes/tern/tern-platformType

Property	Value
Status	stable 
Label	platform type
Definition	The type of platform.
Scope note	
Implementation	A <code>tern:Platform</code> <i>MUST</i> have exactly 1 <code>tern:platformType</code> predicate where the value node is a <code>skos:Concept</code> .
Cardinality	Exactly 1
Node kind	
Class type	<code>core#:Concept</code>
Expected values	

4.1.32.8. Property: `tern:purpose`

Property	Value
IRI	<code>tern:purpose</code>
Shape IRI	https://w3id.org/tern/shapes/tern/tern-purpose
Status	stable 
Label	purpose
Definition	Describe the purpose of something.
Scope note	
Implementation	A <code>tern:purpose</code> predicate has a literal value with the datatype <code>xsd:string</code> .
Cardinality	
Node kind	
Class type	<code>xmlschema#:string</code>
Expected values	

4.1.33. Class: `tern:Procedure`

Property	Value
IRI	<code>tern:Procedure</code>
Status	stable 
Label	Procedure

Property	Value
Definition	A workflow, protocol, plan, algorithm, or computational method specifying how to make an Observation, create a Sample, or make a change to the state of the world (via an [Actuator](http://w3.org/ns/sosa/Actuator). A Procedure is reusable, and might be involved in many Observation, Sampling, or [Actuations](http://w3.org/ns/sosa/Actuation). it explains the steps to be carried out to arrive at a reproducible Result.
Scope note	Input can be used to capture any input values for a procedure, such as the input value of the basal wedge to estimate the basal area per hectare.

4.1.33.1. Property: tern:vocabulary

Property	Value
IRI	tern:vocabulary
Shape IRI	n2be5b758ef2047ccb746d28ad8becc0cb82
Status	experimental ○
Label	vocabulary of procedure
Definition	The vocabulary of the procedure.
Scope note	
Implementation	A tern:Procedure <i>MUST</i> have exactly 1 tern:vocabulary predicate.
Cardinality	Exactly 1
Node kind	
Class type	
Expected values	

4.1.33.2. Property: ssn:hasInput

Property	Value
IRI	ssn:hasInput
Shape IRI	n2be5b758ef2047ccb746d28ad8becc0cb83
Status	experimental ○
Label	procedure has input
Definition	The input of the procedure.
Scope note	
Implementation	A tern:Procedure <i>MAY</i> have at most 1 ssn:hasInput predicate with a value of type tern:Input .
Cardinality	Maximum 1
Node kind	

Property	Value
Class type	
Expected values	

4.1.33.3. Property: `rdf:value`

Property	Value
IRI	<code>rdf:value</code>
Shape IRI	n2be5b758ef2047ccb746d28ad8becc0cb84
Status	experimental ○
Label	value of procedure
Definition	The method value of the procedure.
Scope note	
Implementation	A <code>tern:Procedure</code> <i>MUST</i> have exactly 1 <code>rdf:value</code> predicate with a value of type <code>tern:Method</code> .
Cardinality	Exactly 1
Node kind	
Class type	
Expected values	

4.1.33.4. Property: `tern:hasMethod`

Property	Value
IRI	<code>tern:hasMethod</code>
Shape IRI	n2be5b758ef2047ccb746d28ad8becc0cb85
Status	experimental ○
Label	method of procedure
Definition	The method type of the procedure.
Scope note	
Implementation	If present, <code>tern:hasMethod</code> predicates on a <code>tern:Procedure</code> <i>MUST</i> have values of type <code>tern:Method</code> .
Cardinality	
Node kind	
Class type	
Expected values	

4.1.33.5. Property: void:inDataset

Property	Value
IRI	<code>void:inDataset</code>
Shape IRI	https://w3id.org/tern/shapes/tern/void-inDataset
Status	stable 
Label	in dataset
Definition	A link to the RDF payload's metadata which this resource was a part of.
Scope note	
Implementation	There <i>MUST</i> exist exactly 1 <code>void:inDataset</code> property with an IRI value to a <code>tern:RDFDataset</code> .
Cardinality	Exactly 1
Node kind	<code>sh:IRI</code>
Class type	<code>tern:RDFDataset</code>
Expected values	

4.1.34. Class: tern:RDFDataset

Property	Value
IRI	<code>tern:RDFDataset</code>
Status	stable 
Label	RDFDataset
Definition	A set of RDF triples that are published, maintained or aggregated by a single provider.
Scope note	This is a specialised version of the <code>void:Dataset</code> class where it may be constrained by additional property shapes in the future.

4.1.34.1. Property: dcterms:contributor

Property	Value
IRI	<code>dcterms:contributor</code>
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-contributor
Status	stable 
Label	contributor
Definition	An entity, such as a person, organisation, or service, that is responsible for making contributions to the dataset. The contributor should be described as an RDF resource, rather than just providing the name as a literal.
Scope note	

Property	Value
Implementation	A tern:RDFDataset MAY have a dcterms:contributor predicate where the value node is an IRI.
Cardinality	
Node kind	sh:IRI
Class type	
Expected values	

4.1.34.2. Property: dcterms:created

Property	Value
IRI	dcterms:created
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-created
Status	stable ✓
Label	created
Definition	Date of creation of the dataset. The value should be formatted and data-typed as an xsd:date .
Scope note	
Implementation	A tern:RDFDataset MAY have a dcterms:created predicate where the value node is a literal with the datatype xsd:date .
Cardinality	
Node kind	
Class type	xmlschema#date
Expected values	

4.1.34.3. Property: dcterms:creator

Property	Value
IRI	dcterms:creator
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-creator
Status	stable ✓
Label	creator
Definition	An entity, such as a person, organisation, or service, that is primarily responsible for creating the dataset. The creator should be described as an RDF resource, rather than just providing the name as a literal.
Scope note	
Implementation	A tern:RDFDataset MAY have a dcterms:creator predicate where the value node is an IRI.

Property	Value
Cardinality	
Node kind	sh:IRI
Class type	
Expected values	

4.1.34.4. Property: dcterms:date

Property	Value
IRI	dcterms:date
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-date
Status	stable 
Label	date
Definition	A point or period of time associated with an event in the life-cycle of the resource. The value should be formatted and data-typed as an xsd:date .
Scope note	
Implementation	A tern:RDFDataset MAY have a dcterms:date predicate where the value node is a literal with the datatype xsd:date .
Cardinality	
Node kind	
Class type	xmlschema#:date
Expected values	

4.1.34.5. Property: dcterms:issued

Property	Value
IRI	dcterms:issued
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-issued
Status	stable 
Label	issued
Definition	Date of formal issuance (e.g., publication) of the dataset. The value should be formatted and datatyped as an xsd:date .
Scope note	
Implementation	A tern:RDFDataset MAY have a dcterms:issued predicate where the value node is a literal with the datatype xsd:date .
Cardinality	
Node kind	
Class type	xmlschema#:date

Property	Value
Expected values	

4.1.34.6. Property: `dcterms:license`

Property	Value
IRI	<code>dcterms:license</code>
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-license
Status	stable 
Label	license
Definition	A legal document giving official permission to do something with the resource.
Scope note	
Implementation	A <code>tern:RDFDataset</code> MAY have a <code>dcterms:license</code> predicate where the value node is an IRI.
Cardinality	
Node kind	<code>sh:IRI</code>
Class type	
Expected values	

4.1.34.7. Property: `dcterms:modified`

Property	Value
IRI	<code>dcterms:modified</code>
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-modified
Status	stable 
Label	modified
Definition	Date on which the dataset was changed. The value should be formatted and datatyped as an <code>xsd:date</code> .
Scope note	
Implementation	A <code>tern:RDFDataset</code> MAY have a <code>dcterms:modified</code> predicate where the value node is a literal with the datatype <code>xsd:date</code> .
Cardinality	
Node kind	
Class type	<code>xmlschema#:date</code>
Expected values	

4.1.34.8. Property: `dcterms:publisher`

Property	Value
IRI	dcterms:publisher
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-publisher
Status	stable 
Label	publisher
Definition	An entity, such as a person, organisation, or service, that is responsible for making the dataset available. The publisher should be described as an RDF resource, rather than just providing the name as a literal.
Scope note	
Implementation	A tern:RDFDataset MAY have a dcterms:publisher predicate where the value node is an IRI.
Cardinality	
Node kind	sh:IRI
Class type	
Expected values	

4.1.34.9. Property: [dcterms:rightsHolder](#)

Property	Value
IRI	dcterms:rightsHolder
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-rightsHolder
Status	stable 
Label	rights holder
Definition	A person or organization owning or managing rights over the resource.
Scope note	
Implementation	A tern:RDFDataset MAY have a dcterms:rightsHolder predicate where the value node is an IRI or literal.
Cardinality	
Node kind	sh:IRIOrLiteral
Class type	
Expected values	

4.1.34.10. Property: [dcterms:source](#)

Property	Value
IRI	dcterms:source
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-source
Status	stable 

Property	Value
Label	source
Definition	A related resource from which the dataset is derived. The source should be described as an RDF resource, rather than as a literal.
Scope note	
Implementation	A tern:RDFDataset <i>MAY</i> have a dcterms:source predicate where the value node is an IRI.
Cardinality	
Node kind	sh:IRI
Class type	
Expected values	

4.1.34.11. Property: dcterms:subject

Property	Value
IRI	dcterms:subject
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-subject
Status	stable 
Label	subject
Definition	A topic of the resource. Recommended practice is to refer to the subject with a URI. If this is not possible or feasible, a literal value that identifies the subject may be provided. Both should preferably refer to a subject in a controlled vocabulary.
Scope note	
Implementation	A tern:RDFDataset <i>MAY</i> have a dcterms:subject predicate where the value node is an IRI or literal.
Cardinality	
Node kind	sh:IRIOrLiteral
Class type	
Expected values	

4.1.34.12. Property: void:subset

Property	Value
IRI	void:subset
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-subset
Status	stable 
Label	subset

Property	Value
Definition	The <code>void:subset</code> property can be used to provide descriptions of parts of a dataset. A part of a dataset is itself a <code>void:Dataset</code>, and any of the annotations for datasets listed in this guide can be applied to the subset. Reasons for subdividing a dataset might include: - Parts have different provenance (different <code>dcterms:source</code>) - Parts have different publication dates (different <code>dcterms:date</code>) - Parts are accesible through different SPARQL endpoints (different <code>void:sparqlEndpoint</code>) - Parts are about different topics (different <code>dcterms:subject</code>) - Parts can be downloaded separately in different RDF dumps (different <code>void:dataDump</code>)
Scope note	
Implementation	A <code>tern:RDFDataset</code> MAY have a <code>void:subset</code> predicate where the value node is an IRI of type <code>void:Dataset</code> .
Cardinality	
Node kind	<code>sh:IRI</code>
Class type	<code>void#:Dataset</code>
Expected values	

4.1.34.13. Property: `dcterms:title`

Property	Value
IRI	<code>dcterms:title</code>
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-title
Status	<code>stable</code> 
Label	title
Definition	The name of the dataset.
Scope note	
Implementation	A <code>tern:RDFDataset</code> MAY have a <code>dcterms:title</code> predicate where the value node is a literal with a datatype <code>xsd:string</code> .
Cardinality	
Node kind	
Class type	<code>xmlschema#:string</code>
Expected values	

4.1.34.14. Property: `void:vocabulary`

Property	Value
IRI	<code>void:vocabulary</code>

Property	Value
Shape IRI	https://w3id.org/tern/shapes/tern/RDFDataset-vocabulary
Status	stable 
Label	vocabulary
Definition	A vocabulary or <code>owl:Ontology</code> whose classes or properties are used in a <code>void:Dataset</code> .
Scope note	
Implementation	A <code>tern:RDFDataset</code> MAY have a <code>void:vocabulary</code> predicate where the value node is an IRI.
Cardinality	
Node kind	<code>sh:IRI</code>
Class type	
Expected values	

4.1.34.15. Property: `dcterms:description`

Property	Value
IRI	<code>dcterms:description</code>
Shape IRI	https://w3id.org/tern/shapes/tern/dcterms-description
Status	stable 
Label	description
Definition	A textual description.
Scope note	
Implementation	A <code>dcterms:description</code> predicate has a literal value with the datatype <code>xsd:string</code> .
Cardinality	
Node kind	
Class type	<code>xmlschema#:string</code>
Expected values	

4.1.34.16. Property: `tern:hasAttribute`

Property	Value
IRI	<code>tern:hasAttribute</code>
Shape IRI	https://w3id.org/tern/shapes/tern/tern-hasAttribute
Status	stable 
Label	has attribute

Property	Value
Definition	Link to an Attribute.
Scope note	
Implementation	A tern:hasAttribute predicate <i>MUST</i> have a blank node or an IRI value of type tern:Attribute .
Cardinality	
Node kind	sh:BlankNodeOrIRI
Class type	tern:Attribute
Expected values	

4.1.35. Class: tern:Survey

Property	Value
IRI	tern:Survey
Status	experimental ○
Label	Survey
Definition	A Survey is an Activity during which Sampling or Observation Activities occur.
Scope note	

4.1.35.1. Property: prov:endedAtTime

Property	Value
IRI	prov:endedAtTime
Shape IRI	https://w3id.org/tern/shapes/tern/prov-endedAtTime
Status	stable ☑
Label	ended at time
Definition	The time at which an activity ended.
Scope note	
Implementation	A tern:Survey , tern:SiteVisit or a tern:Intervention <i>MAY</i> have a maximum of 1 prov:endedAtTime predicate where the value node is a literal with the datatype xsd:dateTime .
Cardinality	Maximum 1
Node kind	sh:Literal
Class type	xmlschema#dateTime
Expected values	

4.1.35.2. Property: prov:qualifiedAssociation

Property	Value
IRI	<code>prov:qualifiedAssociation</code>
Shape IRI	https://w3id.org/tern/shapes/tern/prov-qualifiedAssociation
Status	stable ☑
Label	qualified association
Definition	An activity association is an assignment of responsibility to an agent for an activity, indicating that the agent had a role in the activity. It further allows for a plan to be specified, which is the plan intended by the agent to achieve some goals in the context of this activity.
Scope note	
Implementation	A <code>prov:qualifiedAssociation</code> <i>MUST</i> have a blank node or IRI value of type <code>prov:Association</code> .
Cardinality	
Node kind	<code>sh:BlankNodeOrIRI</code>
Class type	<code>prov#:Association</code>
Expected values	

4.1.35.3. Property: prov:startedAtTime

Property	Value
IRI	<code>prov:startedAtTime</code>
Shape IRI	https://w3id.org/tern/shapes/tern/prov-startedAtTime
Status	stable ☑
Label	started at time
Definition	The time at which an activity started.
Scope note	
Implementation	A <code>tern:Survey</code> , <code>tern:SiteVisit</code> or a <code>tern:Intervention</code> <i>MUST</i> have exactly 1 <code>prov:startedAtTime</code> predicate where the value node is a literal with the datatype <code>xsd:dateTime</code> .
Cardinality	Exactly 1
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#:dateTime</code>
Expected values	

4.1.35.4. Property: prov:wasAssociatedWith

Property	Value
IRI	<code>prov:wasAssociatedWith</code>
Shape IRI	https://w3id.org/tern/shapes/tern/prov-wasAssociatedWith
Status	stable 
Label	was associated with
Definition	An activity association is an assignment of responsibility to an agent for an activity, indicating that the agent had a role in the activity. It further allows for a plan to be specified, which is the plan intended by the agent to achieve some goals in the context of this activity.
Scope note	
Implementation	A <code>prov:wasAssociatedWith</code> predicate <i>MUST</i> an IRI value of type <code>prov:Agent</code> or <code>sdo:Person</code> .
Cardinality	
Node kind	
Class type	<code>prov#:Agent</code> <code>schema.org:Person</code>
Expected values	

4.1.35.5. Property: `void:inDataset`

Property	Value
IRI	<code>void:inDataset</code>
Shape IRI	https://w3id.org/tern/shapes/tern/void-inDataset
Status	stable 
Label	in dataset
Definition	A link to the RDF payload's metadata which this resource was a part of.
Scope note	
Implementation	There <i>MUST</i> exist exactly 1 <code>void:inDataset</code> property with an IRI value to a <code>tern:RDFDataset</code> .
Cardinality	Exactly 1
Node kind	<code>sh:IRI</code>
Class type	<code>tern:RDFDataset</code>
Expected values	

4.1.36. Class: `tern:VerticalExtent`

Property	Value
IRI	<code>tern:VerticalExtent</code>

Property	Value
Status	experimental ○
Label	Vertical Extent
Definition	A class representing the vertical extent of an object or phenomenon in a given context.
Scope note	

4.1.36.1. Property: tern:maxAltitude

Property	Value
IRI	tern:maxAltitude
Shape IRI	https://w3id.org/tern/shapes/tern/tern-maxAltitude
Status	experimental ○
Label	maximum altitude
Definition	This SHACL shape defines constraints for the tern:maxAltitude property. It specifies that values of the tern:maxAltitude property must be literals of type xsd:integer, xsd:float, xsd:double, or xsd:decimal. The status of this shape is experimental, indicating that it might be subject to change in the future.
Scope note	
Implementation	A tern:maxAltitude predicate <i>MUST</i> have a literal value of type xsd:integer, xsd:float, xsd:double, xsd:decimal.
Cardinality	Maximum 1
Node kind	sh:Literal
Class type	xmleschema#:integer xmleschema#:float xmleschema#:double xmleschema#:decimal
Expected values	

4.1.36.2. Property: tern:minAltitude

Property	Value
IRI	tern:minAltitude
Shape IRI	https://w3id.org/tern/shapes/tern/tern-minAltitude
Status	experimental ○
Label	minimum altitude

Property	Value
Definition	This SHACL shape defines constraints for the <code>tern:minAltitude</code> property. It specifies that values of the <code>tern:minAltitude</code> property must be literals of type <code>xsd:integer</code> , <code>xsd:float</code> , <code>xsd:double</code> , or <code>xsd:decimal</code> . The status of this shape is experimental, indicating that it might be subject to change in the future.
Scope note	
Implementation	A <code>tern:minAltitude</code> predicate <i>MUST</i> have a literal value of type <code>xsd:integer</code> , <code>xsd:float</code> , <code>xsd:double</code> , <code>xsd:decimal</code> .
Cardinality	Maximum 1
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#integer</code> <code>xmlschema#float</code> <code>xmlschema#double</code> <code>xmlschema#decimal</code>
Expected values	

4.1.36.3. Property: `tern:unit`

Property	Value
IRI	<code>tern:unit</code>
Shape IRI	https://w3id.org/tern/shapes/tern/tern-unit
Status	<code>stable</code> 
Label	unit of measure
Definition	The unit of measure of the value. Recommended best practice is to use the QUDT units of measure vocabulary .
Scope note	
Implementation	A <code>tern:unit</code> predicate <i>MUST</i> have an IRI value.
Cardinality	Maximum 1
Node kind	<code>sh:IRI</code>
Class type	
Expected values	

4.2. External Classes

4.2.1. Class: `prov:Association`

Property	Value
IRI	<code>prov:Association</code>
Status	<code>stable</code> 

Property	Value
Label	Association
Definition	An activity association is an assignment of responsibility to an agent for an activity, indicating that the agent had a role in the activity. It further allows for a plan to be specified, which is the plan intended by the agent to achieve some goals in the context of this activity.
Scope note	Associate an agent to an activity (tern:Sampling , tern:Observation) with a role from ISO 19115-1's CI Role Code .

4.2.1.1. Property: prov:agent

Property	Value
IRI	prov:agent
Shape IRI	https://w3id.org/tern/shapes/tern/Association-agent
Status	stable ☑
Label	agent
Definition	An agent is something that bears some form of responsibility for an activity taking place, for the existence of an entity, or for another agent's activity.
Scope note	
Implementation	A prov:Association <i>MUST</i> have exactly 1 prov:agent predicate where the value node is an IRI of an individual with the type prov:Agent .
Cardinality	Exactly 1
Node kind	sh:IRI
Class type	prov#:Agent
Expected values	

4.2.1.2. Property: prov:hadPlan

Property	Value
IRI	prov:hadPlan
Shape IRI	https://w3id.org/tern/shapes/tern/Association-hadPlan
Status	stable ☑
Label	had plan
Definition	A plan is an entity that represents a set of actions or steps intended by one or more agents to achieve some goals.
Scope note	Associate a plan to the agent which they use for their role in some activity. This may or may not be the same as the procedure of a tern:Sampling or a tern:Observation depending on the role of the agent.

Property	Value
Implementation	A <code>prov:Association</code> <i>MAY</i> have some <code>prov:hadPlan</code> predicate where the value node is an IRI.
Cardinality	
Node kind	<code>sh:IRI</code>
Class type	
Expected values	

4.2.1.3. Property: `prov:hadRole`

Property	Value
IRI	<code>prov:hadRole</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Association-hadRole
Status	<code>stable</code> ☑
Label	had role
Definition	<code>prov:hadRole</code> references the Role (i.e. the function of an entity with respect to an activity), in the context of an instantaneous usage, generation, association, start, and end.
Scope note	
Implementation	A <code>prov:Association</code> <i>MUST</i> have exactly 1 <code>prov:hadRole</code> predicate where the value node is an IRI of a controlled concept from ISO 19115-1's CI Role Code .
Cardinality	Exactly 1
Node kind	<code>sh:IRI</code>
Class type	

Property	Value
Expected values	- author - co author - collaborator - contributor - custodian - distributor - editor - funder - mediator - originator - owner - point of contact - principal investigator - processor - publisher - resource provider - rights holder - sponsor - stakeholder - user

4.2.1.4. prov:Association example

The RDF example below illustrates how to:

- associate a `schema:Person` to an instance of `tern:Sampling` activity with the role *principal investigator*
- associate an `schema:Organization` to a `tern:MaterialSample` with the role *custodian*.

```

<org-1>
  a schema:Organization ;
  schema:name "Org 1" ;
  .

<person-1>
  a schema:Person ;
  schema:name "Person 1" ;
  schema:affiliation <org-1> ;
  .

<site-visit>
  a tern:SiteVisit ;
  prov:startedAtTime "2015-03-22T13:00:00+00:00"^^xsd:dateTime ;
  tern:hasSite <...> ;
  prov:wasAssociatedWith <person-1> ;
  prov:qualifiedAssociation [
    a prov:Association ;
  ]

```

```

        prov:agent <person-1> ;
        prov:hadRole <http://def.isotc211.org/iso19115/-
1/2014/CitationAndResponsiblePartyInformation/code/CI_RoleCode/principalInvestigator>
;
    ] ;
.

<sampling-1>
    a tern:Sampling ;
    ... ;
    tern:hasSiteVisit <site-visit> ;
    prov:wasAssociatedWith <person-1> ;
    prov:qualifiedAssociation [
        a prov:Association ;
        prov:agent <person-1> ;
        prov:hadRole <http://def.isotc211.org/iso19115/-
1/2014/CitationAndResponsiblePartyInformation/code/CI_RoleCode/resourceProvider> ;
    ] ;
    sosa:hasResult <soil-sample-1> ;
.

<soil-sample-1>
    a tern:MaterialSample ;
    ... ;
    sosa:isResultOf <sampling-1> ;
    prov:wasAttributedTo <org-1> ;
    prov:qualifiedAttribution [
        a prov:Attribution ;
        prov:agent <org-1> ;
        prov:hadRole <http://def.isotc211.org/iso19115/-
1/2014/CitationAndResponsiblePartyInformation/code/CI_RoleCode/custodian> ;
    ]
.

```

4.2.2. Class: prov:Attribution

Property	Value
IRI	<code>prov:Attribution</code>
Status	stable 
Label	Attribution
Definition	Attribution is the ascribing of an entity to an agent. When an entity e is attributed to agent ag , entity e was generated by some unspecified activity that in turn was associated to agent ag . Thus, this relation is useful when the activity is not known, or irrelevant.
Scope note	Associate an agent to an entity (<code>tern:Sample</code> , <code>tern:FeatureOfInterest</code> , <code>tern:Site</code>) with a role from ISO 19115-1's CI Role Code .

4.2.2.1. Property: prov:agent

Property	Value
IRI	<code>prov:agent</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Attribution-agent
Status	stable 
Label	agent
Definition	An agent is something that bears some form of responsibility for an activity taking place, for the existence of an entity, or for another agent's activity.
Scope note	
Implementation	A <code>prov:Attribution</code> <i>MUST</i> have exactly 1 <code>prov:agent</code> predicate where the value node is an IRI of an individual with the type <code>prov:Agent</code> .
Cardinality	Exactly 1
Node kind	<code>sh:IRI</code>
Class type	<code>prov#:Agent</code>
Expected values	

4.2.2.2. Property: prov:hadRole

Property	Value
IRI	<code>prov:hadRole</code>
Shape IRI	https://w3id.org/tern/shapes/tern/Attribution-hadRole
Status	stable 
Label	had role
Definition	<code>prov:hadRole</code> references the Role (i.e. the function of an entity with respect to an activity), in the context of an instantaneous usage, generation, association, start, and end.
Scope note	
Implementation	A <code>prov:Attribution</code> <i>MUST</i> have exactly 1 <code>prov:hadRole</code> predicate where the value node is an IRI of a controlled concept from ISO 19115-1's CI Role Code .
Cardinality	Exactly 1
Node kind	<code>sh:IRI</code>
Class type	

Property	Value
Expected values	- author - co author - collaborator - contributor - custodian - distributor - editor - funder - mediator - originator - owner - point of contact - principal investigator - processor - publisher - resource provider - rights holder - sponsor - stakeholder - user

4.2.3. Class: **time:Duration**

Property	Value
IRI	time:Duration
Status	stable 
Label	Duration
Definition	Duration of a temporal extent expressed as a number scaled by a temporal unit
Scope note	

4.2.3.1. Property: **time:numericDuration**

Property	Value
IRI	time:numericDuration
Shape IRI	https://w3id.org/tern/shapes/tern/time-numericDuration
Status	stable 
Label	numeric duration
Definition	Value of a temporal extent expressed as a decimal number scaled by a temporal unit
Scope note	

Property	Value
Implementation	A time:Duration <i>MUST</i> have exactly 1 time:numericDuration predicate where the value node is a literal with a datatype of xsd:decimal .
Cardinality	Exactly 1
Node kind	
Class type	xmlschema#:decimal
Expected values	

4.2.3.2. Property: time:unitType

Property	Value
IRI	time:unitType
Shape IRI	https://w3id.org/tern/shapes/tern/time-unitType
Status	stable ☑
Label	unit type
Definition	The temporal unit which provides the precision of a date-time value or scale of a temporal extent.
Scope note	
Implementation	A time:Duration <i>MUST</i> have exactly 1 time:unitType predicate where the value node is an IRI from a controlled list.
Cardinality	Exactly 1
Node kind	sh:IRI
Class type	
Expected values	- day - hour - minute - month - second - week - year

4.2.4. Class: time:Instant

Property	Value
IRI	time:Instant
Status	stable ☑
Label	Instant
Definition	A temporal entity with zero extent or duration.

Property	Value
Implementation	One or more of [<code>time:inXSDDate</code> , <code>time:inXSDDateTimeStamp</code> , <code>time:inXSDgYear</code> , <code>time:inXSDgYearMonth</code> , <code>time:inTimePosition</code> , and <code>time:inDateTime</code>] <i>MUST</i> be present.
Scope note	

4.2.4.1. Property: `time:inDateTime`

Property	Value
IRI	<code>time:inDateTime</code>
Shape IRI	https://w3id.org/tern/shapes/tern/time-Instant-inDateTime
Status	stable ☑
Label	in date-time
Definition	Position of an instant, expressed using a structured description.
Scope note	
Implementation	Value <i>MUST</i> be a literal with a datatype of <code>xsd:dateTime</code> . Maximum of one value is allowed for this property.
Cardinality	Maximum 1
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#:dateTime</code>
Expected values	

4.2.4.2. Property: `time:inTimePosition`

Property	Value
IRI	<code>time:inTimePosition</code>
Shape IRI	https://w3id.org/tern/shapes/tern/time-inTimePosition
Status	stable ☑
Label	in time position
Definition	Position of a time instant expressed as a <code>TimePosition</code> .
Scope note	
Implementation	Value <i>MUST</i> be an instance of <code>time:TimePosition</code> . Maximum of one value is allowed for this property. The value node <i>MUST</i> be a blank node or IRI.
Cardinality	Maximum 1
Node kind	<code>sh:BlankNodeOrIRI</code>
Class type	<code>time#:TimePosition</code>
Expected values	

4.2.4.3. Property: time:inXSDDate

Property	Value
IRI	<code>time:inXSDDate</code>
Shape IRI	https://w3id.org/tern/shapes/tern/time-inXSDDate
Status	stable 
Label	in XSD date
Definition	Position of an instant, expressed using <code>xsd:date</code> .
Scope note	
Implementation	Value <i>MUST</i> be a literal with a datatype of <code>xsd:date</code> . Maximum of one value is allowed for this property.
Cardinality	Maximum 1
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#:date</code>
Expected values	

4.2.4.4. Property: time:inXSDDateTimeStamp

Property	Value
IRI	<code>time:inXSDDateTimeStamp</code>
Shape IRI	https://w3id.org/tern/shapes/tern/time-inXSDDateTimeStamp
Status	stable 
Label	in XSD date-time-stamp
Definition	Position of an instant, expressed using <code>xsd:dateTimeStamp</code> .
Scope note	
Implementation	Value <i>MUST</i> be a literal with a datatype of <code>xsd:dateTimeStamp</code> . Maximum of one value is allowed for this property.
Cardinality	Maximum 1
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#:dateTimeStamp</code>
Expected values	

4.2.4.5. Property: time:inXSDgYear

Property	Value
IRI	<code>time:inXSDgYear</code>
Shape IRI	https://w3id.org/tern/shapes/tern/time-inXSDgYear
Status	stable 

Property	Value
Label	in XSD g-year
Definition	Position of an instant, expressed using <code>xsd:gYear</code> .
Scope note	
Implementation	Value <i>MUST</i> be a literal with a datatype of <code>xsd:gYear</code> . Maximum of one value is allowed for this property.
Cardinality	Maximum 1
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#gYear</code>
Expected values	

4.2.4.6. Property: `time:inXSDgYearMonth`

Property	Value
IRI	<code>time:inXSDgYearMonth</code>
Shape IRI	https://w3id.org/tern/shapes/tern/time-inXSDgYearMonth
Status	<code>stable</code> 
Label	in XSD g-year-month
Definition	Position of an instant, expressed using <code>xsd:gYearMonth</code> .
Scope note	
Implementation	Value <i>MUST</i> be a literal with a datatype of <code>xsd:gYearMonth</code> . Maximum of one value is allowed for this property.
Cardinality	Maximum 1
Node kind	<code>sh:Literal</code>
Class type	<code>xmlschema#gYearMonth</code>
Expected values	

4.2.5. Class: `time:Interval`

Property	Value
IRI	<code>time:Interval</code>
Status	<code>stable</code> 
Label	Interval
Definition	A temporal entity with an extent or duration.
Scope note	

4.2.5.1. Property: time:hasBeginning

Property	Value
IRI	<code>time:hasBeginning</code>
Shape IRI	https://w3id.org/tern/shapes/tern/time-hasBeginning
Status	stable 
Label	has beginning
Definition	Beginning of a temporal entity.
Scope note	
Implementation	A <code>time:hasBeginning</code> predicate <i>MUST</i> exist where the value node is a blank node or IRI of type <code>time:Instant</code> .
Cardinality	Exactly 1
Node kind	<code>sh:BlankNodeOrIRI</code>
Class type	<code>time#:Instant</code>
Expected values	

4.2.5.2. Property: time:hasDuration

Property	Value
IRI	<code>time:hasDuration</code>
Shape IRI	https://w3id.org/tern/shapes/tern/time-hasDuration
Status	stable 
Label	has duration
Definition	Duration of a temporal entity, event or activity, or thing, expressed as a scaled value.
Scope note	
Implementation	A <code>time:hasDuration</code> <i>MAY</i> exist where the value node is a blank node or IRI of type <code>time:Duration</code> .
Cardinality	Maximum 1
Node kind	<code>sh:BlankNodeOrIRI</code>
Class type	<code>time#:Duration</code>
Expected values	

4.2.5.3. Property: time:hasEnd

Property	Value
IRI	<code>time:hasEnd</code>
Shape IRI	https://w3id.org/tern/shapes/tern/time-hasEnd

Property	Value
Status	stable 
Label	has end
Definition	End of a temporal entity.
Scope note	
Implementation	A <code>time:hasEnd</code> predicate <i>MUST</i> exist where the value node is a blank node or IRI of type <code>time:Instant</code> .
Cardinality	Exactly 1
Node kind	<code>sh:BlankNodeOrIRI</code>
Class type	<code>time#:Instant</code>
Expected values	

5. References

[PROF]

The Profiles Vocabulary, Nicholas J Car; Rob Atkinson. 18 December 2019. W3C Working Group Note. URL: <https://www.w3.org/TR/dx-prof/>

[prov-o]

SPROV-O: The PROV Ontology. Timothy Lebo; Satya Sahoo; Deborah McGuinness. 30 April 2013. W3C Recommendation. URL: <https://www.w3.org/TR/prov-o/>

[vocab-ssn]

Semantic Sensor Network Ontology. Armin Haller; Krzysztof Janowicz; Simon Cox; Danh Le Phuoc; Kerry Taylor; Maxime Lefrançois. 19 October 2017. W3C Recommendation. URL: <https://www.w3.org/TR/vocab-ssn/>

[vocab-ssn-ext]

Extensions to the Semantic Sensor Network Ontology. Simon Cox. 16 January 2020. W3C Working Draft. URL: <https://www.w3.org/TR/vocab-ssn-ext/>

Annex A: Specification Parts



This Annex is normative.

TBD.